

# Package ‘target’

October 17, 2020

**Type** Package

**Title** Predict Combined Function of Transcription Factors

**Version** 1.2.0

**Description** Implement the BETA algorithm for inferring direct target genes from DNA-binding and perturbation expression data Wang et al. (2013) <doi: 10.1038/nprot.2013.150>. Extend the algorithm to predict the combined function of two DNA-binding elements from comparable binding and expression data.

**URL** <https://github.com/MahShaaban/target>

**BugReports** <https://github.com/MahShaaban/target/issues>

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 3.6)

**Imports** BiocGenerics, GenomicRanges, IRanges, matrixStats, methods, stats, graphics, shiny

**Suggests** testthat (>= 2.1.0), knitr, rmarkdown, shinytest, shinyBS, covr

**VignetteBuilder** knitr

**RoxygenNote** 6.1.1

**biocViews** Software, StatisticalMethod, Transcription

**git\_url** <https://git.bioconductor.org/packages/target>

**git\_branch** RELEASE\_3\_11

**git\_last\_commit** 8156625

**git\_last\_commit\_date** 2020-04-27

**Date/Publication** 2020-10-16

**Author** Mahmoud Ahmed [aut, cre]

**Maintainer** Mahmoud Ahmed <mahmoud.s.fahmy@students.kasralainy.edu.eg>

## R topics documented:

|                            |    |
|----------------------------|----|
| associated_peaks . . . . . | 2  |
| direct_targets . . . . .   | 3  |
| find_distance . . . . .    | 3  |
| merge_ranges . . . . .     | 4  |
| plot_predictions . . . . . | 5  |
| rank_product . . . . .     | 5  |
| real_peaks . . . . .       | 6  |
| real_transcripts . . . . . | 7  |
| score_peaks . . . . .      | 8  |
| score_regions . . . . .    | 8  |
| sim_peaks . . . . .        | 9  |
| sim_transcripts . . . . .  | 10 |
| target . . . . .           | 10 |
| target_app . . . . .       | 11 |
| test_predictions . . . . . | 11 |

|              |           |
|--------------|-----------|
| <b>Index</b> | <b>13</b> |
|--------------|-----------|

---

|                  |                                 |
|------------------|---------------------------------|
| associated_peaks | <i>Predict associated peaks</i> |
|------------------|---------------------------------|

---

### Description

This function selects overlapping peaks and regions, calculates the distance between them and score each peak.

### Usage

```
associated_peaks(peaks, regions, regions_col, base = 1e+05)
```

### Arguments

|             |  |
|-------------|--|
| peaks       | A GRanges object                               |
| regions     | A GRanges object                               |
| regions_col | A character string                             |
| base        | An integer to calculate distances relative to. |

### Value

A GRanges object. A similar object to peaks with three added metadata columns.

### Examples

```
# load peaks and transcripts data
data("real_peaks")
data("real_transcripts")

# associated peaks
ap <- associated_peaks(real_peaks, real_transcripts, 'name2')
```

---

|                |                               |
|----------------|-------------------------------|
| direct_targets | <i>Predict direct targets</i> |
|----------------|-------------------------------|

---

**Description**

This function selects overlapping peaks and regions, calculates the distance between them, score each peak and region and calculate rank products of the regions.

**Usage**

```
direct_targets(peaks, regions, regions_col, stats_col, base = 1e+05)
```

**Arguments**

|             |  |
|-------------|--|
| peaks       | A GRanges object                               |
| regions     | A GRanges object                               |
| regions_col | A character string                             |
| stats_col   | A character string                             |
| base        | An integer to calculate distances relative to. |

**Value**

A GRanges object. A similar object to regions with several added metadata columns.

**Examples**

```
# load peaks and transcripts data
data("real_peaks")
data("real_transcripts")

# direct targets
dt <- direct_targets(real_peaks, real_transcripts, 'name2', 't')
```

---

|               |  |
|---------------|--|
| find_distance | <i>Find the distance between peaks and regions</i> |
|---------------|--|

---

**Description**

Calculate the distance between the elements of two GRanges objects.

**Usage**

```
find_distance(peaks, regions, how = "center")
```

**Arguments**

|         |                                      |
|---------|--------------------------------------|
| peaks   | A GRanges object                     |
| regions | A GRanges object                     |
| how     | A character string, default 'center' |

**Value**

A vector of integers

**Examples**

```
library(IRanges)

query <- IRanges(c(1, 4, 9), c(5, 7, 10))
subject <- IRanges(c(2, 2, 10), c(2, 3, 12))
find_distance(query, subject)
```

---

merge\_ranges

*Merge peaks and regions GRanges*

---

**Description**

Merge two GRanges objects by overlaps

**Usage**

```
merge_ranges(peaks, regions)
```

**Arguments**

|         |                  |
|---------|------------------|
| peaks   | A GRanges object |
| regions | A GRanges object |

**Value**

A DataFrame

**Examples**

```
library(IRanges)

query <- IRanges(c(1, 4, 9), c(5, 7, 10))
subject <- IRanges(c(2, 2, 10), c(2, 3, 12))
mergeByOverlaps(query, subject)
```

---

|                  |   |
|------------------|---|
| plot_predictions | <i>Plot the ECDF of ranks by groups</i> |
|------------------|---|

---

**Description**

Plot the cumulative distribution function of choosen value (e.g. ranks) by a factor of the same length, group. Each group is given a color and a label.

**Usage**

```
plot_predictions(rank, group, colors, labels, ...)
```

**Arguments**

|        |  |
|--------|--|
| rank   | A numeric vector   |
| group  | A factor of length equal that of rank                          |
| colors | A character vector of colors for each group                    |
| labels | A character vector of length equal the unique values in groups |
| ...    | Other arguments passed to points                               |

**Value**

NULL.

**Examples**

```
# generate random values
rn1 <- rnorm(100)
rn2 <- rnorm(100, 2)
e <- c(rn1, rn2)

# generate grouping variable
g <- rep(c('up', 'down'), times = c(length(rn1), length(rn2)))

plot_predictions(e,
                 group = g,
                 colors = c('red', 'green'),
                 labels = c('up', 'down'))
```

---

|              |  |
|--------------|--|
| rank_product | <i>Calculate the regions rank products</i> |
|--------------|--|

---

**Description**

Calculate the rank products of the rank of the distances and the statistics.

**Usage**

```
rank_product(region_score, region_stat, region_id)
```

**Arguments**

region\_score    A vector of numerics  
region\_stat     A vector of numerics  
region\_id       A vector of characters

**Value**

A vector of numerics

**Examples**

```
library(IRanges)

query <- IRanges(c(1, 4, 9), c(5, 7, 10))
subject <- IRanges(c(2, 2, 10), c(2, 3, 12))
distance <- find_distance(query, subject)
peak_score <- score_peaks(distance, 100000)
region_id <- c('region1', 'region1', 'region2')
region_score <- score_regions(peak_score, region_id)
region_stat <- c(30, 30, -40)
rank_product(region_score, region_stat, region_id)
```

---

|            |                                    |
|------------|------------------------------------|
| real_peaks | <i>AR peaks in LNCaP cell line</i> |
|------------|------------------------------------|

---

**Description**

Androgen receptor peaks from ChIP-Seq experiment in the LNCaP cell line.

**Usage**

```
real_peaks
```

**Format**

A GRanges

**Source**

[https://github.com/suwangbio/BETA/blob/master/BETA\\_test\\_data/3656\\_peaks.bed](https://github.com/suwangbio/BETA/blob/master/BETA_test_data/3656_peaks.bed)

**See Also**

[real\\_transcripts](#)

[sim\\_peaks](#)

## Examples

```
# load data
data('real_peaks')

# locate the raw data
system.file('extdata', '3656_peaks.bed.gz', package = 'target')

# locate the source code for preparing the data
system.file('extdata', 'make-data.R', package = 'target')
```

---

real\_transcripts

*Differential expression of DHT treated LNCaP cell line*

---

## Description

The differential expression analysis output of LNCaP cell line treated with DHT for 16 hours compared to non-treated cells. The REFSEQ transcript identifiers were used to merge the data.frame with the transcript coordinates from the hg19 reference genome.

## Usage

```
real_transcripts
```

## Format

A GRanges

## Source

[https://github.com/suwangbio/BETA/blob/master/BETA\\_test\\_data/AR\\_diff\\_expr.xls](https://github.com/suwangbio/BETA/blob/master/BETA_test_data/AR_diff_expr.xls)

[https://github.com/suwangbio/BETA/blob/master/BETA\\_1.0.7/BETA/references/hg19.refseq](https://github.com/suwangbio/BETA/blob/master/BETA_1.0.7/BETA/references/hg19.refseq)

## See Also

[real\\_peaks](#)

[sim\\_transcripts](#)

## Examples

```
# load data
data('real_transcripts')

# locate the raw data
system.file('extdata', 'AR_diff_expr.tsv.gz', package = 'target')
system.file('extdata', 'hg19.refseq', package = 'target')

# locate the source code for preparing the data
system.file('extdata', 'make-data.R', package = 'target')
```

---

|             |                              |
|-------------|------------------------------|
| score_peaks | <i>Calculate peak scores</i> |
|-------------|------------------------------|

---

**Description**

Calculate the peak score based on the distance to a region of interest.

**Usage**

```
score_peaks(distance, base)
```

**Arguments**

|          |  |
|----------|--|
| distance | A vector of integers                           |
| base     | An integer to calculate distances relative to. |

**Value**

A vector of integers

**Examples**

```
library(IRanges)

query <- IRanges(c(1, 4, 9), c(5, 7, 10))
subject <- IRanges(c(2, 2, 10), c(2, 3, 12))
distance <- find_distance(query, subject)
score_peaks(distance, 100000)
```

---

|               |                                |
|---------------|--------------------------------|
| score_regions | <i>Calculate region scores</i> |
|---------------|--------------------------------|

---

**Description**

Calculate the region score based on the distance to their assigned peaks.

**Usage**

```
score_regions(peak_score, region_id)
```

**Arguments**

|            |                       |
|------------|-----------------------|
| peak_score | A vector of integers  |
| region_id  | A vector of character |

**Value**

A vector of numerics

**Examples**

```
library(IRanges)

query <- IRanges(c(1, 4, 9), c(5, 7, 10))
subject <- IRanges(c(2, 2, 10), c(2, 3, 12))
distance <- find_distance(query, subject)
peak_score <- score_peaks(distance, 100000)
region_id <- c('region1', 'region1', 'region2')
region_score <- score_regions(peak_score, region_id)
```

---

|           |                        |
|-----------|------------------------|
| sim_peaks | <i>Simulated peaks</i> |
|-----------|------------------------|

---

**Description**

is randomly generated peaks with random distances from the transcripts start sites (TSS) of chromosome 1 of the mm10 mouse genome.

**Usage**

```
sim_peaks
```

**Format**

A GRanges

**See Also**

[real\\_peaks](#)

[sim\\_transcripts](#)

**Examples**

```
# load data
data('sim_peaks')

# locate the source code for preparing the data
system.file('extdata', 'make-data.R', package = 'target')
```

---

|                 |  |
|-----------------|--|
| sim_transcripts | <i>Simulated transcripts The transcripts chromosome 1 of the mm10 mouse genome with randomly singed statistics assigned to each.</i> |
|-----------------|--|

---

### Description

Simulated transcripts The transcripts chromosome 1 of the mm10 mouse genome with randomly singed statistics assigned to each.

### Usage

```
sim_transcripts
```

### Format

A GRanges

### See Also

[real\\_transcripts](#)

[sim\\_transcripts](#)

### Examples

```
# load data
data('sim_transcripts')

# locate the source code for preparing the data
system.file('extdata', 'make-data.R', package = 'target')
```

---

|        |  |
|--------|--|
| target | target: <i>Predict Combined Function of Transcription Factors.</i> |
|--------|--|

---

### Description

Implement the BETA algorithm for inferring direct target genes from DNA-binding and perturbation expression data Wang et al. (2013) <doi: 10.1038/nprot.2013.150>. Extend the algorithm to predict the combined effect of two DNA-binding elements from comprable binding and expression data.

### Details

Predicting associated peaks and direct targets

[associated\\_peaks](#) [direct\\_targets](#)

Plotting and testing predictions [plot\\_predictions](#) [test\\_predictions](#)

Internal target functions: [merge\\_ranges](#) [find\\_distance](#) [score\\_peaks](#) [score\\_regions](#) [rank\\_product](#)

---

|            |                          |
|------------|--------------------------|
| target_app | <i>Run the shiny App</i> |
|------------|--------------------------|

---

**Description**

Run the shiny App

**Usage**

```
target_app()
```

**Value**

Runs the shiny app

---

|                  |   |
|------------------|---|
| test_predictions | <i>Test the ECDF ranks of groups are from same distribution</i> |
|------------------|---|

---

**Description**

Test whether the cumulative distribution function of two groups are drawn from the same distribution.

**Usage**

```
test_predictions(rank, group, compare, ...)
```

**Arguments**

|         |                                       |
|---------|---------------------------------------|
| rank    | A numeric vector                      |
| group   | A factor of length equal that of rank |
| compare | A character vector of length two      |
| ...     | Other arguments passed to ks.test     |

**Value**

An htest object

**Examples**

```
# generate random values
rn1 <- rnorm(100)
rn2 <- rnorm(100, 2)
e <- c(rn1, rn2)

# generate grouping variable
g <- rep(c('up', 'down'), times = c(length(rn1), length(rn2)))

# test
test_predictions(e,
```

```
group = g,  
compare = c('up', 'down'))
```

# Index

## \* datasets

- real\_peaks, [6](#)
- real\_transcripts, [7](#)
- sim\_peaks, [9](#)
- sim\_transcripts, [10](#)

associated\_peaks, [2](#), [10](#)

direct\_targets, [3](#), [10](#)

find\_distance, [3](#), [10](#)

merge\_ranges, [4](#), [10](#)

plot\_predictions, [5](#), [10](#)

rank\_product, [5](#), [10](#)

real\_peaks, [6](#), [7](#), [9](#)

real\_transcripts, [6](#), [7](#), [10](#)

score\_peaks, [8](#), [10](#)

score\_regions, [8](#), [10](#)

sim\_peaks, [6](#), [9](#)

sim\_transcripts, [7](#), [9](#), [10](#), [10](#)

target, [10](#)

target-package (target), [10](#)

target\_app, [11](#)

test\_predictions, [10](#), [11](#)