

Package ‘idr2d’

October 18, 2022

Title Irreproducible Discovery Rate for Genomic Interactions Data

Version 1.10.0

Description A tool to measure reproducibility between genomic experiments that produce two-dimensional peaks (interactions between peaks), such as ChIA-PET, HiChIP, and HiC. idr2d is an extension of the original idr package, which is intended for (one-dimensional) ChIP-seq peaks.

License MIT + file LICENSE

URL <https://idr2d.mit.edu>

Depends R (>= 3.6)

Imports dplyr (>= 0.7.6), futile.logger (>= 1.4.3), GenomeInfoDb (>= 1.14.0), GenomicRanges (>= 1.30), ggplot2 (>= 3.1.1), grDevices, grid, idr (>= 1.2), IRanges (>= 2.18.0), magrittr (>= 1.5), methods, reticulate (>= 1.13), scales (>= 1.0.0), stats, stringr (>= 1.3.1), utils

Suggests DT (>= 0.4), htmltools (>= 0.3.6), knitr (>= 1.20), rmarkdown (>= 1.10), roxygen2 (>= 6.1.0), testthat (>= 2.1.0)

VignetteBuilder knitr

biocViews DNA3DStructure, GeneRegulation, PeakDetection, Epigenetics, FunctionalGenomics, Classification, HiC

Encoding UTF-8

RoxygenNote 7.1.0

SystemRequirements Python (>= 3.5.0), hic-straw

git_url <https://git.bioconductor.org/packages/idr2d>

git_branch RELEASE_3_15

git_last_commit f92649a

git_last_commit_date 2022-04-26

Date/Publication 2022-10-18

Author Konstantin Krismer [aut, cre, cph]

(<<https://orcid.org/0000-0001-8994-3416>>),

David Gifford [ths, cph] (<<https://orcid.org/0000-0003-1709-4034>>)

Maintainer Konstantin Krismer <krismer@mit.edu>

R topics documented:

calculate_midpoint_distance1d	2
calculate_midpoint_distance2d	3
calculate_relative_overlap1d	5
calculate_relative_overlap2d	6
chiapet	8
chipseq	8
determine_anchor_overlap	9
draw_hic_contact_map	10
draw_idr_distribution_histogram	11
draw_rank_idr_scatterplot	12
draw_value_idr_scatterplot	13
establish_bijection	14
establish_bijection1d	15
establish_bijection2d	17
establish_overlap1d	19
establish_overlap2d	20
estimate_idr	22
estimate_idr1d	24
estimate_idr2d	27
estimate_idr2d_hic	29
hic	31
parse_hic_pro_matrix	33
parse_juicer_matrix	33
preprocess	35
remove_nonstandard_chromosomes1d	36
remove_nonstandard_chromosomes2d	37
Index	38

calculate_midpoint_distance1d

Distance between Midpoints of two Peaks

Description

Calculates the distance in nucleotides between the midpoints of two peaks.

Note: peaks must be on the same chromosome; start coordinate is always less than end coordinate

Usage

```
calculate_midpoint_distance1d(peak1_start, peak1_end, peak2_start, peak2_end)
```

Arguments

peak1_start integer vector; genomic start coordinate(s) of peak in replicate 1
 peak1_end integer vector; genomic end coordinate(s) of peak in replicate 1
 peak2_start integer vector; genomic start coordinate(s) of peak in replicate 2
 peak2_end integer vector; genomic end coordinate(s) of peak in replicate 2

Value

positive integer vector; distances between peak pairs

Examples

```
# identical, zero distance
calculate_midpoint_distance1d(100, 120,
                             100, 120)

# centered, zero distance
calculate_midpoint_distance1d(100, 120,
                             90, 130)

# off by 10 per anchor
calculate_midpoint_distance1d(100, 120,
                             110, 130)

# vectorized example
calculate_midpoint_distance1d(c(100, 100, 100),
                             c(120, 120, 120),
                             c(100, 90, 110),
                             c(120, 130, 130))
```

calculate_midpoint_distance2d

Distance between Anchor Midpoints of two Interactions

Description

Calculates the distance in nucleotides between the anchor midpoints of two interactions, which is the sum of the distance between midpoints of anchor A in interaction 1 and anchor A in interaction 2, and the distance between midpoints of anchor B in interaction 1 and anchor B in interaction 2.

Note: all anchors must be on the same chromosome; start coordinate is always less than end coordinate

Usage

```
calculate_midpoint_distance2d(  
  int1_anchor_a_start,  
  int1_anchor_a_end,  
  int1_anchor_b_start,  
  int1_anchor_b_end,  
  int2_anchor_a_start,  
  int2_anchor_a_end,  
  int2_anchor_b_start,  
  int2_anchor_b_end  
)
```

Arguments

```
int1_anchor_a_start  
    integer vector; genomic start coordinate(s) of anchor A in replicate 1 interaction  
int1_anchor_a_end  
    integer vector; genomic end coordinate(s) of anchor A in replicate 1 interaction  
int1_anchor_b_start  
    integer vector; genomic start coordinate(s) of anchor B in replicate 1 interaction  
int1_anchor_b_end  
    integer vector; genomic end coordinate(s) of anchor B in replicate 1 interaction  
int2_anchor_a_start  
    integer vector; genomic start coordinate(s) of anchor A in replicate 2 interaction  
int2_anchor_a_end  
    integer vector; genomic end coordinate(s) of anchor A in replicate 2 interaction  
int2_anchor_b_start  
    integer vector; genomic start coordinate(s) of anchor B in replicate 2 interaction  
int2_anchor_b_end  
    integer vector; genomic end coordinate(s) of anchor B in replicate 2 interaction
```

Value

positive integer vector; distances between interaction pairs

Examples

```
# identical, zero distance  
calculate_midpoint_distance2d(100, 120, 240, 260,  
                             100, 120, 240, 260)  
  
# centered, zero distance  
calculate_midpoint_distance2d(100, 120, 240, 260,  
                             90, 130, 230, 270)  
  
# off by 10 per anchor  
calculate_midpoint_distance2d(100, 120, 240, 250,  
                             110, 130, 230, 240)
```

```
# off by 10 (anchor B only)
calculate_midpoint_distance2d(100, 120, 240, 250,
                             90, 130, 250, 260)

# vectorized example
calculate_midpoint_distance2d(c(100, 100, 100, 100),
                             c(120, 120, 120, 120),
                             c(240, 240, 240, 240),
                             c(260, 260, 250, 250),
                             c(100, 90, 110, 90),
                             c(120, 130, 130, 130),
                             c(240, 230, 230, 250),
                             c(260, 270, 240, 260))
```

```
calculate_relative_overlap1d
```

Relative Anchor Overlap of two Peaks

Description

Calculates the overlap between anchor A of interaction 1 and anchor A of interaction 2, as well as anchor B of interaction 1 and anchor B of interaction 2. The overlap (in nucleotides) is then normalized by the length of the anchors.

Usage

```
calculate_relative_overlap1d(peak1_start, peak1_end, peak2_start, peak2_end)
```

Arguments

peak1_start	integer vector; genomic start coordinate(s) of peak in replicate 1
peak1_end	integer vector; genomic end coordinate(s) of peak in replicate 1
peak2_start	integer vector; genomic start coordinate(s) of peak in replicate 2
peak2_end	integer vector; genomic end coordinate(s) of peak in replicate 2

Value

numeric vector; relative overlaps between peak pairs

Examples

```
# 100% overlap
calculate_relative_overlap1d(100, 120,
                           100, 120)

# 50% overlap
```

```

calculate_relative_overlap1d(100, 120,
                             100, 110)

# negative overlap
calculate_relative_overlap1d(100, 120,
                             130, 140)

# larger negative overlap
calculate_relative_overlap1d(100, 120,
                             200, 220)

# vectorized example
calculate_relative_overlap1d(c(100, 100, 100, 100),
                             c(120, 120, 120, 120),
                             c(100, 100, 130, 200),
                             c(120, 110, 140, 220))

```

```
calculate_relative_overlap2d
```

Relative Anchor Overlap of two Interactions

Description

Calculates the overlap between anchor A of interaction 1 and anchor A of interaction 2, as well as anchor B of interaction 1 and anchor B of interaction 2. The overlap (in nucleotides) is then normalized by the length of the anchors.

Note: anchors A and B of the same interaction have to be on the same chromosome; start coordinate is always less than end coordinate

Usage

```

calculate_relative_overlap2d(
  int1_anchor_a_start,
  int1_anchor_a_end,
  int1_anchor_b_start,
  int1_anchor_b_end,
  int2_anchor_a_start,
  int2_anchor_a_end,
  int2_anchor_b_start,
  int2_anchor_b_end
)

```

Arguments

```

int1_anchor_a_start
  integer vector; genomic start coordinate(s) of anchor A in replicate 1 interaction
int1_anchor_a_end
  integer vector; genomic end coordinate(s) of anchor A in replicate 1 interaction

```

```

int1_anchor_b_start
    integer vector; genomic start coordinate(s) of anchor B in replicate 1 interaction
int1_anchor_b_end
    integer vector; genomic end coordinate(s) of anchor B in replicate 1 interaction
int2_anchor_a_start
    integer vector; genomic start coordinate(s) of anchor A in replicate 2 interaction
int2_anchor_a_end
    integer vector; genomic end coordinate(s) of anchor A in replicate 2 interaction
int2_anchor_b_start
    integer vector; genomic start coordinate(s) of anchor B in replicate 2 interaction
int2_anchor_b_end
    integer vector; genomic end coordinate(s) of anchor B in replicate 2 interaction

```

Value

numeric vector; relative overlaps between interaction pairs

Examples

```

# 100% overlap
calculate_relative_overlap2d(100, 120, 240, 260,
                            100, 120, 240, 260)

# 50% overlap
calculate_relative_overlap2d(100, 120, 240, 250,
                            100, 110, 240, 260)

# negative overlap
calculate_relative_overlap2d(100, 120, 240, 250,
                            130, 140, 260, 280)

# larger negative overlap
calculate_relative_overlap2d(100, 120, 240, 250,
                            200, 220, 340, 350)

# vectorized example
calculate_relative_overlap2d(c(100, 100, 100, 100),
                           c(120, 120, 120, 120),
                           c(240, 240, 240, 240),
                           c(260, 250, 250, 250),
                           c(100, 100, 130, 200),
                           c(120, 110, 140, 220),
                           c(240, 240, 260, 340),
                           c(260, 260, 280, 350))

```

 chiapet

Example Genomic Interaction Data Set

Description

This object contains genomic interactions on chromosomes 1 to 5, which could be the results of Hi-C or ChIA-PET experiments, done in duplicates.

Usage

```
chiapet
```

Format

A list with two components, the data frames rep1_df and rep2_df, which have the following seven columns:

column 1:	chr_a	character; genomic location of anchor A - chromosome (e.g., "chr3")
column 2:	start_a	integer; genomic location of anchor A - start coordinate
column 3:	end_a	integer; genomic location of anchor A - end coordinate
column 4:	chr_b	character; genomic location of anchor B - chromosome (e.g., "chr3")
column 5:	start_b	integer; genomic location of anchor B - start coordinate
column 6:	end_b	integer; genomic location of anchor B - end coordinate
column 7:	fdr	numeric; False Discovery Rate - significance of interaction

 chipseq

Example Genomic Peak Data Set

Description

This object contains genomic peaks from two replicate ChIP-seq experiments.

Usage

```
chipseq
```

Format

A list with two components, the data frames rep1_df and rep2_df, which have the following four columns:

column 1:	chr	character; genomic location of peak - chromosome (e.g., "chr3")
column 2:	start	integer; genomic location of peak - start coordinate
column 3:	end	integer; genomic location of peak - end coordinate
column 4:	value	numeric; heuristic used to rank the peaks

determine_anchor_overlap

Identifies Overlapping Anchors

Description

Identifies all overlapping anchor pairs (m:n mapping).

Usage

```
determine_anchor_overlap(rep1_anchor, rep2_anchor, max_gap = -1L)
```

Arguments

rep1_anchor data frame with the following columns:

column 1: chr character; genomic location of anchor in replicate 1 - chromosome (e.g., "chr3")
column 2: start integer; genomic location of anchor in replicate 1 - start coordinate
column 3: end integer; genomic location of anchor in replicate 1 - end coordinate

rep2_anchor data frame with the following columns:

column 1: chr character; genomic location of anchor in replicate 2 - chromosome (e.g., "chr3")
column 2: start integer; genomic location of anchor in replicate 2 - start coordinate
column 3: end integer; genomic location of anchor in replicate 2 - end coordinate

max_gap integer; maximum gap in nucleotides allowed between two anchors for them to be considered as overlapping (defaults to -1, i.e., overlapping anchors)

Value

A data frame containing overlapping anchor pairs with the following columns:

column 1: rep1_idx anchor index in data frame rep1_anchor
column 2: rep2_idx anchor index in data frame rep2_anchor

Examples

```
rep1_df <- idr2d::chiapet$rep1_df
rep2_df <- idr2d::chiapet$rep2_df

rep1_anchor_a <- data.frame(chr = rep1_df[, 1],
                           start = rep1_df[, 2],
                           end = rep1_df[, 3])
rep2_anchor_a <- data.frame(chr = rep2_df[, 1],
                           start = rep2_df[, 2],
                           end = rep2_df[, 3])
```

```
anchor_a_overlap <- determine_anchor_overlap(rep1_anchor_a, rep2_anchor_a)
```

```
draw_hic_contact_map Create Hi-C contact map
```

Description

Creates Hi-C contact maps to visualize the results of [estimate_idr2d_hic](#).

Usage

```
draw_hic_contact_map(
  df,
  idr_cutoff = NULL,
  chromosome = NULL,
  start_coordinate = NULL,
  end_coordinate = NULL,
  title = NULL,
  values_normalized = FALSE,
  log_values = TRUE
)
```

Arguments

<code>df</code>	output of estimate_idr2d_hic , a data frame with the following columns:
column 1:	<code>interaction</code> character; genomic location of interaction block (e.g., "chr1:204940000-204940000")
column 2:	<code>value</code> numeric; p-value, FDR, or heuristic used to rank the interactions
column 3:	<code>"rep_value"</code> numeric; value of corresponding replicate interaction
column 4:	<code>"rank"</code> integer; rank of the interaction, established by value column, ascending order
column 5:	<code>"rep_rank"</code> integer; rank of corresponding replicate interaction
column 6:	<code>"idr"</code> integer; IDR of the block and the corresponding block in the other replicate
<code>idr_cutoff</code>	numeric; only show blocks with $IDR < idr_cutoff$, shows all blocks by default
<code>chromosome</code>	character; chromosome name or list of chromosome names to be analyzed, e.g., UCSC chromosome 1, "chr1", defaults to all chromosomes (<code>chromosome = NULL</code>)
<code>start_coordinate</code>	integer; only show contact map window between " <code>start_coordinate</code> " and " <code>end_coordinate</code> ", by default shows entire chromosome
<code>end_coordinate</code>	integer; only show contact map window between " <code>start_coordinate</code> " and " <code>end_coordinate</code> ", by default shows entire chromosome
<code>title</code>	character; plot title
<code>values_normalized</code>	logical; are read counts in value column raw or normalized? Defaults to FALSE

log_values logical; log-transform value column? Defaults to TRUE

Value

ggplot2 object; Hi-C contact map

Examples

```
idr_results_df <- estimate_idr2d_hic(idr2d::hic$rep1_df,
                                   idr2d::hic$rep2_df)
draw_hic_contact_map(idr_results_df, idr_cutoff = 0.05, chromosome = "chr1")
```

```
draw_idr_distribution_histogram
      Create histogram of IDR values
```

Description

Creates diagnostic plots to visualize the results of [estimate_idr](#).

Usage

```
draw_idr_distribution_histogram(
  df,
  remove_na = TRUE,
  xlab = "IDR",
  ylab = "density",
  title = "IDR value distribution"
)
```

Arguments

df part of output of [estimate_idr](#), a data frame with at least the following named columns:

idr IDR of the peak and the corresponding peak in the other replicate.

remove_na logical; should NA values be removed?

xlab character; x axis label

ylab character; y axis label

title character; plot title

Value

ggplot2 object; IDR distribution histogram

Examples

```
idr_results <- estimate_idr1d(idr2d:::chipseq$rep1_df,
                             idr2d:::chipseq$rep2_df,
                             value_transformation = "log")
draw_idr_distribution_histogram(idr_results$rep1_df)
```

```
draw_rank_idr_scatterplot
  Create scatterplot of IDR values
```

Description

Creates diagnostic plots to visualize the results of [estimate_idr](#).

Usage

```
draw_rank_idr_scatterplot(
  df,
  remove_na = TRUE,
  xlab = "rank in replicate 1",
  ylab = "rank in replicate 2",
  log_idr = FALSE,
  title = "rank - IDR dependence",
  color_gradient = c("rainbow", "default"),
  alpha = 1,
  max_points_shown = 2500
)
```

Arguments

df	part of output of estimate_idr , a data frame with at least the following named columns:
rank	integer; rank of the peak, established by value column, ascending order
rep_rank	integer; rank of corresponding replicate peak.
idr	IDR of the peak and the corresponding peak in the other replicate.
remove_na	logical; should NA values be removed?
xlab	character; x axis label
ylab	character; y axis label
log_idr	logical; use logarithmized IDRs for colors to better distinguish highly significant IDRs
title	character; plot title
color_gradient	character; either "rainbow" or "default"

alpha numeric; transparency of dots, from 0.0 - 1.0, where 1.0 is completely opaque;
 default is 1.0

max_points_shown integer; default is 2500

Value

ggplot2 object; IDR rank scatterplot

Examples

```
idr_results <- estimate_idr1d(idr2d:::chipseq$rep1_df,
                             idr2d:::chipseq$rep2_df,
                             value_transformation = "log")
draw_rank_idr_scatterplot(idr_results$rep1_df)
```

draw_value_idr_scatterplot

Create scatterplot of IDR values

Description

Creates diagnostic plots to visualize the results of [estimate_idr](#).

Usage

```
draw_value_idr_scatterplot(
  df,
  remove_na = TRUE,
  remove_outliers = TRUE,
  xlab = "transformed value in replicate 1",
  ylab = "transformed value in replicate 2",
  log_axes = FALSE,
  log_idr = FALSE,
  title = "value - IDR dependence",
  color_gradient = c("rainbow", "default"),
  alpha = 1,
  max_points_shown = 2500
)
```

Arguments

df part of output of [estimate_idr](#), a data frame with at least the following named columns:

value	numeric; p-value, FDR, or heuristic used to rank the peaks
rep_value	numeric; value of corresponding replicate peak
idr	IDR of the peak and the corresponding peak in the other replicate.

remove_na	logical; should NA values be removed?
remove_outliers	logical; removes extreme data points
xlab	character; x axis label
ylab	character; y axis label
log_axes	logical; show logarithmized values from replicate 1 and 2 (default value is FALSE)
log_idr	logical; use logarithmized IDRs for colors to better distinguish highly significant IDRs (default value is FALSE)
title	character; plot title
color_gradient	character; either "rainbow" or "default"
alpha	numeric; transparency of dots, from 0.0 - 1.0, where 1.0 is completely opaque; default is 1.0
max_points_shown	integer; default is 2500

Value

ggplot2 object; IDR value scatterplot

Examples

```
idr_results <- estimate_idr1d(idr2d:::chipseq$rep1_df,
                             idr2d:::chipseq$rep2_df,
                             value_transformation = "log")
draw_value_idr_scatterplot(idr_results$rep1_df)
```

establish_bijection *Finds One-to-One Correspondence between Peaks or interactions from Replicate 1 and 2*

Description

This method establishes a bijective assignment between observations (genomic peaks in case of ChIP-seq, genomic interactions in case of ChIA-PET, HiChIP, and Hi-C) from replicate 1 and 2. An observation in replicate 1 is assigned to an observation in replicate 2 if and only if (1) the observation loci in both replicates overlap (or the gap between them is less than or equal to `max_gap`), and (2) there is no other observation in replicate 2 that overlaps with the observation in replicate 1 and has a lower *ambiguity resolution value*.

Usage

```

establish_bijection(
  rep1_df,
  rep2_df,
  analysis_type = c("IDR1D", "IDR2D"),
  ambiguity_resolution_method = c("overlap", "midpoint", "value"),
  max_gap = -1L
)

```

Arguments

rep1_df	data frame of observations (i.e., genomic peaks or genomic interactions) of replicate 1. If analysis_type is IDR1D, the columns of rep1_df are described in establish_bijection1d , otherwise in establish_bijection2d
rep2_df	data frame of observations (i.e., genomic peaks or genomic interactions) of replicate 2. Same columns as rep1_df.
analysis_type	"IDR2D" for genomic interaction data sets, "IDR1D" for genomic peak data sets
ambiguity_resolution_method	defines how ambiguous assignments (when one interaction or peak in replicate 1 overlaps with multiple interactions or peaks in replicate 2 or vice versa) are resolved. For available methods, see establish_overlap1d or establish_overlap2d , respectively.
max_gap	integer; maximum gap in nucleotides allowed between two anchors for them to be considered as overlapping (defaults to -1, i.e., overlapping anchors)

Value

See [establish_bijection1d](#) or [establish_bijection2d](#), respectively.

Examples

```

rep1_df <- idr2d::chipseq$rep1_df
rep1_df$value <- preprocess(rep1_df$value, "log")

rep2_df <- idr2d::chipseq$rep2_df
rep2_df$value <- preprocess(rep2_df$value, "log")

mapping <- establish_bijection(rep1_df, rep2_df, analysis_type = "IDR1D")

```

establish_bijection1d *Finds One-to-One Correspondence between Peaks from Replicate 1 and 2*

Description

This method establishes a bijective assignment between peaks from replicate 1 and 2. A peak in replicate 1 is assigned to a peak in replicate 2 if and only if (1) they overlap (or the gap between the peaks is less than or equal to `max_gap`), and (2) there is no other peak in replicate 2 that overlaps with the peak in replicate 1 and has a lower *ambiguity resolution value*.

Usage

```
establish_bijection1d(
  rep1_df,
  rep2_df,
  ambiguity_resolution_method = c("overlap", "midpoint", "value"),
  max_gap = -1L
)
```

Arguments

- `rep1_df` data frame of observations (i.e., genomic peaks) of replicate 1, with at least the following columns (position of columns matter, column names are irrelevant):
- column 1: `chr` character; genomic location of peak - chromosome (e.g., "chr3")
 - column 2: `start` integer; genomic location of peak - start coordinate
 - column 3: `end` integer; genomic location of peak - end coordinate
 - column 4: `value` numeric; p-value, FDR, or heuristic used to rank the interactions
- `rep2_df` data frame of observations (i.e., genomic peaks) of replicate 2, with the following columns (position of columns matter, column names are irrelevant):
- column 1: `chr` character; genomic location of peak - chromosome (e.g., "chr3")
 - column 2: `start` integer; genomic location of peak - start coordinate
 - column 3: `end` integer; genomic location of peak - end coordinate
 - column 4: `value` numeric; p-value, FDR, or heuristic used to rank the interactions
- `ambiguity_resolution_method` defines how ambiguous assignments (when one interaction in replicate 1 overlaps with multiple interactions in replicate 2 or vice versa) are resolved. Available methods:
- "value" interactions are prioritized by ascending or descending value column (see `sorting_direction`), e.g., if two interactions overlap, the interaction pair is chosen which has the highest relative overlap, i.e., overlap in nucleotides of replicate 1 in the pair.
 - "overlap" the interaction pair is chosen which has the highest relative overlap, i.e., overlap in nucleotides of replicate 1 in the pair.
 - "midpoint" the interaction pair is chosen which has the smallest distance between their anchor midpoints, i.e., distance from the midpoint of the interaction in replicate 1 to the midpoint of the interaction in replicate 2.
- `max_gap` integer; maximum gap in nucleotides allowed between two anchors for them to be considered as overlapping (defaults to -1, i.e., overlapping anchors)

Value

Data frames `rep1_df` and `rep2_df` with the following columns:

column 1:	chr	character; genomic location of peak - chromosome (e.g., "chr3")
column 2:	start	integer; genomic location of peak - start coordinate
column 3:	end	integer; genomic location of peak - end coordinate
column 4:	value	numeric; p-value, FDR, or heuristic used to rank the peaks
column 5:	rep_value	numeric; value of corresponding replicate peak. If no corresponding peak was found, rep_value is set to NA
column 6:	rank	integer; rank of the peak, established by value column, ascending order
column 7:	rep_rank	integer; rank of corresponding replicate peak. If no corresponding peak was found, rep_rank is set to NA
column 8:	idx	integer; peak index, primary key
column 9:	rep_idx	integer; specifies the index of the corresponding peak in the other replicate (foreign key). If no corresponding peak was found, rep_idx is set to NA

Examples

```
rep1_df <- idr2d::chipseq$rep1_df
rep1_df$value <- preprocess(rep1_df$value, "log")

rep2_df <- idr2d::chipseq$rep2_df
rep2_df$value <- preprocess(rep2_df$value, "log")

mapping <- establish_bijection1d(rep1_df, rep2_df)
```

establish_bijection2d *Finds One-to-One Correspondence between Interactions from Replicate 1 and 2*

Description

This method establishes a bijective assignment between interactions from replicate 1 and 2. An interaction in replicate 1 is assigned to an interaction in replicate 2 if and only if (1) both anchors of the interactions overlap (or the gap between anchor A/B in replicate 1 and 2 is less than or equal to `max_gap`), and (2) there is no other interaction in replicate 2 that overlaps with the interaction in replicate 1 and has a lower *ambiguity resolution value*.

Usage

```
establish_bijection2d(
  rep1_df,
  rep2_df,
  ambiguity_resolution_method = c("overlap", "midpoint", "value"),
  max_gap = -1L
)
```

Arguments

`rep1_df` data frame of observations (i.e., genomic interactions) of replicate 1, with at least the following columns (position of columns matter, column names are irrelevant):

column 1:	chr_a	character; genomic location of anchor A - chromosome (e.g., "chr3")
column 2:	start_a	integer; genomic location of anchor A - start coordinate
column 3:	end_a	integer; genomic location of anchor A - end coordinate
column 4:	chr_b	character; genomic location of anchor B - chromosome (e.g., "chr3")
column 5:	start_b	integer; genomic location of anchor B - start coordinate
column 6:	end_b	integer; genomic location of anchor B - end coordinate
column 7:	value	numeric; p-value, FDR, or heuristic used to rank the interactions

rep2_df data frame of observations (i.e., genomic interactions) of replicate 2, with the following columns (position of columns matter, column names are irrelevant):

column 1:	chr_a	character; genomic location of anchor A - chromosome (e.g., "chr3")
column 2:	start_a	integer; genomic location of anchor A - start coordinate
column 3:	end_a	integer; genomic location of anchor A - end coordinate
column 4:	chr_b	character; genomic location of anchor B - chromosome (e.g., "chr3")
column 5:	start_b	integer; genomic location of anchor B - start coordinate
column 6:	end_b	integer; genomic location of anchor B - end coordinate
column 7:	value	numeric; p-value, FDR, or heuristic used to rank the interactions

ambiguity_resolution_method

defines how ambiguous assignments (when one interaction in replicate 1 overlaps with multiple interactions in replicate 2 or vice versa) are resolved. Available methods:

"value"	interactions are prioritized by ascending or descending value column (see sorting_direction), e.g., if two interactions overlap, the interaction pair is chosen which has the highest relative overlap, i.e., overlap in nucleotides of replicate 1 in the pair.
"overlap"	the interaction pair is chosen which has the highest relative overlap, i.e., overlap in nucleotides of replicate 1 in the pair.
"midpoint"	the interaction pair is chosen which has the smallest distance between their anchor midpoints, i.e., distance from the midpoint of the interaction pair to the midpoint of the other interaction in the pair.

max_gap	integer; maximum gap in nucleotides allowed between two anchors for them to be considered as overlapping (defaults to -1, i.e., overlapping anchors)
---------	--

Value

Data frames rep1_df and rep2_df with the following columns:

column 1:	chr_a	character; genomic location of anchor A - chromosome (e.g., "chr3")
column 2:	start_a	integer; genomic location of anchor A - start coordinate
column 3:	end_a	integer; genomic location of anchor A - end coordinate
column 4:	chr_b	character; genomic location of anchor B - chromosome (e.g., "chr3")
column 5:	start_b	integer; genomic location of anchor B - start coordinate
column 6:	end_b	integer; genomic location of anchor B - end coordinate
column 7:	value	numeric; p-value, FDR, or heuristic used to rank the interactions
column 8:	"rep_value"	numeric; value of corresponding replicate interaction. If no corresponding interaction was found, NA
column 9:	"rank"	integer; rank of the interaction, established by value column, ascending order
column 10:	"rep_rank"	integer; rank of corresponding replicate interaction. If no corresponding interaction was found, NA
column 11:	"idx"	integer; interaction index, primary key
column 12:	"rep_idx"	integer; specifies the index of the corresponding interaction in the other replicate (foreign key).

Examples

```

rep1_df <- idr2d::chiapet$rep1_df
rep1_df$fdr <- preprocess(rep1_df$fdr, "log_additive_inverse")

rep2_df <- idr2d::chiapet$rep2_df
rep2_df$fdr <- preprocess(rep2_df$fdr, "log_additive_inverse")

mapping <- establish_bijection2d(rep1_df, rep2_df)

```

establish_overlap1d *Establish m:n Mapping Between Peaks from Replicate 1 and 2*

Description

This method returns all overlapping interactions between two replicates. For each pair of overlapping interactions, the *ambiguity resolution value* (ARV) is calculated, which helps to reduce the m:n mapping to a 1:1 mapping. The semantics of the ARV depend on the specified `ambiguity_resolution_method`, but in general interaction pairs with lower ARVs have priority over interaction pairs with higher ARVs when the bijective mapping is established.

Usage

```

establish_overlap1d(
  rep1_df,
  rep2_df,
  ambiguity_resolution_method = c("overlap", "midpoint", "value"),
  max_gap = -1L
)

```

Arguments

`rep1_df` data frame of observations (i.e., genomic peaks) of replicate 1, with at least the following columns (position of columns matter, column names are irrelevant):

column 1:	<code>chr</code>	character; genomic location of peak - chromosome (e.g., "chr3")
column 2:	<code>start</code>	integer; genomic location of peak - start coordinate
column 3:	<code>end</code>	integer; genomic location of peak - end coordinate
column 4:	<code>value</code>	numeric; p-value, FDR, or heuristic used to rank the interactions

`rep2_df` data frame of observations (i.e., genomic peaks) of replicate 2, with the following columns (position of columns matter, column names are irrelevant):

column 1:	<code>chr</code>	character; genomic location of peak - chromosome (e.g., "chr3")
column 2:	<code>start</code>	integer; genomic location of peak - start coordinate
column 3:	<code>end</code>	integer; genomic location of peak - end coordinate
column 4:	<code>value</code>	numeric; p-value, FDR, or heuristic used to rank the interactions

`ambiguity_resolution_method`
 defines how ambiguous assignments (when one interaction in replicate 1 overlaps with multiple interactions in replicate 2 or vice versa) are resolved. Available methods:

"value" interactions are prioritized by ascending or descending value column (see `sorting_direction`), e.g., if two interactions overlap, the one with the higher value is chosen.

"overlap" the interaction pair is chosen which has the highest relative overlap, i.e., overlap in nucleotides of replicate 1 in replicate 2.

"midpoint" the interaction pair is chosen which has the smallest distance between their anchor midpoints, i.e., distance from the midpoint of the interaction in replicate 1 to the midpoint of the interaction in replicate 2.

`max_gap` integer; maximum gap in nucleotides allowed between two anchors for them to be considered as overlapping (defaults to -1, i.e., overlapping anchors)

Value

data frame with the following columns:

column 1: `rep1_idx` index of interaction in replicate 1 (i.e., row index in `rep1_df`)
 column 2: `rep2_idx` index of interaction in replicate 2 (i.e., row index in `rep2_df`)
 column 3: `arv` ambiguity resolution value used turn m:n mapping into 1:1 mapping. Interaction pairs with lower arv have priority over interaction pairs with higher arv.

Examples

```
rep1_df <- idr2d::chipseq$rep1_df
rep1_df$value <- preprocess(rep1_df$value, "log_additive_inverse")

rep2_df <- idr2d::chipseq$rep2_df
rep2_df$value <- preprocess(rep2_df$value, "log_additive_inverse")

# shuffle to break preexisting order
rep1_df <- rep1_df[sample.int(nrow(rep1_df)), ]
rep2_df <- rep2_df[sample.int(nrow(rep2_df)), ]

# sort by value column
rep1_df <- dplyr::arrange(rep1_df, value)
rep2_df <- dplyr::arrange(rep2_df, value)

pairs_df <- establish_overlap1d(rep1_df, rep2_df)
```

`establish_overlap2d` *Establish m:n mapping between interactions from replicate 1 and 2*

Description

This method returns all overlapping interactions between two replicates. For each pair of overlapping interactions, the *ambiguity resolution value* (ARV) is calculated, which helps to reduce the m:n mapping to a 1:1 mapping. The semantics of the ARV depend on the specified `ambiguity_resolution_method`, but in general interaction pairs with lower ARVs have priority over interaction pairs with higher ARVs when the bijective mapping is established.

Usage

```

establish_overlap2d(
  rep1_df,
  rep2_df,
  ambiguity_resolution_method = c("overlap", "midpoint", "value"),
  max_gap = -1L
)

```

Arguments

`rep1_df` data frame of observations (i.e., genomic interactions) of replicate 1, with at least the following columns (position of columns matter, column names are irrelevant):

column 1: `chr_a` character; genomic location of anchor A - chromosome (e.g., "chr3")
column 2: `start_a` integer; genomic location of anchor A - start coordinate
column 3: `end_a` integer; genomic location of anchor A - end coordinate
column 4: `chr_b` character; genomic location of anchor B - chromosome (e.g., "chr3")
column 5: `start_b` integer; genomic location of anchor B - start coordinate
column 6: `end_b` integer; genomic location of anchor B - end coordinate
column 7: `value` numeric; p-value, FDR, or heuristic used to rank the interactions

`rep2_df` data frame of observations (i.e., genomic interactions) of replicate 2, with the following columns (position of columns matter, column names are irrelevant):

column 1: `chr_a` character; genomic location of anchor A - chromosome (e.g., "chr3")
column 2: `start_a` integer; genomic location of anchor A - start coordinate
column 3: `end_a` integer; genomic location of anchor A - end coordinate
column 4: `chr_b` character; genomic location of anchor B - chromosome (e.g., "chr3")
column 5: `start_b` integer; genomic location of anchor B - start coordinate
column 6: `end_b` integer; genomic location of anchor B - end coordinate
column 7: `value` numeric; p-value, FDR, or heuristic used to rank the interactions

`ambiguity_resolution_method` defines how ambiguous assignments (when one interaction in replicate 1 overlaps with multiple interactions in replicate 2 or vice versa) are resolved. Available methods:

"value" interactions are prioritized by ascending or descending value column (see `sorting_direction`), e.g., if two interactions overlap, the one with the higher value is chosen.
"overlap" the interaction pair is chosen which has the highest relative overlap, i.e., overlap in nucleotides of replicate 1 in replicate 2.
"midpoint" the interaction pair is chosen which has the smallest distance between their anchor midpoints, i.e., distance from the midpoint of the interaction in replicate 1 to the midpoint of the interaction in replicate 2.

`max_gap` integer; maximum gap in nucleotides allowed between two anchors for them to be considered as overlapping (defaults to -1, i.e., overlapping anchors)

Value

data frame with the following columns:

column 1: rep1_idx index of interaction in replicate 1 (i.e., row index in rep1_df)
 column 2: rep2_idx index of interaction in replicate 2 (i.e., row index in rep2_df)
 column 3: arv ambiguity resolution value used turn m:n mapping into 1:1 mapping. Interaction pairs with lower ar

Examples

```
rep1_df <- idr2d::chiapet$rep1_df
rep1_df$fdr <- preprocess(rep1_df$fdr, "log_additive_inverse")

rep2_df <- idr2d::chiapet$rep2_df
rep2_df$fdr <- preprocess(rep2_df$fdr, "log_additive_inverse")

# shuffle to break preexisting order
rep1_df <- rep1_df[sample.int(nrow(rep1_df)), ]
rep2_df <- rep2_df[sample.int(nrow(rep2_df)), ]

# sort by value column
rep1_df <- dplyr::arrange(rep1_df, rep1_df$fdr)
rep2_df <- dplyr::arrange(rep2_df, rep2_df$fdr)

pairs_df <- establish_overlap2d(rep1_df, rep2_df)
```

estimate_idr

Estimates IDR for Genomic Peaks or Genomic Interactions

Description

Estimates IDR for Genomic Peaks or Genomic Interactions

Usage

```
estimate_idr(
  rep1_df,
  rep2_df,
  analysis_type = "IDR2D",
  value_transformation = c("identity", "additive_inverse", "multiplicative_inverse",
    "log", "log_additive_inverse"),
  ambiguity_resolution_method = c("overlap", "midpoint", "value"),
  remove_nonstandard_chromosomes = TRUE,
  max_factor = 1.5,
  jitter_factor = 1e-04,
  max_gap = -1L,
  mu = 0.1,
  sigma = 1,
  rho = 0.2,
  p = 0.5,
  eps = 0.001,
```

```

    max_iteration = 30,
    local_idr = TRUE
)

```

Arguments

rep1_df	data frame of observations (i.e., genomic peaks or genomic interactions) of replicate 1. If analysis_type is IDR1D, the columns of rep1_df are described in establish_bijection1d , otherwise in establish_bijection2d
rep2_df	data frame of observations (i.e., genomic peaks or genomic interactions) of replicate 2. Same columns as rep1_df.
analysis_type	"IDR2D" for genomic interaction data sets, "IDR1D" for genomic peak data sets
value_transformation	the values in x have to be transformed in a way such that when ordered in descending order, more significant interactions end up on top of the list. If the values in x are p-values, "log_additive_inverse" is recommended. The following transformations are supported: <ul style="list-style-type: none"> "identity" no transformation is performed on x "additive_inverse" $x. = -x$ "multiplicative_inverse" $x. = 1 / x$ "log" $x. = \log(x)$. Note: zeros are replaced by <code>.Machine\$double.xmin</code> "log_additive_inverse" $x. = -\log(x)$, recommended if x are p-values. Note: zeros are replaced by <code>.Machine\$double.xmin</code> <p>either "ascending" (more significant interactions have lower value in value column) or "descending" (more significant interactions have higher value in value column)</p>
ambiguity_resolution_method	defines how ambiguous assignments (when one interaction or peak in replicate 1 overlaps with multiple interactions or peaks in replicate 2 or vice versa) are resolved. For available methods, see establish_overlap1d or establish_overlap2d , respectively.
remove_nonstandard_chromosomes	removes peaks and interactions containing genomic locations on non-standard chromosomes using keepStandardChromosomes (default is TRUE)
max_factor	numeric; controls the replacement values for Inf and -Inf. Inf are replaced by $\max(x) * \max_factor$ and -Inf are replaced by $\min(x) / \max_factor$.
jitter_factor	numeric; controls the magnitude of the noise that is added to x. This is done to break ties in x. Set jitter_factor = NULL for no jitter.
max_gap	integer; maximum gap in nucleotides allowed between two anchors for them to be considered as overlapping (defaults to -1, i.e., overlapping anchors)
mu	a starting value for the mean of the reproducible component.
sigma	a starting value for the standard deviation of the reproducible component.
rho	a starting value for the correlation coefficient of the reproducible component.
p	a starting value for the proportion of reproducible component.

eps Stopping criterion. Iterations stop when the increment of log-likelihood is < eps*log-likelihood, Default=0.001.

max_iteration integer; maximum number of iterations for IDR estimation (defaults to 30)

local_idr see [est.IDR](#)

Value

See [estimate_idr1d](#) or [estimate_idr2d](#), respectively.

References

Q. Li, J. B. Brown, H. Huang and P. J. Bickel. (2011) Measuring reproducibility of high-throughput experiments. *Annals of Applied Statistics*, Vol. 5, No. 3, 1752-1779.

Examples

```
idr_results <- estimate_idr(idr2d:::chiapet$rep1_df,
                           idr2d:::chiapet$rep2_df,
                           analysis_type = "IDR2D",
                           value_transformation = "log_additive_inverse")
summary(idr_results)
```

estimate_idr1d	<i>Estimates IDR for Genomic Peak Data</i>
----------------	--

Description

This method estimates Irreproducible Discovery Rates (IDR) for peaks in replicated ChIP-seq experiments.

Usage

```
estimate_idr1d(
  rep1_df,
  rep2_df,
  value_transformation = c("identity", "additive_inverse", "multiplicative_inverse",
    "log", "log_additive_inverse"),
  ambiguity_resolution_method = c("overlap", "midpoint", "value"),
  remove_nonstandard_chromosomes = TRUE,
  max_factor = 1.5,
  jitter_factor = 1e-04,
  max_gap = -1L,
  mu = 0.1,
  sigma = 1,
  rho = 0.2,
  p = 0.5,
```



```

    eps = 0.001,
    max_iteration = 30,
    local_idr = TRUE
  )

```

Arguments

- rep1_df** data frame of observations (i.e., genomic peaks) of replicate 1, with at least the following columns (position of columns matter, column names are irrelevant):
- column 1: chr character; genomic location of peak - chromosome (e.g., "chr3")
 - column 2: start integer; genomic location of peak - start coordinate
 - column 3: end integer; genomic location of peak - end coordinate
 - column 4: value numeric; p-value, FDR, or heuristic used to rank the interactions
- rep2_df** data frame of observations (i.e., genomic peaks) of replicate 2, with the following columns (position of columns matter, column names are irrelevant):
- column 1: chr character; genomic location of peak - chromosome (e.g., "chr3")
 - column 2: start integer; genomic location of peak - start coordinate
 - column 3: end integer; genomic location of peak - end coordinate
 - column 4: value numeric; p-value, FDR, or heuristic used to rank the interactions
- value_transformation** the values in x have to be transformed in a way such that when ordered in descending order, more significant interactions end up on top of the list. If the values in x are p-values, "log_additive_inverse" is recommended. The following transformations are supported:
- "identity" no transformation is performed on x
 - "additive_inverse" $x. = -x$
 - "multiplicative_inverse" $x. = 1 / x$
 - "log" $x. = \log(x)$. Note: zeros are replaced by `.Machine$double.xmin`
 - "log_additive_inverse" $x. = -\log(x)$, recommended if x are p-values. Note: zeros are replaced by `.Machine$double.xmin`
- either "ascending" (more significant interactions have lower value in value column) or "descending" (more significant interactions have higher value in value column)
- ambiguity_resolution_method** defines how ambiguous assignments (when one interaction in replicate 1 overlaps with multiple interactions in replicate 2 or vice versa) are resolved. Available methods:
- "value" interactions are prioritized by ascending or descending value column (see `sorting_direction`), e.g., if two interactions have the same value, the interaction with the highest relative overlap is chosen
 - "overlap" the interaction pair is chosen which has the highest relative overlap, i.e., overlap in nucleotides of replicate 1 in the pair
 - "midpoint" the interaction pair is chosen which has the smallest distance between their anchor midpoints, i.e., distance from the midpoint of the interaction pair to the midpoint of the interaction pair in replicate 2

remove_nonstandard_chromosomes	removes peaks containing genomic locations on non-standard chromosomes using keepStandardChromosomes (default is TRUE)
max_factor	numeric; controls the replacement values for Inf and -Inf. Inf are replaced by $\max(x) * \text{max_factor}$ and -Inf are replaced by $\min(x) / \text{max_factor}$.
jitter_factor	numeric; controls the magnitude of the noise that is added to x. This is done to break ties in x. Set jitter_factor = NULL for no jitter.
max_gap	integer; maximum gap in nucleotides allowed between two anchors for them to be considered as overlapping (defaults to -1, i.e., overlapping anchors)
mu	a starting value for the mean of the reproducible component.
sigma	a starting value for the standard deviation of the reproducible component.
rho	a starting value for the correlation coefficient of the reproducible component.
p	a starting value for the proportion of reproducible component.
eps	Stopping criterion. Iterations stop when the increment of log-likelihood is $< \text{eps} * \log\text{-likelihood}$, Default=0.001.
max_iteration	integer; maximum number of iterations for IDR estimation (defaults to 30)
local_idr	see est.IDR

Value

List with three components, (rep1_df, rep2_df, and analysis_type) containing the interactions from input data frames rep1_df and rep2_df with the following additional columns:

column 1:	chr	character; genomic location of peak - chromosome (e.g., "chr3")
column 2:	start	integer; genomic location of peak - start coordinate
column 3:	end	integer; genomic location of peak - end coordinate
column 4:	value	numeric; p-value, FDR, or heuristic used to rank the peaks
column 5:	rep_value	numeric; value of corresponding replicate peak. If no corresponding peak was found, rep_value is NA
column 6:	rank	integer; rank of the peak, established by value column, ascending order
column 7:	rep_rank	integer; rank of corresponding replicate peak. If no corresponding peak was found, rep_rank is NA
column 8:	idx	integer; peak index, primary key
column 9:	rep_idx	integer; specifies the index of the corresponding peak in the other replicate (foreign key). If no corresponding peak was found, rep_idx is NA
column 10:	idr	IDR of the peak and the corresponding peak in the other replicate. If no corresponding peak was found, idr is NA

References

Q. Li, J. B. Brown, H. Huang and P. J. Bickel. (2011) Measuring reproducibility of high-throughput experiments. *Annals of Applied Statistics*, Vol. 5, No. 3, 1752-1779.

Examples

```
idr_results <- estimate_idr1d(idr2d::chipseq$rep1_df,
                             idr2d::chipseq$rep2_df,
                             value_transformation = "log")
summary(idr_results)
```

estimate_idr2d

*Estimates IDR for Genomic Interaction Data***Description**

This method estimates Irreproducible Discovery Rates (IDR) between two replicates of experiments identifying genomic interactions, such as Hi-C, ChIA-PET, and HiChIP.

Usage

```
estimate_idr2d(
  rep1_df,
  rep2_df,
  value_transformation = c("identity", "additive_inverse", "multiplicative_inverse",
    "log", "log_additive_inverse"),
  ambiguity_resolution_method = c("overlap", "midpoint", "value"),
  remove_nonstandard_chromosomes = TRUE,
  max_factor = 1.5,
  jitter_factor = 1e-04,
  max_gap = -1L,
  mu = 0.1,
  sigma = 1,
  rho = 0.2,
  p = 0.5,
  eps = 0.001,
  max_iteration = 30,
  local_idr = TRUE
)
```

Arguments

`rep1_df` data frame of observations (i.e., genomic interactions) of replicate 1, with at least the following columns (position of columns matter, column names are irrelevant):

column 1:	<code>chr_a</code>	character; genomic location of anchor A - chromosome (e.g., "chr3")
column 2:	<code>start_a</code>	integer; genomic location of anchor A - start coordinate
column 3:	<code>end_a</code>	integer; genomic location of anchor A - end coordinate
column 4:	<code>chr_b</code>	character; genomic location of anchor B - chromosome (e.g., "chr3")
column 5:	<code>start_b</code>	integer; genomic location of anchor B - start coordinate
column 6:	<code>end_b</code>	integer; genomic location of anchor B - end coordinate
column 7:	<code>value</code>	numeric; p-value, FDR, or heuristic used to rank the interactions

`rep2_df` data frame of observations (i.e., genomic interactions) of replicate 2, with the following columns (position of columns matter, column names are irrelevant):

column 1:	chr_a	character; genomic location of anchor A - chromosome (e.g., "chr3")
column 2:	start_a	integer; genomic location of anchor A - start coordinate
column 3:	end_a	integer; genomic location of anchor A - end coordinate
column 4:	chr_b	character; genomic location of anchor B - chromosome (e.g., "chr3")
column 5:	start_b	integer; genomic location of anchor B - start coordinate
column 6:	end_b	integer; genomic location of anchor B - end coordinate
column 7:	value	numeric; p-value, FDR, or heuristic used to rank the interactions

value_transformation

the values in x have to be transformed in a way such that when ordered in descending order, more significant interactions end up on top of the list. If the values in x are p-values, "log_additive_inverse" is recommended. The following transformations are supported:

"identity"	no transformation is performed on x
"additive_inverse"	$x. = -x$
"multiplicative_inverse"	$x. = 1 / x$
"log"	$x. = \log(x)$. Note: zeros are replaced by <code>.Machine\$double.xmin</code>
"log_additive_inverse"	$x. = -\log(x)$, recommended if x are p-values. Note: zeros are replaced by <code>.Machine\$double</code>

either "ascending" (more significant interactions have lower value in value column) or "descending" (more significant interactions have higher value in value column)

ambiguity_resolution_method

defines how ambiguous assignments (when one interaction in replicate 1 overlaps with multiple interactions in replicate 2 or vice versa) are resolved. Available methods:

"value"	interactions are prioritized by ascending or descending value column (see <code>sorting_direction</code>), e.g., if two in
"overlap"	the interaction pair is chosen which has the highest relative overlap, i.e., overlap in nucleotides of replicate 1 in
"midpoint"	the interaction pair is chosen which has the smallest distance between their anchor midpoints, i.e., distance from

remove_nonstandard_chromosomes

removes interactions containing genomic locations on non-standard chromosomes using `keepStandardChromosomes` (default is TRUE)

max_factor	numeric; controls the replacement values for Inf and $-\text{Inf}$. Inf are replaced by $\max(x) * \text{max_factor}$ and $-\text{Inf}$ are replaced by $\min(x) / \text{max_factor}$.
jitter_factor	numeric; controls the magnitude of the noise that is added to x . This is done to break ties in x . Set <code>jitter_factor = NULL</code> for no jitter.
max_gap	integer; maximum gap in nucleotides allowed between two anchors for them to be considered as overlapping (defaults to -1, i.e., overlapping anchors)
mu	a starting value for the mean of the reproducible component.
sigma	a starting value for the standard deviation of the reproducible component.
rho	a starting value for the correlation coefficient of the reproducible component.
p	a starting value for the proportion of reproducible component.

eps Stopping criterion. Iterations stop when the increment of log-likelihood is < eps*log-likelihood, Default=0.001.

max_iteration integer; maximum number of iterations for IDR estimation (defaults to 30)

local_idr see [est.IDR](#)

Value

List with three components, (rep1_df, rep2_df, and analysis_type) containing the interactions from input data frames rep1_df and rep2_df with the following additional columns:

column 1: chr_a
 column 2: start_a
 column 3: end_a
 column 4: chr_b
 column 5: start_b
 column 6: end_b
 column 7: value
 column 8: "rep_value"
 column 9: "rank"
 column 10: "rep_rank"
 column 11: "idx"
 column 12: "rep_idx"
 idr IDR of the interaction and the corresponding interaction in the other replicate. If no corresponding interaction w

References

Q. Li, J. B. Brown, H. Huang and P. J. Bickel. (2011) Measuring reproducibility of high-throughput experiments. *Annals of Applied Statistics*, Vol. 5, No. 3, 1752-1779.

Examples

```
idr_results <- estimate_idr2d(idr2d::chiapet$rep1_df,
                             idr2d::chiapet$rep2_df,
                             value_transformation = "log_additive_inverse")
summary(idr_results)
```

estimate_idr2d_hic *Estimates IDR for Genomic Interactions measured by Hi-C experiments*

Description

This method estimates Irreproducible Discovery Rates (IDR) of genomic interactions between two replicates of Hi-C experiments.

Before calling this method, call Juicer .hic contact matrix c

The contact matrix is subdivided into blocks, where the block size is determined by resolution. The reads per block are used to rank blocks and replicate blocks are easily matched by genomic location.

Usage

```
estimate_idr2d_hic(
  rep1_df,
  rep2_df,
  combined_min_value = 30,
  combined_max_value = Inf,
  min_value = -Inf,
  max_value = Inf,
  max_factor = 1.5,
  jitter_factor = 1e-04,
  mu = 0.1,
  sigma = 1,
  rho = 0.2,
  p = 0.5,
  eps = 0.001,
  max_iteration = 30,
  local_idr = TRUE
)
```

Arguments

rep1_df	data frame of either parsed .hic file from Juicer (output of parse_juicer_matrix) or parsed .matrix and .bed files from HiC-Pro (output of parse_hic_pro_matrix) for replicate 1
rep2_df	data frame of either parsed .hic file from Juicer (output of parse_juicer_matrix) or parsed .matrix and .bed files from HiC-Pro (output of parse_hic_pro_matrix) for replicate 2
combined_min_value	exclude blocks with a combined (replicate 1 + replicate 2) read count or normalized read count of less than combined_min_value (default is 20 reads, set combined_min_value = -Inf to disable)
combined_max_value	exclude blocks with a combined (replicate 1 + replicate 2) read count or normalized read count of more than combined_max_value (disabled by default, set combined_max_value = Inf to disable)
min_value	exclude blocks with a read count or normalized read count of less than min_value in one replicate (disabled by default, set min_value = -Inf to disable)
max_value	exclude blocks with a read count or normalized read count of more than max_value in one replicate (disabled by default, set max_value = Inf to disable)
max_factor	numeric; controls the replacement values for Inf and -Inf. Inf are replaced by $\max(x) * \max_factor$ and -Inf are replaced by $\min(x) / \max_factor$.
jitter_factor	numeric; controls the magnitude of the noise that is added to x. This is done to break ties in x. Set jitter_factor = NULL for no jitter.

mu	a starting value for the mean of the reproducible component.
sigma	a starting value for the standard deviation of the reproducible component.
rho	a starting value for the correlation coefficient of the reproducible component.
p	a starting value for the proportion of reproducible component.
eps	Stopping criterion. Iterations stop when the increment of log-likelihood is < eps*log-likelihood, Default=0.001.
max_iteration	integer; maximum number of iterations for IDR estimation (defaults to 30)
local_idr	see est.IDR

Value

Data frame with the following columns:

column 1:	interaction	character; genomic location of interaction block (e.g., "chr1:204940000-204940000")
column 2:	value	numeric; p-value, FDR, or heuristic used to rank the interactions
column 3:	"rep_value"	numeric; value of corresponding replicate interaction
column 4:	"rank"	integer; rank of the interaction, established by value column, ascending order
column 5:	"rep_rank"	integer; rank of corresponding replicate interaction
column 6:	"idr"	integer; IDR of the block and the corresponding block in the other replicate

References

Q. Li, J. B. Brown, H. Huang and P. J. Bickel. (2011) Measuring reproducibility of high-throughput experiments. *Annals of Applied Statistics*, Vol. 5, No. 3, 1752-1779.

Examples

```
idr_results_df <- estimate_idr2d_hic(idr2d:::hic$rep1_df,
                                   idr2d:::hic$rep2_df)
summary(idr_results_df)
```

hic *Example Hi-C data set*

Description

This object contains data from a Hi-C contact map of human chromosome 1 and a resolution of $2.5 * 10^6$, extracted from GEO series GSE71831.

Usage

```
hic
```

Format

A list with two components, the data frames `rep1_df` and `rep2_df`, which have the following four columns:

column 1:	chr	character; genomic location of block - chromosome (e.g., "chr3")
column 2:	region1	integer; genomic location of block - coordinate A
column 3:	region2	integer; genomic location of block - coordinate B
column 4:	value	numeric; heuristic used to rank blocks, in this case: number of reads

parse_hic_pro_matrix *Parse .matrix and .bed files from HiC-Pro for IDR2D analysis*

Description

This function is used to convert the contact matrix from a HiC-Pro pipeline analysis run into an IDR2D compatible format. It takes one .matrix and one .bed file per replicate from HiC-Pro and returns the contact matrix for a specific chromosome for IDR2D analysis (see [estimate_idr2d_hic](#))

Usage

```
parse_hic_pro_matrix(matrix_file, bed_file, chromosome = "chr1")
```

Arguments

matrix_file	path to .matrix file from HiC-Pro analysis run
bed_file	path to .bed file from HiC-Pro analysis run
chromosome	chromosome name to be analyzed, defaults to UCSC chromosome 1 ("chr1")

Value

Data frame with the following columns:

column 1:	chr	character; chromosome of block (e.g., "chr3")
column 2:	region1	integer; genomic location of side A of block in Hi-C contact matrix
column 3:	region2	integer; genomic location of side B of block in Hi-C contact matrix
column 4:	value	numeric; (normalized) read count in block

References

Servant, N., Varoquaux, N., Lajoie, B.R. et al. HiC-Pro: an optimized and flexible pipeline for Hi-C data processing. *Genome Biol* 16, 259 (2015) doi:10.1186/s13059-015-0831-x

parse_juicer_matrix *Parse .hic files from Juicer for IDR2D analysis*

Description

parse_juicer_matrix uses the Python package hic-straw internally to read .hic contact matrix files (see [hic-straw on PyPI](#) or the [Aiden lab GitHub repository](#) for more information).

The contact matrix is subdivided into blocks, where the block size is determined by resolution. The reads per block are used to rank blocks and replicate blocks are easily matched by genomic location.

Usage

```
parse_juicer_matrix(
    hic_file,
    resolution = 1e+06,
    normalization = c("NONE", "VC", "VC_SQRT", "KR"),
    chromosome = "chr1",
    use_python = NULL,
    use_virtualenv = NULL,
    use_condaenv = NULL
)
```

Arguments

hic_file	path to .hic file (either local file path or URL).
resolution	block resolution of Hi-C contact matrix in base pairs, defaults to 1,000,000 bp (usually one of the following: 2500000, 1000000, 500000, 250000, 100000, 50000, 25000, 10000, 5000)
normalization	normalization step performed by Python package hic-straw, one of the following: "NONE", "VC", "VC_SQRT", "KR".
chromosome	chromosome name to be analyzed, defaults to UCSC chromosome 1 ("chr1")
use_python	if Python is not on PATH, specify path to Python binary here (see use_python)
use_virtualenv	if Python package hic-straw is not in base virtualenv environment, specify environment here (see use_virtualenv)
use_condaenv	if Python package hic-straw is not in base conda environment, specify environment here (see use_condaenv)

Value

Data frame with the following columns:

column 1:	chr	character; chromosome of block (e.g., "chr3")
column 2:	region1	integer; genomic location of side A of block in Hi-C contact matrix
column 3:	region2	integer; genomic location of side B of block in Hi-C contact matrix
column 4:	value	numeric; (normalized) read count in block

References

Neva C. Durand, James T. Robinson, Muhammad S. Shamim, Ido Machol, Jill P. Mesirov, Eric S. Lander, and Erez Lieberman Aiden. "Juicebox provides a visualization system for Hi-C contact

maps with unlimited zoom." Cell Systems 3(1), 2016.

```
preprocess
```

Prepares Data for IDR Analysis

Description

This method removes invalid values, establishes the correct ranking, and breaks ties prior to IDR analysis.

Inf and -Inf are replaced by $\max(x) * \max_factor$ and $\min(x) / \max_factor$, respectively.

NA values in x are replaced by $\text{mean}(x)$.

All values in x are transformed using the transformation specified in `value_transformation`.

Lastly, a small amount of noise is added to x to break ties. The magnitude of the noise is controlled by `jitter_factor`.

Usage

```
preprocess(
  x,
  value_transformation = c("identity", "additive_inverse", "multiplicative_inverse",
    "log", "log_additive_inverse"),
  max_factor = 1.5,
  jitter_factor = 1e-04
)
```

Arguments

<code>x</code>	numeric vector of values
<code>value_transformation</code>	the values in x have to be transformed in a way such that when ordered in descending order, more significant interactions end up on top of the list. If the values in x are p-values, "log_additive_inverse" is recommended. The following transformations are supported:
<code>"identity"</code>	no transformation is performed on x
<code>"additive_inverse"</code>	$x. = -x$
<code>"multiplicative_inverse"</code>	$x. = 1 / x$
<code>"log"</code>	$x. = \log(x)$. Note: zeros are replaced by <code>.Machine\$double.xmin</code>
<code>"log_additive_inverse"</code>	$x. = -\log(x)$, recommended if x are p-values. Note: zeros are replaced by <code>.Machine\$double.xmin</code>
<code>order</code>	either "ascending" (more significant interactions have lower value in value column) or "descending" (more significant interactions have higher value in value column)
<code>max_factor</code>	numeric; controls the replacement values for Inf and -Inf. Inf are replaced by $\max(x) * \max_factor$ and -Inf are replaced by $\min(x) / \max_factor$.

`jitter_factor` numeric; controls the magnitude of the noise that is added to `x`. This is done to break ties in `x`. Set `jitter_factor = NULL` for no jitter.

Value

numeric vector; transformed and stripped values of `x`, ready for IDR analysis

Examples

```
rep1_df <- idr2d::chiapet$rep1_df
rep1_df$fd_r <- preprocess(rep1_df$fd_r, "log_additive_inverse")
```

remove_nonstandard_chromosomes1d

Removes Peaks on Non-standard Chromosomes

Description

Removes Peaks on Non-standard Chromosomes

Usage

```
remove_nonstandard_chromosomes1d(x)
```

Arguments

`x` data frame of genomic peaks, with the following columns (position of columns matter, column names are irrelevant):

column 1:	<code>chr</code>	character; genomic location of peak - chromosome (e.g., "chr3")
column 2:	<code>start</code>	integer; genomic location of peak - start coordinate
column 3:	<code>end</code>	integer; genomic location of peak - end coordinate
column 4:	<code>value</code>	numeric; p-value, FDR, or heuristic used to rank the peaks

Value

`x` without non-standard chromosomes.

Examples

```
rep1_df <- remove_nonstandard_chromosomes1d(idr2d::chipseq$rep1_df)
```

`remove_nonstandard_chromosomes2d`*Removes Interactions on Non-standard Chromosomes*

Description

Removes Interactions on Non-standard Chromosomes

Usage

```
remove_nonstandard_chromosomes2d(x)
```

Arguments

`x` data frame of genomic interactions, with the following columns (position of columns matter, column names are irrelevant):

column 1:	<code>chr_a</code>	character; genomic location of anchor A - chromosome (e.g., "chr3")
column 2:	<code>start_a</code>	integer; genomic location of anchor A - start coordinate
column 3:	<code>end_a</code>	integer; genomic location of anchor A - end coordinate
column 4:	<code>chr_b</code>	character; genomic location of anchor B - chromosome (e.g., "chr3")
column 5:	<code>start_b</code>	integer; genomic location of anchor B - start coordinate
column 6:	<code>end_b</code>	integer; genomic location of anchor B - end coordinate
column 7:	<code>value</code>	numeric; p-value, FDR, or heuristic used to rank the interactions

Value

`x` without non-standard chromosomes.

Examples

```
rep1_df <- remove_nonstandard_chromosomes2d(idr2d:::chiapet$rep1_df)
```

Index

* datasets

- chiapet, [8](#)
- chipseq, [8](#)
- hic, [31](#)

- calculate_midpoint_distance1d, [2](#)
- calculate_midpoint_distance2d, [3](#)
- calculate_relative_overlap1d, [5](#)
- calculate_relative_overlap2d, [6](#)
- chiapet, [8](#)
- chipseq, [8](#)

- determine_anchor_overlap, [9](#)
- draw_hic_contact_map, [10](#)
- draw_idr_distribution_histogram, [11](#)
- draw_rank_idr_scatterplot, [12](#)
- draw_value_idr_scatterplot, [13](#)

- est. IDR, [24](#), [26](#), [29](#), [31](#)
- establish_bijection, [14](#)
- establish_bijection1d, [15](#), [15](#), [23](#)
- establish_bijection2d, [15](#), [17](#), [23](#)
- establish_overlap1d, [15](#), [19](#), [23](#)
- establish_overlap2d, [15](#), [20](#), [23](#)
- estimate_idr, [11–13](#), [22](#)
- estimate_idr1d, [24](#), [24](#)
- estimate_idr2d, [24](#), [27](#)
- estimate_idr2d_hic, [10](#), [29](#), [33](#)

- hic, [31](#)

- keepStandardChromosomes, [23](#), [26](#), [28](#)

- parse_hic_pro_matrix, [30](#), [33](#)
- parse_juicer_matrix, [30](#), [33](#)
- preprocess, [35](#)

- remove_nonstandard_chromosomes1d, [36](#)
- remove_nonstandard_chromosomes2d, [37](#)

- use_condaenv, [34](#)
- use_python, [34](#)
- use_virtualenv, [34](#)