

Package ‘ORFik’

October 16, 2018

Type Package

Title Open Reading Frames in Genomics

Version 1.0.0

Description Tools for manipulation of RiboSeq, RNASeq and CageSeq data. ORFik is extremely fast through use of C, data.table and GenomicRanges. Package allows to reassign starts of the transcripts with the use of CageSeq data, automatic shifting of RiboSeq reads, finding of Open Reading Frames for the whole genomes and many more.

biocViews Software, Sequencing, RiboSeq, RNASeq, FunctionalGenomics, Coverage, Alignment, DataImport

License MIT + file LICENSE

LazyData TRUE

BugReports <https://github.com/JokingHero/ORFik/issues>

URL <https://github.com/JokingHero/ORFik>

Depends R (>= 3.5.0), IRanges (>= 2.13.28), GenomicRanges (>= 1.31.23), GenomicAlignments (>= 1.15.13)

Imports S4Vectors (>= 0.17.39), GenomeInfoDb (>= 1.15.5), GenomicFeatures (>= 1.31.10), rtracklayer (>= 1.39.9), Rcpp (>= 0.12.16), data.table (>= 1.10.4-3), Biostrings (>= 2.47.12), stats, tools, Rsamtools (>= 1.31.3)

RoxygenNote 6.0.1

Suggests testthat, rmarkdown, knitr, BiocStyle, BSgenome, BSgenome.Hsapiens.UCSC.hg19, ggplot2 (>= 2.2.1)

LinkingTo Rcpp

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/ORFik>

git_branch RELEASE_3_7

git_last_commit 74296f8

git_last_commit_date 2018-04-30

Date/Publication 2018-10-15

Author Kornel Labun [aut, cre, cph],
Haakon Tjeldnes [aut, dtc],
Katarzyna Chyzynska [ctb, dtc],
Evind Valen [ths, fnd]

Maintainer Kornel Labun <kornellabun@gmail.com>

R topics documented:

ORFik-package	4
addFirstCdsOnLeaderEnds	5
addNewTSSOnLeaders	5
assignAnnotations	6
assignFirstExons	6
assignFirstExonsStartSite	7
assignLastExonsStopSite	7
asTX	8
bedToGR	8
changePointAnalysis	9
checkRFP	9
checkRNA	10
codonSumsPerGroup	10
computeFeatures	11
computeFeaturesCage	12
coverageByWindow	14
coveragePerTiling	15
defineIsoform	16
defineTrailer	16
detectRibosomeShifts	17
disengagementScore	18
distToCds	19
downstreamN	20
downstreamOfPerGroup	21
entropy	21
extendLeaders	22
extendsTSSexons	23
filterCage	23
findCageUTRFivelen	24
findFa	24
findMapORFs	25
findMaxPeaks	26
findNewTSS	26
findORFs	27
findORFsFasta	28
firstEndPerGroup	29
firstExonPerGroup	29
firstStartPerGroup	30
fixSeqnames	31
floss	31
fpkm	32
fpkm_calc	33
fractionLength	34
fread.bed	35
getStartStopWindows	35
groupGRangesBy	36
gSort	37
hasHits	38
insideOutsideORF	38
is.grl	39

is.gr_or_grl	40
isInFrame	40
isOverlapping	41
isPeriodic	42
kozakSequenceScore	42
lastExonEndPerGroup	43
lastExonPerGroup	44
lastExonStartPerGroup	44
makeExonRanks	45
makeORFNames	46
mapToGRanges	46
matchNaming	47
matchSeqlevels	47
metaWindow	48
numExonsPerGroup	48
orfID	49
orfScore	50
parseCigar	51
rankOrder	51
reassignTSSbyCage	52
reduceKeepAttr	53
regroupRleList	54
removeMetaCols	55
riboSeqReadWidths	55
ribosomeReleaseScore	56
ribosomeStallingScore	57
seqnamesPerGroup	58
shiftFootprints	58
sortPerGroup	59
startCodons	60
startDefinition	61
startSites	61
stopCodons	62
stopDefinition	63
stopSites	63
strandBool	64
strandPerGroup	65
subsetCoverage	65
subset_to_frame	66
tile1	66
translationalEff	67
txLen	68
txNames	69
txNamesWithLeaders	69
txSeqsFromFa	70
uniqueGroups	70
uniqueOrder	71
unlistGrl	72
upstreamOfPerGroup	72
validExtension	73
validGRL	73
widthPerGroup	74

ORFik-package

ORFik for analysis of open reading frames.

Description

Main goals:

1. Finding Open Reading Frames (very fast) in the genome of interest or on the set of transcripts/sequences.
2. Utilities for metaplots of RiboSeq coverage over gene START and STOP codons allowing to spot the shift.
3. Shifting functions for the RiboSeq data.
4. Finding new Transcription Start Sites with the use of CageSeq data.
5. Various measurements of gene identity e.g. FLOSS, coverage, ORFscore, entropy that are recreated based on many scientific publications.
6. Utility functions to extend GenomicRanges for faster grouping, splitting, tiling etc.

Author(s)

Maintainer: Kornel Labun <kornellabun@gmail.com> [copyright holder]

Authors:

- Haakon Tjeldnes <hauken_heyken@hotmail.com> [data contributor]

Other contributors:

- Katarzyna Chyzynska <katchyz@gmail.com> [contributor, data contributor]
- Evind Valen <evind.valen@gmail.com> [thesis advisor, funder]

See Also

Useful links:

- <https://github.com/JokingHero/ORFik>
- Report bugs at <https://github.com/JokingHero/ORFik/issues>

 addFirstCdsOnLeaderEnds

Extends leaders downstream

Description

When reassigning Transcript start sites, often you want to add downstream too. This is a simple way to do that

Usage

```
addFirstCdsOnLeaderEnds(fiveUTRs, cds)
```

Arguments

fiveUTRs	The 5' leader sequences as GRangesList
cds	If you want to extend 5' leaders downstream, to catch uorfs going into cds, include it.

Value

a GRangesList of cds exons added to ends

 addNewTSSOnLeaders *add cage max peaks as new transcript start sites for each 5' leader (*) strands are not supported, since direction must be known.*

Description

add cage max peaks as new transcript start sites for each 5' leader (*) strands are not supported, since direction must be known.

Usage

```
addNewTSSOnLeaders(fiveUTRs, maxPeakPosition)
```

Arguments

fiveUTRs	The 5' leader sequences as GRangesList
maxPeakPosition	The max peak for each 5' leader found by cage

Value

a GRanges object of first exons

assignAnnotations *Overlaps GRanges object with provided annotations.*

Description

It will return same list of GRanges, but with metadata columns: transcript_id - id of transcripts that overlap with each ORF gene_id - id of gene that this transcript belongs to isoform - for coding protein alignment in relation to cds on corresponding transcript, for non-coding transcripts alignment in relation to the transcript.

Usage

```
assignAnnotations(ORFs, con)
```

Arguments

ORFs - GRanges or GRangesList object of your ORFs.
 con - Path to gtf file with annotations.

Value

A GRanges object of your ORFs with metadata columns 'gene', 'transcript', 'isoform' and 'biotype'.

assignFirstExons *After all transcript start sites have been updated from cage, put GRangesList back together*

Description

After all transcript start sites have been updated from cage, put GRangesList back together

Usage

```
assignFirstExons(firstExons, fiveUTRs)
```

Arguments

firstExons The first exon of every transcript from 5' leaders
 fiveUTRs The 5' leader sequences as GRangesList

Value

a GRangesList

`assignFirstExonsStartSite`*Reassign the start positions of the first exons per group in grl*

Description

make sure your grl is sorted, since start of "-" strand objects should be the max end in group, use `ORFik:::sortPerGroup(grl)` to get sorted grl.

Usage

```
assignFirstExonsStartSite(grl, newStarts)
```

Arguments

`grl` a [GRangesList](#) object
`newStarts` an integer vector of same length as grl, with new start values

Value

the same [GRangesList](#) with new start sites

`assignLastExonsStopSite`*Reassign the stop positions of the last exons per group*

Description

make sure your grl is sorted, since stop of "-" strand objects should be the min start in group, use `ORFik:::sortPerGroup(grl)` to get sorted grl.

Usage

```
assignLastExonsStopSite(grl, newStops)
```

Arguments

`grl` a [GRangesList](#) object
`newStops` an integer vector of same length as grl, with new start values

Value

the same [GRangesList](#) with new stop sites

 asTX

Map genomic to transcript coordinates by reference

Description

Map genomic to transcript coordinates by reference

Usage

```
asTX(grl, reference)
```

Arguments

grl	a GRangesList of ranges within the reference, grl must have column called names that gives grouping for result
reference	a GRangesList of ranges that include and are bigger or equal to grl ig. cds is grl and gene can be reference

Value

a GRangesList in transcript coordinates

 bedToGR

Converts different type of files to Granges

Description

column 5 will be set to score Only Accepts bed files for now, standard format from Fantom5

Usage

```
bedToGR(x, bed6 = TRUE)
```

Arguments

x	An data.frame from imported bed-file, to convert to GRanges
bed6	If bed6, no meta column is added

Value

a GRanges object from bed

changePointAnalysis *Get the offset for specific RiboSeq read width*

Description

Get the offset for specific RiboSeq read width

Usage

```
changePointAnalysis(x, feature = "start")
```

Arguments

x a vector with points to analyse, assumes the zero is in the middle + 1
feature (character) either "start" or "stop"

Value

a single numeric offset

checkRFP *Helper Function to check valid RFP input*

Description

Helper Function to check valid RFP input

Usage

```
checkRFP(class)
```

Arguments

class, the given class of RFP object

Value

NULL, stop if invalid object

checkRNA *Helper Function to check valid RNA input*

Description

Helper Function to check valid RNA input

Usage

checkRNA(class)

Arguments

class, the given class of RNA object

Value

NULL, stop if invalid object

codonSumsPerGroup *Get hits per codon*

Description

Helper for entropy function, normally not used directly

Usage

codonSumsPerGroup(h, indeces, L, N, reg_len, runLengths, countList)

Arguments

h	indices per tuple
indeces	whole list of indices
L	Lengths
N	hit sums
reg_len	size of runs
runLengths	integers per run
countList	a Rle of count repetitions (000,1,00,1 etc)

Value

a list of codon sums

computeFeatures	<i>Get all possible features in ORFik</i>
-----------------	---

Description

If you want to get all the features easily, you can use this function. Each feature have a link to an article describing its creation and idea behind it. Look at the functions in the feature family to see all of them.

Usage

```
computeFeatures(grl, RFP, RNA = NULL, Gtf = NULL, faFile = NULL,
  riboStart = 26, riboStop = 34, orfFeatures = TRUE,
  includeNonVarying = TRUE)
```

Arguments

grl	a GRangesList object with usually ORFs, but can also be either leaders, cds', 3' utrs, etc.
RFP	RiboSeq reads as GAlignment , GRanges or GRangesList object
RNA	RnaSeq reads as GAlignment , GRanges or GRangesList object
Gtf	a TxDb object of a gtf file,
faFile	a FaFile or BSgenome from the fasta file, see ?FaFile
riboStart	usually 26, the start of the floss interval, see ?floss
riboStop	usually 34, the end of the floss interval
orfFeatures	a logical, is the grl a list of orfs?
includeNonVarying	a logical, if TRUE, include all features not dependent on RiboSeq data and RNASeq data, that is: Kozak , fractionLengths , distORFCDS , isInFrame , isOverlapping and rankInTx

Details

If you used [CageSeq](#) to reannotate your leaders your txDB object, must contain the reassigned leaders. In the future release reassignment will create txdb objects for you, but currently this is not supported, therefore be carefull.

Value

a [data.table](#) with scores, each column is one score type, name of columns are the names of the scores, i.g [\[floss\(\)\]](#) or [\[fpkm\(\)\]](#)

See Also

Other features: [computeFeaturesCage](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
# Usually the ORFs are found in orfik, which makes names for you etc.
# Here we make an example from scratch
## Not run:
gtf <- system.file("extdata", "annotations.gtf",
package = "ORFik") ## location of the gtf file
suppressWarnings(txdb <-
  GenomicFeatures::makeTxDbFromGFF(gtf, format = "gtf"))
# use cds' as ORFs for this example
ORFs <- GenomicFeatures::cdsBy(txdb, by = "tx", use.names = TRUE)
ORFs <- makeORFNames(ORFs) # need ORF names
# make Ribo-seq data,
RFP <- unlistGrl(firstExonPerGroup(ORFs))
suppressWarnings(computeFeatures(ORFs, RFP, Gtf = txdb))
# For more thorough examples, see vignettes.

## End(Not run)
```

computeFeaturesCage *Get all possible features in ORFik*

Description

Normally dont use this function, but instead use: [computeFeatures()]

Usage

```
computeFeaturesCage(grl, RFP, RNA = NULL, Gtf = NULL, tx = NULL,
  fiveUTRs = NULL, cds = NULL, threeUTRs = NULL, faFile = NULL,
  riboStart = 26, riboStop = 34, extension = NULL, orfFeatures = TRUE,
  cageFiveUTRs = NULL, includeNonVarying = TRUE, grl.is.sorted = FALSE)
```

Arguments

grl	a GRangesList object with usually ORFs, but can also be either leaders, cds', 3' utrs or ORFs are a special case, see argument tx_len
RFP	ribo seq reads as GAlignment , GRanges or GRangesList object
RNA	rna seq reads as GAlignment , GRanges or GRangesList object
Gtf	a TxDb object of a gtf file,
tx	a GrangesList of transcripts, normally called from: <code>exonsBy(Gtf, by = "tx", use.names = T)</code> only add this if you are not including Gtf file You do not need to reassign these to the cage peaks, it will do it for you.
fiveUTRs	fiveUTRs as GRangesList , must be original unchanged fiveUTRs
cds	a GRangesList of coding sequences
threeUTRs	a GrangesList of transcript 3' utrs, normally called from: <code>threeUTRsByTranscript(Gtf, use.names = T)</code>
faFile	a FaFile or BSgenome from the fasta file, see <code>?FaFile</code>
riboStart	usually 26, the start of the floss interval, see <code>?floss</code>

riboStop	usually 34, the end of the floss interval
extension	a numeric/integer needs to be set! set to 0 if you did not use cage, if you used cage to change tss' when finding the orfs, standard cage extension is 1000
orfFeatures	a logical, is the grl a list of orfs? Must be assigned.
cageFiveUTRs	a GRangesList, if you used cage-data to extend 5' utrs, include this, also extension must match with the extension used for these.
includeNonVarying	a logical T, if TRUE, include all features not dependent on Ribo-seq data and RNA-seq data, that is: Kozak, fractionLengths, distORFCDS, isInFrame, isOverlapping and rankInTx
grl.is.sorted	logical (F), a speed up if you know argument grl is sorted, set this to TRUE.

Details

A specialized version if you used Cage data, and don't have a new txdb with reassigned leaders, transcripts and gene starts. If you do have a txdb with cage reassignments, use `computeFeatures` instead. Each feature have a link to an article describing feature, try `?floss`

Value

a data.table with scores, each column is one score type, name of columns are the names of the scores, i.g `[floss()]` or `[fpkm()]`

See Also

Other features: [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
# a small example without cage-seq data:
# we will find ORFs in the 5' utrs
# and then calculate features on them
## Not run:
if (requireNamespace("BSgenome.Hsapiens.UCSC.hg19")) {
  library(GenomicFeatures)
  # Get the gtf txdb file
  txdbFile <- system.file("extdata", "hg19_knownGene_sample.sqlite",
    package = "GenomicFeatures")
  txdb <- loadDb(txdbFile)

  # Extract sequences of fiveUTRs.
  fiveUTRs <- fiveUTRsByTranscript(txdb, use.names = TRUE)[1:10]
  faFile <- BSgenome.Hsapiens.UCSC.hg19::Hsapiens
  # need to suppress warning because of bug in GenomicFeatures, will
  # be fixed soon.
  tx_seqs <- suppressWarnings(extractTranscriptSeqs(faFile, fiveUTRs))

  # Find all ORFs on those transcripts and get their genomic coordinates
  fiveUTR_ORFs <- findMapORFs(fiveUTRs, tx_seqs)
  unlistedORFs <- unlistGr1(fiveUTR_ORFs)
  # group GRanges by ORFs instead of Transcripts
  fiveUTR_ORFs <- groupGRangesBy(unlistedORFs, unlistedORFs$names)
```

```

# make some toy ribo seq and rna seq data
starts <- unlistGrl(ORFik:::firstExonPerGroup(fiveUTR_ORFs))
RFP <- promoters(starts, upstream = 0, downstream = 1)
score(RFP) <- rep(29, length(RFP)) # the original read widths

# set RNA seq to duplicate transcripts
RNA <- unlistGrl(exonsBy(txdb, by = "tx", use.names = TRUE))

cageNotUsed <- 0 # used to inform that no cage was used

computeFeaturesCage(grl = fiveUTR_ORFs, orfFeatures = TRUE, RFP = RFP,
  RNA = RNA, Gtf = txdb, faFile = faFile, extension = cageNotUsed)

}
# See vignettes for more examples

## End(Not run)

```

coverageByWindow

Compute coverage for every GRangesList subset.

Description

This is similar to [GenomicFeatures::coverageByTranscript()], but it adds: automatic sorting of the windows, fix for some rare cases when subsetting fails on minus/plus strands and security that subsetting of windows will always return values (zeros) instead of out of bounds error.

Usage

```
coverageByWindow(x, windows, ignore.strand = FALSE, is.sorted = FALSE,
  keep.names = TRUE)
```

Arguments

x	the cigar of the reads
windows	(GRangesList) of transcripts or CDS or other ranges that will be subsetting coverage of 'x'
ignore.strand	(logical) Whether to consider all reads to be "*".
is.sorted	(logical), is windows already sorted.
keep.names	logical (T), keep names and meta cols

Details

Minus strand is already flipped so that the most 5' position on the window is the first position in the returned Rle.

Value

(RleList) of positional counts of 'x' ranges overlapping each consecutive position of the elements of 'windows'

Examples

```

cds <- GenomicRanges::GRangesList(
  GenomicRanges::GRanges(seqnames = "chr1",
    ranges = IRanges::IRanges(100, 200),
    strand = "+"))
reads <- GenomicRanges::GRanges(
  seqnames = "chr1",
  ranges = IRanges::IRanges(c(100, 150), c(110, 160)),
  strand = "+")
ORFik::coverageByWindow(reads, cds)

```

coveragePerTiling	<i>Get coverage per group</i>
-------------------	-------------------------------

Description

It tiles each GRangesList group, and finds hits per position

Usage

```
coveragePerTiling(grl, reads, is.sorted = FALSE, keep.names = TRUE)
```

Arguments

grl	a GRangesList of 5' utrs or transcripts.
reads	a GAlignment or GRanges object of RiboSeq, RnaSeq etc
is.sorted	logical (F), is grl sorted.
keep.names	logical (T), keep names or not.

Value

a Rle, one list per group with # of hits per position.

Examples

```

ORF <- GRanges(seqnames = "1",
  ranges = IRanges(start = c(1, 10, 20),
    end = c(5, 15, 25)),
  strand = "+")
grl <- GRangesList(tx1_1 = ORF)
RFP <- GRanges("1", IRanges(25, 25), "+")
coveragePerTiling(grl, RFP)

```

defineIsoform *Overlaps GRanges object with provided annotations.*

Description

Overlaps GRanges object with provided annotations.

Usage

```
defineIsoform(rel_orf, tran, isoform_names = c("perfect_match",
  "elong_START_match", "trunc_START_match", "elong_STOP_match",
  "trunc_STOP_match", "overlap_inside", "overlap_both", "overlap_upstream",
  "overlap_downstream", "upstream", "downstream", "none"))
```

Arguments

rel_orf - GRanges object of your ORF.

tran - GRanges object of annotation (transcript or cds) that overlapped in some way rel_orf.

isoform_names - A vector of strings that will be used instead of these defaults: 'perfect_match' - start and stop matches the tran object strand wise 'elong_START_match' - rel_orf is extension from the STOP side of the tran 'trunc_START_match' - rel_orf is truncation from the STOP side of the tran 'elong_STOP_match' - rel_orf is extension from the START side of the tran 'trunc_STOP_match' - rel_orf is truncation from the START side of the tran 'overlap_inside' - rel_orf is inside tran object 'overlap_both' - rel_orf contains tran object inside 'overlap_upstream' - rel_orf is overlapping upstream part of the tran 'overlap_downstream' - rel_orf is overlapping downstream part of the tran 'upstream' - rel_orf is upstream towards the tran 'downstream' - rel_orf is downstream towards the tran 'none' - when none of the above options is true

Value

A string object of defined isoform towards transcript.

defineTrailer *Defines trailers for ORF.*

Description

Creates GRanges object as a trailer for ORFranges representing ORF, maintaining restrictions of transcriptRanges. Assumes that ORFranges is on the transcriptRanges, strands and seqlevels are in agreement. When lengthOftrailer is smaller than space left on the transcript than all available space is returned as trailer.

Usage

```
defineTrailer(ORFranges, transcriptRanges, lengthOftrailer = 200)
```


Arguments

ORFranges GRanges object of your Open Reading Frame.
transcriptRanges GRanges object of transtript.
lengthOftrailer Numeric. Default is 10.

Details

It assumes that ORFranges and transcriptRanges are not sorted when on minus strand. Should be like: (200, 600) (50, 100)

Value

A GRanges object of trailer.

Examples

```
ORFranges <- GRanges(seqnames = Rle(rep("1", 3)),
  ranges = IRanges(start = c(1, 10, 20),
    end = c(5, 15, 25)),
  strand = "+")
transcriptRanges <- GRanges(seqnames = Rle(rep("1", 5)),
  ranges = IRanges(start = c(1, 10, 20, 30, 40),
    end = c(5, 15, 25, 35, 45)),
  strand = "+")
defineTrailer(ORFranges, transcriptRanges)
```

detectRibosomeShifts *Detect ribosome shifts*

Description

Utilizes periodicity measurement (fourier transform) and change point analysis to detect ribosomal footprint shifts for each of the ribosomal read lengths. Returns subset of read lengths and their shifts for which top covered transcripts follow periodicity measure. Each shift value assumes 5' anchoring of the reads, so that output offsets values will shift 5' anchored footprints to be on the p-site of the ribosome.

Usage

```
detectRibosomeShifts(footprints, txdb, start = TRUE, stop = FALSE,
  top_tx = 10L, minFiveUTR = 30L, minCDS = 150L, minThreeUTR = 30L,
  firstN = 150L)
```

Arguments

footprints	(GAlignments) object of RiboSeq reads - footprints
txdb	a txdb object from a gtf file
start	(logical) Whether to include predictions based on the start codons. Default TRUE.
stop	(logical) Whether to include predictions based on the stop codons. Default FALSE.
top_tx	(integer) Specify which transcripts to use for estimation of the shifts. By default we take top 10 top covered transcripts as they represent less noisy dataset. This is only applicable when there are more than 1000 transcripts.
minFiveUTR	(integer) minimum bp for 5' UTR during filtering for the transcripts
minCDS	(integer) minimum bp for CDS during filtering for the transcripts
minThreeUTR	(integer) minimum bp for 3' UTR during filtering for the transcripts
firstN	(integer) Represents how many bases of the transcripts downstream of start codons to use for initial estimation of the periodicity.

Details

Check out vignette for the examples of plotting RiboSeq metaplots over start and stop codons, so that you can verify visually whether this function detects correct shifts.

Value

a data.frame with lengths of footprints and their predicted corresponding offsets

Examples

```
## Not run:
gtf_file <- system.file("extdata", "annotations.gtf", package = "ORFik")
txdb <- GenomicFeatures::makeTxDbFromGFF(gtf_file, format = "gtf")
riboSeq_file <- system.file("extdata", "ribo-seq.bam", package = "ORFik")
footprints <- GenomicAlignments::readGAlignments(
  riboSeq_file, param = ScanBamParam(flag = scanBamFlag(
    isDuplicate = FALSE, isSecondaryAlignment = FALSE)))

detectRibosomeShifts(footprints, txdb, stop = TRUE)

## End(Not run)
```

disengagementScore *Disengagement score (DS)*

Description

Disengagement score is defined as

$$(\text{RPFs over ORF}) / (\text{RPFs downstream to tx end})$$

A pseudo-count of one is added to both the ORF and downstream sums.

Usage

```
disengagementScore(gr1, RFP, GtfOrTx)
```

Arguments

`gr1` a [GRangesList](#) object with usually either leaders, cds', 3' utrs or ORFs.
`RFP` RiboSeq reads as `GAlignment`, `GRanges` or `GRangesList` object
`GtfOrTx` If it is `TxDb` object transcripts will be extracted using `exonsBy(Gtf, by = "tx", use.names = TRUE)`
 Else it must be [GRangesList](#)

Value

a named vector of numeric values of scores

References

doi: 10.1242/dev.098344

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
ORF <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 10, 20), end = c(5, 15, 25)),
               strand = "+")
gr1 <- GRangesList(tx1_1 = ORF)
tx <- GRangesList(tx1 = GRanges("1", IRanges(1, 50), "+"))
RFP <- GRanges("1", IRanges(c(1,10,20,30,40), width = 3), "+")
disengagementScore(gr1, RFP, tx)
```

distToCds

Get distances between ORF ends and starts of their transcripts cds'.

Description

Will calculate distance between each ORF end and beginning of the corresponding cds. Matching is done by transcript names. This is applicable practically to the upstream (fiveUTRs) ORFs. The cds start site, will be presumed to be on + 1 of end of fiveUTRs.

Usage

```
distToCds(ORFs, fiveUTRs, cds = NULL, extension = NULL)
```

Arguments

ORFs	orfs as GRangesList , names of orfs must be transcript names
fiveUTRs	fiveUTRs as GRangesList , must be original unchanged fiveUTRs
cds	cds' as GRangesList , only add if you used CageSeq to extend leaders
extension	Numeric that needs set to 0 if you did not use CageSeq if you used CageSeq to change tss' when finding the orfs, standard cage extension is 1000.

Value

an integer vector, +1 means one base upstream of cds, -1 means 2nd base in cds, 0 means orf stops at cds start.

References

doi: 10.1074/jbc.R116.733899

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
grl <- GRangesList(tx1_1 = GRanges("1", IRanges(1, 10), "+"))
fiveUTRs <- GRangesList(tx1 = GRanges("1", IRanges(1, 20), "+"))
distToCds(grl, fiveUTRs, extension = 0)
```

downstreamN

Restrict GRangesList

Description

Will restrict GRangesList to 'N' bp downstream from the first base.

Usage

```
downstreamN(grl, firstN = 150L)
```

Arguments

grl	(GRangesList)
firstN	(integer) Allow only this many bp downstream

Value

a GRangesList of reads restricted to firstN and tiled by 1

downstreamOfPerGroup *Get rest of objects downstream*

Description

Per group get the part downstream of position defined in downstreamOf downstreamOf(tx, OR-Fik:::stopSites(cds, asGR = F)) will return the 3' utrs per transcript as GRangesList, usually used for interesting parts of the transcripts, like upstream open reading frames(uorf). downstreamOf +/- 1 is start/end site of transformed tx's, depending on strand

Usage

```
downstreamOfPerGroup(tx, downstreamOf)
```

Arguments

tx a [GRangesList](#), usually of Transcripts to be changed
 downstreamOf a vector of integers, for each group in tx, where is the new start point of first valid exon.

Value

a GRangesList of downstream part

entropy *Calucalte entropy value of overlapping input reads.*

Description

Calculates entropy of the 'reads' coverage over each 'grl' group. The entropy value per group is a real number in the interval (0:1), where 0 indicates no variance in reads over group. For example c(0,0,0,0) has 0 entropy, since no reads overlap.

Usage

```
entropy(grl, reads)
```

Arguments

grl a [GRangesList](#) that the reads will be overlapped with
 reads a GAlignment object or GRanges or GRangesList, usually data from RiboSeq or RnaSeq

Value

A numeric vector containing one entropy value per element in 'grl'

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
ORF <- GRanges("1", ranges = IRanges(start = c(1, 12, 22),
                                     end = c(10, 20, 32)),
              strand = "+",
              names = rep("tx1_1", 3))
names(ORF) <- rep("tx1", 3)
grl <- GRangesList(tx1_1 = ORF)
RFP <- GRanges("1", IRanges(c(25, 35), c(25, 35)), "+")
# grl must have same names as cds + _1 etc, so that they can be matched.
entropy(grl, RFP)
# or on cds
cdsORF <- GRanges("1", IRanges(35, 44), "+", names = "tx1")
names(cdsORF) <- "tx1"
cds <- GRangesList(tx1 = cdsORF)
entropy(cds, RFP)
```

extendLeaders

Extend the leaders transcription start sites.

Description

Will extend the leaders or transcripts upstream by extension. Requires the grl to be sorted beforehand, use [sortPerGroup](#) to get sorted grl.

Usage

```
extendLeaders(grl, extension = 1000, cds = NULL)
```

Arguments

grl	a GRangesList of 5' utrs or transcripts.
extension	an integer, how much to extend the leaders. Or a GRangesList where start / stops by strand are the positions to use as new starts.
cds	If you want to extend 5' leaders downstream, to catch upstream ORFs going into cds, include it. It will add first cds exon to grl matched by names. Do not add for transcripts, as they are already included.

Value

an extended [GRangeslist](#)

Examples

```

library(GenomicFeatures)
samplefile <- system.file("extdata", "hg19_knownGene_sample.sqlite",
                          package = "GenomicFeatures")
txdb <- loadDb(samplefile)
fiveUTRs <- fiveUTRsByTranscript(txdb) # <- extract only 5' leaders
tx <- exonsBy(txdb, by = "tx", use.names = TRUE)
cds <- cdsBy(txdb, "tx", use.names = TRUE)
## now try(extend upstream 1000, downstream 1st cds exons):
extendLeaders(fiveUTRs, extension = 1000, cds)

## when extending transcripts, don't include cds' of course,
## since they are already there
extendLeaders(tx, extension = 1000)

```

extendsTSSexons *Extend first exon of each transcript with length specified*

Description

Extend first exon of each transcript with length specified

Usage

```
extendsTSSexons(fiveUTRs, extension = 1000)
```

Arguments

fiveUTRs	The 5' leader sequences as GRangesList
extension	The number of bases upstream to add on transcripts

Value

granges object of first exons

filterCage *Filter peak of cage-data by value*

Description

Filter peak of cage-data by value

Usage

```
filterCage(rawCage, filterValue = 1)
```

Arguments

rawCage	The raw cage-data
filterValue	The number of counts(score) to filter on for a tss to pass as hit

Value

the filtered Granges object

findCageUTRFiveLen	<i>Get length of leaders ordered after oldTxNames</i>
--------------------	---

Description

Normally only a helper function for ORFik

Usage

```
findCageUTRFiveLen(fiveUTRs, oldTxNames)
```

Arguments

fiveUTRs	a GRangesList object of leaders
oldTxNames	a character vector of names to group fiveUTRs by.

Value

a GRangesList of reordered leaders.

findFa	<i>Convenience wrapper for Rsamtools FaFile</i>
--------	---

Description

Convenience wrapper for Rsamtools FaFile

Usage

```
findFa(faFile)
```

Arguments

faFile	a character path or FaFile
--------	----------------------------

Value

a FaFile or BSgenome

findMapORFs	<i>Find ORFs and immediately map them to their genomic positions.</i>
-------------	---

Description

Finds ORFs on the sequences of interest, but returns relative positions to the positions of 'grl' argument. For example, 'grl' can be exons of known transcripts (with genomic coordinates), and 'seq' sequences of those transcripts, in that case, [findMapORFs()] will return genomic coordinates of ORFs found on transcript sequences.

Usage

```
findMapORFs(grl, seqs, startCodon = startDefinition(1),
            stopCodon = stopDefinition(1), longestORF = FALSE, minimumLength = 0)
```

Arguments

grl	(GRangesList) of sequences to search for ORFs, probably in genomic coordinates
seqs	(DNASTringSet or character) DNA sequences to search for Open Reading Frames.
startCodon	(character) Possible START codons to search for. Check [startDefinition()] for helper function.
stopCodon	(character) Possible STOP codons to search for. Check [stopDefinition()] for helper function.
longestORF	(logical) Default FALSE. When TRUE will only report ORFs that are longest, all smaller overlapping ORFs will be ignored. When FALSE will report all possible ORFs in all three reading frames.
minimumLength	(integer) Default is 0. Minimum length of ORF, without counting 3bp for START and STOP codons. For example minimumLength = 8 will result in size of ORFs to be at least START + 8*3 (bp) + STOP. Use this param to restrict search.

Details

This function assumes that 'seq' is in widths relative to 'grl', and that their orders match.

Value

A GRangesList of ORFs.

See Also

[findORFs()], [findORFsFasta()], [startDefinition()], [stopDefinition()]

Other findORFs: [findORFsFasta](#), [findORFs](#), [startDefinition](#), [stopDefinition](#)

Examples

```
# This sequence has ORFs at 1-9 and 4-9
seqs <- c("ATGATGTAA") # the dna sequence
findORFs(seqs)
# lets assume that this sequence comes from two exons as follows
gr <- GRanges(seqnames = rep("1", 2), # chromosome 1
              ranges = IRanges(start = c(21, 10), end = c(23, 15)),
              strand = rep("-", 2), names = rep("tx1", 2))
grl <- GRangesList(tx1 = gr)
findMapORFs(grl, seqs) # ORFs are properly mapped to its genomic coordinates

grl <- c(grl, grl)
names(grl) <- c("tx1", "tx2")
findMapORFs(grl, c(seqs, seqs))
```

findMaxPeaks	<i>Find max peak for each transcript, returns as data.table, without names, but with index</i>
--------------	--

Description

Find max peak for each transcript, returns as data.table, without names, but with index

Usage

```
findMaxPeaks(cageOverlaps, filteredCage)
```

Arguments

cageOverlaps	The cageOverlaps between cage and extended 5' leaders
filteredCage	The filtered raw cage-data used to reassign 5' leaders

Value

a data.table of max peaks

findNewTSS	<i>Finds max peaks per transcript from reads in the cagefile</i>
------------	--

Description

Finds max peaks per transcript from reads in the cagefile

Usage

```
findNewTSS(fiveUTRs, cageData, extension)
```

Arguments

fiveUTRs	The 5' leader sequences as GRangesList
cageData	The location of the cage-file
extension	The number of bases upstream to add on transcripts

Value

a Hits object

findORFs	<i>Find Open Reading Frames.</i>
----------	----------------------------------

Description

Find all Open Reading Frames (ORFs) on the input sequences in 5'-3' direction, but within all three possible reading frames. For each sequence of the input vector [IRanges](#) with START and STOP positions (inclusive) will be returned as [IRangesList](#). Returned coordinates are relative to the input sequences.

Usage

```
findORFs(seqs, startCodon = startDefinition(1),
         stopCodon = stopDefinition(1), longestORF = FALSE, minimumLength = 0)
```

Arguments

seqs	(DNAStrngSet or character) DNA sequences to search for Open Reading Frames.
startCodon	(character) Possible START codons to search for. Check [startDefinition()] for helper function.
stopCodon	(character) Possible STOP codons to search for. Check [stopDefinition()] for helper function.
longestORF	(logical) Default FALSE. When TRUE will only report ORFs that are longest, all smaller overlapping ORFs will be ignored. When FALSE will report all possible ORFs in all three reading frames.
minimumLength	(integer) Default is 0. Minimum length of ORF, without counting 3bp for START and STOP codons. For example minimumLength = 8 will result in size of ORFs to be at least START + 8*3 (bp) + STOP. Use this param to restrict search.

Value

(IRangesList) of ORFs locations including START and STOP codons grouped by input sequences.

See Also

[findMapORFs()], [findORFsFasta()], [startDefinition()], [stopDefinition()]

Other findORFs: [findMapORFs](#), [findORFsFasta](#), [startDefinition](#), [stopDefinition](#)

Examples

```

findORFs("ATGTAA")
findORFs("ATGTAA") # not in frame anymore

findORFs("ATGATGTAA") # two ORFs
findORFs("ATGATGTAA", longestORF = TRUE) # only longest of two above

findORFs(c("ATGTAA", "ATGATGTAA"))

```

findORFsFasta	<i>Finds Open Reading Frames in fasta files.</i>
---------------	--

Description

Searches through each fasta header and reports all ORFs found for sense (+) and antisense strand (-) in all frames. Name of the header will be used as seqnames of reported ORFs. Each fasta header is treated separately, and name of the sequence will be used as seqname in returned GRanges object.

Usage

```

findORFsFasta(filePath, startCodon = startDefinition(1),
  stopCodon = stopDefinition(1), longestORF = TRUE, minimumLength = 0,
  is.circular = FALSE)

```

Arguments

filePath	(character) Path to the fasta file.
startCodon	(character) Possible START codons to search for. Check [startDefinition()] for helper function.
stopCodon	(character) Possible STOP codons to search for. Check [stopDefinition()] for helper function.
longestORF	(logical) Default FALSE. When TRUE will only report ORFs that are longest, all smaller overlapping ORFs will be ignored. When FALSE will report all possible ORFs in all three reading frames.
minimumLength	(integer) Default is 0. Minimum length of ORF, without counting 3bp for START and STOP codons. For example minimumLength = 8 will result in size of ORFs to be at least START + 8*3 (bp) + STOP. Use this param to restrict search.
is.circular	(logical) Whether the genome in filePath is circular. Prokaryotic genomes are usually circular.

Value

(GRanges) object of ORFs mapped from fasta file. Positions are relative to the fasta file.

See Also

[findORFs()], [findMapORFs()], [startDefinition()], [stopDefinition()]

Other findORFs: [findMapORFs](#), [findORFs](#), [startDefinition](#), [stopDefinition](#)

Examples

```
# location of the example fasta file
example_genome <- system.file("extdata", "genome.fasta", package = "ORFik")
findORFsFasta(example_genome)
```

firstEndPerGroup	<i>Get first end per granges group</i>
------------------	--

Description

grl must be sorted, call `ORFik:::sortPerGroup` if needed

Usage

```
firstEndPerGroup(grl, keep.names = TRUE)
```

Arguments

grl	a GRangesList
keep.names	a boolean, keep names or not

Value

a `Rle(keep.names = T)`, or integer vector(F)

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
                  ranges = IRanges(c(7, 14), width = 3),
                  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
                   ranges = IRanges(c(4, 1), c(9, 3)),
                   strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
firstEndPerGroup(grl)
```

firstExonPerGroup	<i>Get first exon per GRangesList group</i>
-------------------	---

Description

grl must be sorted, call `ORFik:::sortPerGroup` if needed

Usage

```
firstExonPerGroup(grl)
```

Arguments

grl	a GRangesList
-----	-------------------------------

Value

a GRangesList of the first exon per group

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
firstExonPerGroup(grl)
```

firstStartPerGroup	<i>Get first start per granges group</i>
--------------------	--

Description

grl must be sorted, call ORFik:::sortPerGroup if needed

Usage

```
firstStartPerGroup(grl, keep.names = TRUE)
```

Arguments

grl a [GRangesList](#)
 keep.names a boolean, keep names or not

Value

a Rle(keep.names = TRUE), or integer vector(FALSE)

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
firstStartPerGroup(grl)
```

fixSeqnames	<i>Seqnames cleanup</i>
-------------	-------------------------

Description

For many datasets, the fa file and the gtf file have different naming This functions tries to fix the naming to the GRanges standard chrX instead of X chr1 instead of 1 etc..

Usage

```
fixSeqnames(gr1)
```

Arguments

gr1 a [GRangesList](#)

Value

a GRangesList with fixed seqnames

floss	<i>Fragment Length Organization Similarity Score</i>
-------	--

Description

This feature is usually calculated only for RiboSeq reads. For reads of width between 'start' and 'end', sum the fraction of RiboSeq reads (per widths) that overlap ORFs and normalize by CDS.

Usage

```
floss(gr1, RFP, cds, start = 26, end = 34)
```

Arguments

gr1	a GRangesList object with ORFs
RFP	ribosomal footprints, given as Galignment or GRanges object, must be already shifted and resized to the p-site
cds	a GRangesList of coding sequences, cds has to have names as gr1 so that they can be matched
start	usually 26, the start of the floss interval
end	usually 34, the end of the floss interval

Details

Pseudo explanation of the function:

$$\text{SUM}[\text{start to stop}]((\text{gr1}[\text{start:end}][\text{name}]/\text{gr1}) / (\text{cds}[\text{start:end}][\text{name}]/\text{cds}))$$

Please read more in the article.

Value

a vector of FLOSS of length same as grl

References

doi: 10.1016/j.celrep.2014.07.045

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [fpm_calc](#), [fpm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
ORF <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 12, 22),
                                end = c(10, 20, 32)),
               strand = "+")
grl <- GRangesList(tx1_1 = ORF)
# RFP is 1 width position based GRanges
RFP <- GRanges("1", IRanges(c(1, 25, 35, 38), width = 1), "+")
score(RFP) <- c(28, 28, 28, 29) # original width in score col
cds <- GRangesList(tx1 = GRanges("1", IRanges(35, 44), "+"))
# grl must have same names as cds + _1 etc, so that they can be matched.
floss(grl, RFP, cds)
# or change ribosome start/stop, more strict
floss(grl, RFP, cds, 28, 28)
```

fpm

Create normalizations of overlapping read counts.

Description

FPKM is short for "Fragments Per Kilobase of transcript per Million fragments". When calculating RiboSeq data FPKM over ORFs use ORFs as 'grl'. When calculating RNASeq data FPKM use full transcripts as 'grl'.

Usage

```
fpm(grl, reads, pseudoCount = 0)
```

Arguments

grl	a GRangesList object can be either transcripts, 5' utrs, cds', 3' utrs or ORFs as a special case (uORFs, potential new cds' etc).
reads	a GAlignment , GRanges or GRangesList object, usually of RiboSeq, RnaSeq, CageSeq, etc.
pseudoCount	an integer, by default is 0, set it to 1 if you want to avoid NA and inf values.

Value

a numeric vector with the fpm values

References

doi: 10.1038/nbt.1621

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpm_calc](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
ORF <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 10, 20),
                               end = c(5, 15, 25)),
               strand = "+")
gr1 <- GRangesList(tx1_1 = ORF)
RFP <- GRanges("1", IRanges(25, 25), "+")
fpm(gr1, RFP)
```

fpm_calc

Create normalizations of counts

Description

A helper for [fpm()] Normally use function [fpm()], if you want unusual normalization , you can use this. Short for: Fragments per kilobase of transcript per million fragments Normally used in Translations efficiency calculations

Usage

```
fpm_calc(counts, lengthSize, librarySize)
```

Arguments

counts	a list, # of read hits per group
lengthSize	a list of lengths per group
librarySize	a numeric of size 1, the # of reads in library

Value

a numeric vector

References

doi: 10.1038/nbt.1621

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

fractionLength	<i>Fraction Length</i>
----------------	------------------------

Description

Fraction Length is defined as

$$(\text{lengths of } \text{grl}) / (\text{length of } \text{tx_len})$$

so that each group in the grl is divided by the corresponding transcript.

Usage

```
fractionLength(grl, tx_len)
```

Arguments

grl	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs. ORFs are a special case, see argument tx_len
tx_len	the transcript lengths of the transcripts, a named (tx names) vector of integers. If you have the transcripts as GRangesList, call 'ORFik::widthPerGroup(tx, TRUE)'. If you used CageSeq to reannotate leaders, then the tss for the the leaders have changed, therefore the tx lengths have changed. To account for that call: 'tx_len <- widthPerGroup(extendLeaders(tx, cageFiveUTRs))' and calculate fraction length using 'fractionLength(grl, tx_len)'.

Value

a numeric vector of ratios

References

doi: 10.1242/dev.098343

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
ORF <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 10, 20), end = c(5, 15, 25)),
               strand = "+")
grl <- GRangesList(tx1_1 = ORF)
# grl must have same names as cds + _1 etc, so that they can be matched.
tx <- GRangesList(tx1 = GRanges("1", IRanges(1, 50), "+"))
fractionLength(grl, ORFik::widthPerGroup(tx, keep.names = TRUE))
```

fread.bed	<i>Load bed file as GRanges.</i>
-----------	----------------------------------

Description

Wraps around `rtracklayer::import.bed` and tries to speed up loading with the use of `data.table`. Supports `gzip`, `gz`, `bgz` and `bed` formats.

Usage

```
fread.bed(filePath)
```

Arguments

`filePath` The location of the bed file

Value

a `GRanges` object

Examples

```
# path to example CageSeq data from hg19 heart sample
cageData <- system.file("extdata", "cage-seq-heart.bed.bgz",
                       package = "ORFik")
fread.bed(cageData)
```

<code>getStartStopWindows</code>	<i>Get Start and Stop codon within specified windows over CDS.</i>
----------------------------------	--

Description

For each `cds` in `'txdb'` object, filtered by `'txNames'`, get a window around start and stop codons within `'window_size'` downstream and upstream of the codon.

Usage

```
getStartStopWindows(txdb, txNames, start = TRUE, stop = TRUE,
                    window_size = 30L, cds = NULL)
```

Arguments

txdb	a txdb object of annotations
txNames	a character vector of the transcript names to use
start	(logical) whether to include start codons
stop	(logical) whether to include stop codons
window_size	(integer) size of the window to extract upstream of the start/stop codon and downstream
cds	a GRangesList with cds, a speedup if you already have them loaded.

Value

a list with two slots "starts" and "stops", each contains a GRangesList of windows around start and stop codons for the transcripts of interest

Examples

```
gtf_file <- system.file("extdata", "annotations.gtf", package = "ORFik")
txdb <- GenomicFeatures::makeTxDbFromGFF(gtf_file, format = "gtf")
txNames <- txNamesWithLeaders(txdb)
getStartStopWindows(txdb, txNames)
```

groupGRangesBy	<i>Group GRanges</i>
----------------	----------------------

Description

It will group / split the GRanges object by the argument 'other'. For example if you would like to group GRanges object by gene, set other to gene names.

Usage

```
groupGRangesBy(gr, other = NULL)
```

Arguments

gr	a GRanges object
other	a vector of unique names to group by

Details

If 'other' is not specified function will try to use the names of the GRanges object. It will then be similar to 'split(gr, names(gr))'.

It is important that all groups in 'other' are unique, otherwise duplicates will be grouped together.

Value

a GRangesList named after names(Granges) if other is NULL, else names are from unique(other)

Examples

```

ORFranges <- GRanges(seqnames = Rle(rep("1", 3)),
                    ranges = IRanges(start = c(1, 10, 20),
                                     end = c(5, 15, 25)),
                    strand = "+")
ORFranges2 <- GRanges("1",
                    ranges = IRanges(start = c(20, 30, 40),
                                     end = c(25, 35, 45)),
                    strand = "+")
names(ORFranges) = rep("tx1_1", 3)
names(ORFranges2) = rep("tx1_2", 3)
gr1 <- GRangesList(tx1_1 = ORFranges, tx1_2 = ORFranges2)
gr <- unlist(gr1, use.names = FALSE)
## now recreate the gr1
## group by orf
grltest <- groupGRangesBy(gr) # using the names to group
identical(gr1, grltest) ## they are identical

## group by transcript
names(gr) <- txNames(gr)
grltest <- groupGRangesBy(gr)
identical(gr1, grltest) ## they are not identical

```

gSort

*Sort a GRangesList, helper.***Description**

A helper for [sortPerGroup()]. A faster, more versatile reimplementaion of GenomicRanges::sort(). Normally not used directly. Groups first each group, then either decreasing or increasing (on starts if byStarts == T, on ends if byStarts == F)

Usage

```
gSort(gr1, decreasing = FALSE, byStarts = TRUE)
```

Arguments

gr1	a GRangesList
decreasing	should the first in each group have max(start(group)) ->T or min-> default(F) ?
byStarts	a logical T, should it order by starts or ends F.

Value

an equally named GRangesList, where each group is sorted within group.

hasHits *Hits from reads*

Description

Finding GRanges groups that have overlap hits with reads

Usage

```
hasHits(grl, reads, keep.names = FALSE)
```

Arguments

grl a GRanges or GRangesList
 reads a GAlignment or GRanges object with reads
 keep.names logical (F), keep names or not

Value

a list of logicals, T == hit, F == no hit

insideOutsideORF *Inside/Outside score (IO)*

Description

Inside/Outside score is defined as

$$\frac{\text{reads over ORF}}{\text{reads outside ORF and within transcript}}$$

A pseudo-count of one was added to both the ORF and outside sums.

Usage

```
insideOutsideORF(grl, RFP, GtfOrTx)
```

Arguments

grl a GRangesList object with usually either leaders, cds', 3' utrs or ORFs
 RFP ribo seq reads as GAlignment, GRanges or GRangesList object
 GtfOrTx if Gtf: a TxDb object of a gtf file that transcripts will be extracted with 'ex-
 onsBy(Gtf, by = "tx", use.names = TRUE)', if a GrangesList will use as is

Value

a named vector of numeric values of scores

References

doi: 10.1242/dev.098345

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
# Check inside outside score of a ORF within a transcript
ORF <- GRanges("1",
               ranges = IRanges(start = c(20, 30, 40),
                                end = c(25, 35, 45)),
               strand = "+")

grl <- GRangesList(tx1_1 = ORF)

tx1 <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 10, 20, 30, 40, 50),
                                end = c(5, 15, 25, 35, 45, 200)),
               strand = "+")
tx <- GRangesList(tx1 = tx1)
RFP <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 4, 30, 60, 80, 90),
                                end = c(30, 33, 63, 90, 110, 120)),
               strand = "+")

insideOutsideORF(grl, RFP, tx)
```

is.grl

Helper function to check for GRangesList

Description

Helper function to check for GRangesList

Usage

```
is.grl(class)
```

Arguments

class	the class you want to check if is GRL, either a character from class or the object itself.
-------	--

Value

a boolean

`is.gr_or_grl` *Helper function to check for GRangesList or GRanges class*

Description

Helper function to check for GRangesList or GRanges class

Usage

```
is.gr_or_grl(class)
```

Arguments

`class` the class you want to check if is GRL or GR, either a character from class or the object itself.

Value

a boolean

`isInFrame` *Find frame for each orf relative to cds*

Description

Input of this function, is the output of the function [distToCds()]

Usage

```
isInFrame(dists)
```

Arguments

`dists` a vector of distances between ORF and cds

Details

possible outputs: 0: orf is in frame with cds 1: 1 shifted from cds 2: 2 shifted from cds

Value

a logical vector

References

doi: 10.1074/jbc.R116.733899

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
# simple example
isInFrame(c(3,6,8,11,15))

# GRangesList example
gr1 <- GRangesList(tx1_1 = GRanges("1", IRanges(1,10), "+"))
fiveUTRs <- GRangesList(tx1 = GRanges("1", IRanges(1,20), "+"))
dist <- distToCds(gr1, fiveUTRs, extension = 0)
isInFrame <- isInFrame(dist)
```

isOverlapping

Find frame for each orf relative to cds

Description

Input of this function, is the output of the function [distToCds()]

Usage

```
isOverlapping(dists)
```

Arguments

dists a vector of distances between ORF and cds

Value

a logical vector

References

doi: 10.1074/jbc.R116.733899

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
# # simple example
isOverlapping(c(-3,-6,8,11,15))

# GRangesList example
gr1 <- GRangesList(tx1_1 = GRanges("1", IRanges(1,10), "+"))
fiveUTRs <- GRangesList(tx1 = GRanges("1", IRanges(1,20), "+"))
dist <- distToCds(gr1, fiveUTRs, extension = 0)
isOverlapping <- isOverlapping(dist)
```

isPeriodic	<i>Find if there is periodicity in the vector</i>
------------	---

Description

Find if there is periodicity in the vector

Usage

```
isPeriodic(x)
```

Arguments

x (numeric) Vector of values to detect periodicity of 3 like in RiboSeq data.

Value

a logical, if it is periodic.

kozakSequenceScore	<i>Make a score for each ORFs start region by proximity to Kozak</i>
--------------------	--

Description

The closer the sequence is to the Kozak sequence the higher the score, based on the experimental pwm from article referenced. Minimum score is 0 (worst correlation), max is 1 (the best base per column was chosen).

Usage

```
kozakSequenceScore(gr1, faFile, species = "human", include.N = FALSE)
```

Arguments

gr1	a GRangesList grouped by ORF
faFile	a FaFile from the fasta file, see ?FaFile. Can also be path to fastaFile with fai file in same dir.
species	("human"), which species to use, currently supports human, zebrafish and mouse (m. musculus). You can also specify a pfm for your own species. Syntax of pfm is an rectangular integer matrix, where all columns must sum to the same value, normally 100. See example for more information. Rows are in order: c("A", "C", "G", "T")
include.N	logical (F), if TRUE, allow N bases to be counted as hits, score will be average of the other bases. If True, N bases will be added to pfm, automatically, so dont include them if you make your own pfm.

Value

a numeric vector with values between 0 and 1
 an integer vector, one score per orf

References

doi: <https://doi.org/10.1371/journal.pone.0108475>

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
# Usually the ORFs are found in orfik, which makes names for you etc.
# Here we make an example from scratch
seqName <- "Chromosome"
ORF1 <- GRanges(seqnames = seqName,
                ranges = IRanges(c(1007, 1096), width = 60),
                strand = c("+", "+"))
ORF2 <- GRanges(seqnames = seqName,
                ranges = IRanges(c(400, 100), width = 30),
                strand = c("-", "-"))
ORFs <- GRangesList(tx1 = ORF1, tx2 = ORF2)
ORFs <- makeORFNames(ORFs) # need ORF names
# get faFile for sequences
faFile <- FaFile(system.file("extdata", "genome.fasta",
                             package = "ORFik"))
kozakSequenceScore(ORFs, faFile)
# For more details see vignettes.
```

lastExonEndPerGroup *Get last end per granges group*

Description

Get last end per granges group

Usage

```
lastExonEndPerGroup(gr1, keep.names = TRUE)
```

Arguments

gr1 a [GRangesList](#)
 keep.names a boolean, keep names or not

Value

a [Rle](#)(keep.names = T), or integer vector(F)

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
lastExonEndPerGroup(grl)
```

lastExonPerGroup *Get last exon per GRangesList group*

Description

grl must be sorted, call `ORFik:::sortPerGroup` if needed

Usage

```
lastExonPerGroup(grl)
```

Arguments

grl a [GRangesList](#)

Value

a `GRangesList` of the last exon per group

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
lastExonPerGroup(grl)
```

lastExonStartPerGroup *Get last start per granges group*

Description

Get last start per granges group

Usage

```
lastExonStartPerGroup(grl, keep.names = TRUE)
```

Arguments

`gr1` a [GRangesList](#)
`keep.names` a boolean, keep names or not

Value

a `Rle(keep.names = T)`, or integer vector(`F`)

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
gr1 <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
lastExonStartPerGroup(gr1)
```

makeExonRanks	<i>Make a meta column with exon ranks</i>
---------------	---

Description

Must be ordered, so that same transcripts are ordered together.

Usage

```
makeExonRanks(gr1, byTranscript = FALSE)
```

Arguments

`gr1` a [GRangesList](#)
`byTranscript` if ORfs are by transcript, check duplicates

Value

an integer vector of indices for exon ranks

makeORFNames	<i>Make ORF names per orf</i>
--------------	-------------------------------

Description

grl must be grouped by transcript If a list of orfs are grouped by transcripts, but does not have ORF names, then create them and return the new GRangesList

Usage

```
makeORFNames(grl)
```

Arguments

grl a [GRangesList](#)

Value

(GRangesList) with ORF names, grouped by transcripts, sorted.

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
makeORFNames(grl)
```

mapToGRanges	<i>Map orfs to genomic coordinates</i>
--------------	--

Description

Creates GRangesList from the results of ORFs_as_List and the GRangesList used to find the ORFs

Usage

```
mapToGRanges(grl, result)
```

Arguments

grl A [GRangesList](#) of the original sequences that gave the orfs
 result List. A list of the results of finding uorfs list syntax is: result[1] contain grouping indices, named index result[2] contains two columns of start and stops, named orf

Value

A [GRangesList](#) of ORFs.

matchNaming	<i>Match naming of GRangesList</i>
-------------	------------------------------------

Description

Given a GRangesList and a reference, make the naming convention and the number of metacolumns equal to reference

Usage

```
matchNaming(gr, reference)
```

Arguments

gr	a GRangesList or GRanges object
reference	a GRangesList of a reference

Value

a GRangesList

matchSeqlevels	<i>Match seqnames</i>
----------------	-----------------------

Description

Check that seqlevels of fiveUTRs and cage uses the same standard, i.g chr1 vs 1.

Usage

```
matchSeqlevels(filteredCage, fiveUTRs)
```

Arguments

filteredCage	Cage-data to check seqnames in
fiveUTRs	The 5' leader sequences as GRangesList

Value

filteredCage with matched seqnames convention

metaWindow	<i>Calculate metaplot coverage of reads around input GRangesList object.</i>
------------	--

Description

Sums up coverage over set of GRanges objects that.

Usage

```
metaWindow(x, windows)
```

Arguments

x	GRanges object of your reads. You should resize them beforehand to width of 1 to focus on 5' ends of footprints.
windows	GRanges object of your CDSs start or stop positions. Its width has to be even number as we will assume in the middle is position zero which is included in the downstream window.

Value

A data.frame with average counts (avg_counts) of reads mapped to positions (position) specified in windows along with frame (frame).

Examples

```
windows <- GenomicRanges::GRangesList(
  GenomicRanges::GRanges(seqnames = "chr1",
    ranges = IRanges::IRanges(c(50, 100), c(80, 200)),
    strand = "-")
)
x <- GenomicRanges::GRanges(
  seqnames = "chr1",
  ranges = IRanges::IRanges(c(100, 180), c(200, 300)),
  strand = "-"
)
metaWindow(x, windows)
```

numExonsPerGroup	<i>Get list of the number of exons per group</i>
------------------	--

Description

Can also be used generally to get number of GRanges object per GRangesList group

Usage

```
numExonsPerGroup(gr1, keep.names = TRUE)
```


Arguments

grl a GRangesList
 keep.names a boolean, keep names or not

Value

an integer vector of counts

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
numExonsPerGroup(grl)
```

orfID	<i>Get id's for orf</i>
-------	-------------------------

Description

These id's can be uniquely identified by isoform etc, this is not supported by GenomicRanges.

Usage

```
orfID(grl, with.tx = FALSE)
```

Arguments

grl a [GRangesList](#)
 with.tx a boolean, include transcript names, if you want unique orfs, so that they don't have multiple versions on different isoforms, set it to FALSE.

Value

a character vector of ids, 1 per orf

orfScore *Get ORFscore for a GRangesList of ORFs*

Description

ORFscore tries to check whether the first frame of the 3 possible frames in an ORF has more reads than second and third frame.

Usage

```
orfScore(grl, RFP, is.sorted = FALSE)
```

Arguments

grl	a GRangesList object with ORFs
RFP	ribosomal footprints, given as Galignment object, Granges or GRangesList
is.sorted	logical (F), is grl sorted.

Details

Pseudocode: assume rff - is reads fraction in specific frame

$$\text{ORFscore} = \log(\text{rrf1} + \text{rrf2} + \text{rrf3})$$

For all ORFs where rrf2 or rrf3 is bigger than rrf1, negate the resulting value.

```
ORFscore[rrf1Smaller] <- ORFscore[rrf1Smaller] * -1
```

As result there is one value per ORF: Positive values say that the first frame have the most reads, negative values say that the first frame does not have the most reads.

Value

a matrix with 4 columns, the orfscore and score of each of the 3 tiles

References

doi: 10.1002/embj.201488411

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```

ORF <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 10, 20), end = c(5, 15, 25)),
               strand = "+")
names(ORF) <- c("tx1", "tx1", "tx1")
gr1 <- GRangesList(tx1_1 = ORF)
RFP <- GRanges("1", IRanges(25, 25), "+") # 1 width position based
score(RFP) <- 28 # original width
orfScore(gr1, RFP) # negative because more hits on frames 1,2 than 0.

# example with positive result, more hits on frame 0 (in frame of ORF)
RFP <- GRanges("1", IRanges(c(1, 1, 1, 25), width = 1), "+")
score(RFP) <- c(28, 29, 31, 28) # original width
orfScore(gr1, RFP)

```

 parseCigar

Shift ribo-seq reads using cigar string

Description

Shift ribo-seq reads using cigar string

Usage

```
parseCigar(cigar, shift, is_plus_strand)
```

Arguments

cigar the cigar of the reads
 shift the shift as numeric
 is_plus_strand logical

Value

the shifted read

rankOrder

ORF rank in transcripts

Description

ig. second orf_2 -> 2

Usage

```
rankOrder(gr1)
```

Arguments

gr1 a [GRangesList](#) object with ORFs

Value

a numeric vector of integers

References

doi: 10.1074/jbc.R116.733899

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpm_calc](#), [fpm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
                  ranges = IRanges(c(7, 14), width = 3),
                  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
                   ranges = IRanges(c(4, 1), c(9, 3)),
                   strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
grl <- ORFik:::makeORFNames(grl)
rankOrder(grl)
```

reassignTSSbyCage	<i>Reassign all Transcript Start Sites (TSS)</i>
-------------------	--

Description

Given a GRangesList of 5' UTRs or transcripts, reassign the start positions using max peaks from CageSeq data. A max peak is defined as new TSS if it is within boundary of 5' leader range, specified by 'extension' in bp. A max peak must also be higher than minimum CageSeq peak cutoff specified in 'filterValue'. The new TSS will then be the positioned where the cage read (with highest read count in the interval).

Usage

```
reassignTSSbyCage(fiveUTRs, cage, extension = 1000, filterValue = 1,
                  cds = NULL)
```

Arguments

fiveUTRs	(GRangesList) The 5' leaders or transcript sequences
cage	Either a filePath for CageSeq file, or already loaded CageSeq peak data as GRanges.
extension	The maximum number of bases upstream of the TSS to search for CageSeq peak.
filterValue	The minimum number of reads on cage position, for it to be counted as possible new tss. (represented in score column in CageSeq data) to If you already filtered, set it to 0.

`cds` (GRangesList) CDS of relative fiveUTRs, applicable only if you want to extend 5' leaders downstream of CDS's, to allow upstream ORFs that can overlap into CDS's.

Value

a GRangesList of newly assigned TSS for fiveUTRs, using CageSeq data.

Examples

```
# example 5' leader, notice exon_rank column
fiveUTRs <- GenomicRanges::GRangesList(
  GenomicRanges::GRanges(seqnames = "chr1",
    ranges = IRanges::IRanges(1000, 2000),
    strand = "+",
    exon_rank = 1))
names(fiveUTRs) <- "tx1"

# make fake CageSeq data from promoter of 5' leaders, notice score column
cage <- GenomicRanges::GRanges(
  seqnames = "chr1",
  ranges = IRanges::IRanges(500, 510),
  strand = "+",
  score = 10)

# finally reassign TSS for fiveUTRs
reassignTSSbyCage(fiveUTRs, cage)
```

reduceKeepAttr

Reduce GRanges / GRangesList

Description

Extends function [GenomicRanges::reduce()] by trying to keep names and meta columns, if it is a GRangesList. It also does not loose sorting for GRangesList, since original reduce sorts all by ascending. If `keep.names == FALSE`, it's just the normal GenomicRanges::reduce with sorting negative strands descending for GRangesList.

Usage

```
reduceKeepAttr(grl, keep.names = FALSE, drop.empty.ranges = FALSE,
  min.gapwidth = 1L, with.revmap = FALSE, with.inframe.attrib = FALSE,
  ignore.strand = FALSE)
```

Arguments

`grl` a GRangesList or GRanges object

`keep.names` (FALSE) keep the names and meta columns of the GRangesList

`drop.empty.ranges` (FALSE) if a group is empty (width 0), delete it.

`min.gapwidth` (1L) how long gap can it be to say they belong together

with.revmap (FALSE) return info on which mapped to which
 with.inframe.attrib (FALSE) For internal use.
 ignore.strand (FALSE), can different strands be reduced together.

Value

A reduced GRangesList

Examples

```
ORF <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 2, 3), end = c(1, 2, 3)),
               strand = "+")
# For GRanges
reduceKeepAttr(ORF, keep.names = TRUE)
# For GRangesList
grl <- GRangesList(tx1_1 = ORF)
reduceKeepAttr(grl, keep.names = TRUE)
```

regroupRleList	<i>Regroup rle from GRangesList</i>
----------------	-------------------------------------

Description

Almost direct copy of IRanges regroupBySupergroup. But only works on rle and GRangesList. This function will be removed if IRanges regroupBySupergroup is exported.

Usage

```
regroupRleList(rle, supergroups)
```

Arguments

rle A RleList to reduce groups on.
 supergroups A GRangesList to group by

Value

A regrouped RleList

removeMetaCols	<i>Removes meta columns</i>
----------------	-----------------------------

Description

Removes meta columns

Usage

```
removeMetaCols(gr1)
```

Arguments

gr1 a GRangesList or GRanges object

Value

same type and structure as input without meta columns

riboSeqReadWidths	<i>Get RiboSeq widths</i>
-------------------	---------------------------

Description

Input a ribo-seq object and get width of reads, if input is p-shifted and GRanges, the "\$score column" must exist, and contain the original read widths.

Usage

```
riboSeqReadWidths(reads)
```

Arguments

reads a GRanges or GAlignment object.

Value

an integer vector of widths

ribosomeReleaseScore *Ribosome Release Score (RRS)*

Description

Ribosome Release Score is defined as

$$(RPFs \text{ over ORF}) / (RPFs \text{ over } 3' \text{ utrs})$$

and additionally normalized by lengths. If RNA is added as argument, it will normalize by RNA counts to justify location of 3' utrs. It can be understood as a ribosome stalling feature. A pseudo-count of one was added to both the ORF and downstream sums.

Usage

```
ribosomeReleaseScore(gr1, RFP, GtfOrThreeUtrs, RNA = NULL)
```

Arguments

gr1	a GRangesList object with usually either leaders, cds', 3' utrs or ORFs.
RFP	RiboSeq reads as GAlignment , GRanges or GRangesList object
GtfOrThreeUtrs	if Gtf: a TxDb object of a gtf file transcripts is called from: 'threeUTRsByTranscript(Gtf, use.names = TRUE)', if object is GRangesList , it is presumed to be the 3' utrs
RNA	RnaSeq reads as GAlignment , GRanges or GRangesList object

Value

a named vector of numeric values of scores, NA means that no 3' utr was found for that transcript.

References

doi: 10.1016/j.cell.2013.06.009

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeStallingScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
ORF <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 10, 20), end = c(5, 15, 25)),
               strand = "+")
gr1 <- GRangesList(tx1_1 = ORF)
threeUTRs <- GRangesList(tx1 = GRanges("1", IRanges(40, 50), "+"))
RFP <- GRanges("1", IRanges(25, 25), "+")
RNA <- GRanges("1", IRanges(1, 50), "+")
ribosomeReleaseScore(gr1, RFP, threeUTRs, RNA)
```

ribosomeStallingScore *Ribosome Stalling Score (RSS)*

Description

Is defined as

$$\frac{\text{(RPFs over ORF stop sites)}}{\text{(RPFs over ORFs)}}$$

and normalized by lengths A pseudo-count of one was added to both the ORF and downstream sums.

Usage

```
ribosomeStallingScore(gr1, RFP)
```

Arguments

gr1 a [GRangesList](#) object with usually either leaders, cds', 3' utrs or ORFs.
RFP RiboSeq reads as [GAlignment](#), [GRanges](#) or [GRangesList](#) object

Value

a named vector of numeric values of RSS scores

References

doi: 10.1016/j.cels.2017.08.004

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [subsetCoverage](#), [translationalEff](#)

Examples

```
ORF <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 10, 20), end = c(5, 15, 25)),
               strand = "+")
gr1 <- GRangesList(tx1_1 = ORF)
RFP <- GRanges("1", IRanges(25, 25), "+")
ribosomeStallingScore(gr1, RFP)
```

seqnamesPerGroup	<i>Get list of seqnames per granges group</i>
------------------	---

Description

Get list of seqnames per granges group

Usage

```
seqnamesPerGroup(gr1, keep.names = TRUE)
```

Arguments

gr1	a GRangesList
keep.names	a boolean, keep names or not

Value

a character vector or Rle of seqnames(if seqnames == T)

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
                  ranges = IRanges(c(7, 14), width = 3),
                  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
                   ranges = IRanges(c(4, 1), c(9, 3)),
                   strand = c("-", "-"))
gr1 <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
seqnamesPerGroup(gr1)
```

shiftFootprints	<i>Shift footprints by selected offsets</i>
-----------------	---

Description

Function shifts footprints (GRanges) using specified offsets for every of the specified lengths. Reads that do not conform to the specified lengths are filtered out and rejected. Reads are resized to single base in 5' end fashion, treated as p site. This function takes account for junctions in cigars of the reads. Length of the footprint is saved in size' parameter of GRanges output. Footprints are also sorted according to their genomic position, ready to be saved as a bed file.

Usage

```
shiftFootprints(footprints, selected_lengths, selected_shifts)
```

Arguments

`footprints` (GAlignments) object of RiboSeq reads

`selected_lengths`
Numeric vector of lengths of footprints you select for shifting.

`selected_shifts`
Numeric vector of shifts for corresponding `selected_lengths`. eg. `c(10, -10)` with `selected_lengths` of `c(31, 32)` means length of 31 will be shifted left by 10. Footprints of length 32 will be shifted right by 10.

Value

A GRanges object of shifted footprints, sorted and resized to 1bp of p-site, with metacolumn "size" indicating footprint size before shifting and resizing.

Examples

```
## Not run:
gtf_file <- system.file("extdata", "annotations.gtf", package = "ORFik")
txdb <- GenomicFeatures::makeTxDbFromGFF(gtf_file, format = "gtf")
riboSeq_file <- system.file("extdata", "ribo-seq.bam", package = "ORFik")
footprints <- GenomicAlignments::readGAlignments(
  riboSeq_file, param = ScanBamParam(flag = scanBamFlag(
    isDuplicate = FALSE, isSecondaryAlignment = FALSE)))
# detect the shifts automagically
shifts <- detectRibosomeShifts(footprints, txdb)
# shift the RiboSeq footprints
shiftedReads <- shiftFootprints(footprints, shifts$fragment_length,
  shifts$offsets_start)

## End(Not run)
```

sortPerGroup	<i>Sort a GRangesList</i>
--------------	---------------------------

Description

A faster, more versatile reimplementaion of `sort.GenomicRanges` for `GRangesList`, which works poorly for more than 10k groups. This function sorts each group, where "+" strands are increasing by starts and "-" strands are decreasing by ends.

Usage

```
sortPerGroup(grl, ignore.strand = FALSE)
```

Arguments

`grl` a `GRangesList`

`ignore.strand` a boolean, if FALSE: should minus strands be sorted from highest to lowest ends. If TRUE: from lowest to highest ends.

Value

an equally named GRangesList, where each group is sorted within group.

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(14, 7), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(1, 4), c(3, 9)),
  strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
sortPerGroup(grl)
```

startCodons	<i>Get the Start codons(3 bases) from a GRangesList of orfs grouped by orfs</i>
-------------	---

Description

In ATGTTTTGC, get the positions ATG. It takes care of exons boundaries, with exons < 3 length.

Usage

```
startCodons(grl, is.sorted = FALSE)
```

Arguments

grl	a GRangesList object
is.sorted	a boolean, a speedup if you know the ranges are sorted

Value

a GRangesList of start codons, since they might be split on exons

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
startCodons(grl, is.sorted = FALSE)
```

startDefinition	<i>Returns start definitions</i>
-----------------	----------------------------------

Description

According to: <<http://www.ncbi.nlm.nih.gov/Taxonomy/taxonomyhome.html/index.cgi?chapter=tgencodes#SG1>> ncbi genetic code number for translation.

Usage

```
startDefinition(transl_table)
```

Arguments

transl_table numeric. NCBI genetic code number for translation.

Value

A string of START sites separated with "|".

See Also

Other findORFs: [findMapORFs](#), [findORFsFasta](#), [findORFs](#), [stopDefinition](#)

Examples

```
startDefinition
startDefinition(1)
```

startSites	<i>Get the start sites from a GRangesList of orfs grouped by orfs</i>
------------	---

Description

In ATGTTTTGG, get the position of the A.

Usage

```
startSites(grl, asGR = FALSE, keep.names = FALSE, is.sorted = FALSE)
```

Arguments

grl a [GRangesList](#) object
asGR a boolean, return as GRanges object
keep.names if asGR is False, do you still want to keep a named vector
is.sorted a speedup, if you know the ranges are sorted

Value

if asGR is False, a vector, if True a GRanges object

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
startSites(grl, is.sorted = FALSE)
```

stopCodons	<i>Get the Stop codons (3 bases) from a GRangesList of orfs grouped by orfs</i>
------------	---

Description

In ATGTTTTGC, get the positions TGC. It takes care of exons boundaries, with exons < 3 length.

Usage

```
stopCodons(grl, is.sorted = FALSE)
```

Arguments

grl	a GRangesList object
is.sorted	a boolean, a speedup if you know the ranges are sorted

Value

a GRangesList of stop codons, since they might be split on exons

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
stopCodons(grl, is.sorted = FALSE)
```

stopDefinition	<i>Returns stop definitions</i>
----------------	---------------------------------

Description

According to: <<http://www.ncbi.nlm.nih.gov/Taxonomy/taxonomyhome.html/index.cgi?chapter=tgencodes#SG1>> ncbi genetic code number for translation.

Usage

```
stopDefinition(transl_table)
```

Arguments

transl_table numeric. NCBI genetic code number for translation.

Value

A string of STOP sites separated with "|".

See Also

Other findORFs: [findMapORFs](#), [findORFsFasta](#), [findORFs](#), [startDefinition](#)

Examples

```
stopDefinition
stopDefinition(1)
```

stopSites	<i>Get the stop sites from a GRangesList of orfs grouped by orfs</i>
-----------	--

Description

In ATGTTTTGC, get the position of the C.

Usage

```
stopSites(grl, asGR = FALSE, keep.names = FALSE, is.sorted = FALSE)
```

Arguments

grl a [GRangesList](#) object
asGR a boolean, return as GRanges object
keep.names if asGR is False, do you still want to keep a named vector
is.sorted a speedup, if you know the ranges are sorted

Value

if asGR is False, a vector, if True a GRanges object

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
grl <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
stopSites(grl, is.sorted = FALSE)
```

strandBool

Get logical list of strands

Description

Helper function to get a logical list of True/False, if GRangesList group have + strand = T, if - strand = F Also checks for * strands, so a good check for bugs

Usage

```
strandBool(grl)
```

Arguments

grl a [GRangesList](#) or GRanges object

Value

a logical vector

Examples

```
gr <- GRanges(Rle(c("chr2", "chr2", "chr1", "chr3"), c(1, 3, 2, 4)),
  IRanges(1:10, width = 10:1),
  Rle(strand(c("-", "+", "*", "+", "-")), c(1, 2, 2, 3, 2)))
strandBool(gr)
```

strandPerGroup	<i>Get list of strands per granges group</i>
----------------	--

Description

Get list of strands per granges group

Usage

```
strandPerGroup(gr1, keep.names = TRUE)
```

Arguments

gr1	a GRangesList
keep.names	a boolean, keep names or not

Value

a vector named/unnamed of characters

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
gr1 <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)
strandPerGroup(gr1)
```

subsetCoverage	<i>Subset GRanges to get coverage.</i>
----------------	--

Description

GRanges object should be beforehand tiled to size of 1. This subsetting takes account for strand.

Usage

```
subsetCoverage(cov, y)
```

Arguments

cov	A coverage object from coverage()
y	GRanges object for which coverage should be extracted

Value

numeric vector of coverage of input GRanges object

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpm_calc](#), [fpm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [translationalEff](#)

subset_to_frame	<i>Subset GRanges to get desired frame. GRanges object should be beforehand tiled to size of 1. This subsetting takes account for strand.</i>
-----------------	---

Description

Subset GRanges to get desired frame. GRanges object should be beforehand tiled to size of 1. This subsetting takes account for strand.

Usage

```
subset_to_frame(x, frame)
```

Arguments

x	A tiled to size of 1 GRanges object
frame	A numeric indicating which frame to extract

Value

GRanges object reduced to only first frame

tile1	<i>Tile a GRangesList by 1</i>
-------	--------------------------------

Description

Will tile a GRangesList into single bp resolution, each group of the list will be splited by positions of 1. Returned values are sorted. This is not supported originally by GenomicRanges. As a precaution, this function requires the unlisted objects to have names.

Usage

```
tile1(grl, sort.on.return = TRUE, matchNaming = TRUE)
```

Arguments

grl	a GRangesList object with names
sort.on.return	logical (T), should the groups be sorted before return.
matchNaming	logical (T), should groups keep unlisted names and meta data.(This make the list very big, for > 100K groups)

Value

a GRangesList grouped by original group, tiled to 1

Examples

```
gr1 <- GRanges("1", ranges = IRanges(start = c(1, 10, 20),
                                     end = c(5, 15, 25)),
              strand = "+")
gr2 <- GRanges("1", ranges = IRanges(start = c(20, 30, 40),
                                     end = c(25, 35, 45)),
              strand = "+")
names(gr1) = rep("tx1_1", 3)
names(gr2) = rep("tx1_2", 3)
grl <- GRangesList(tx1_1 = gr1, tx1_2 = gr2)
tile1(grl)
```

translationalEff	<i>Translational efficiency</i>
------------------	---------------------------------

Description

Uses RnaSeq and RiboSeq to get translational efficiency of every element in 'grl'. Translational efficiency is defined as:

$$(\text{density of RPF within ORF}) / (\text{RNA expression of ORFs transcript})$$
Usage

```
translationalEff(grl, RNA, RFP, tx, with.fpkm = FALSE, pseudoCount = 0)
```

Arguments

grl	a GRangesList object can be either transcripts, 5' utrs, cds', 3' utrs or ORFs as a special case (uORFs, potential new cds' etc).
RNA	RnaSeq reads as GAlignment, GRanges or GRangesList object
RFP	RiboSeq reads as GAlignment, GRanges or GRangesList object
tx	a GRangesList of the transcripts. If you used cage data, then the tss for the the leaders have changed, therefor the tx lengths have changed. To account for that call: ' translationalEff(grl, RNA, RFP, tx = extendLeaders(tx, cageFiveUTRs)) ' where cageFiveUTRs are the reannotated by CageSeq data leaders.
with.fpkm	logical F, if true return the fpkm values together with translational efficiency
pseudoCount	an integer, 0, set it to 1 if you want to avoid NA and inf values. It also helps against bias from low depth libraries.

Value

a numeric vector of fpkm ratios, if with.fpkm is TRUE, return a data.table with te and fpkm values

References

doi: 10.1126/science.1168978

See Also

Other features: [computeFeaturesCage](#), [computeFeatures](#), [disengagementScore](#), [distToCds](#), [entropy](#), [floss](#), [fpkm_calc](#), [fpkm](#), [fractionLength](#), [insideOutsideORF](#), [isInFrame](#), [isOverlapping](#), [kozakSequenceScore](#), [orfScore](#), [rankOrder](#), [ribosomeReleaseScore](#), [ribosomeStallingScore](#), [subsetCoverage](#)

Examples

```
ORF <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 10, 20), end = c(5, 15, 25)),
               strand = "+")
grl <- GRangesList(tx1_1 = ORF)
RFP <- GRanges("1", IRanges(25, 25), "+")
RNA <- GRanges("1", IRanges(1, 50), "+")
tx <- GRangesList(tx1 = GRanges("1", IRanges(1, 50), "+"))
# grl must have same names as cds + _1 etc, so that they can be matched.
te <- translationalEff(grl, RNA, RFP, tx, with.fpkm = TRUE, pseudoCount = 1)
te$fpkmRFP
te$te
```

txLen

Get transcript lengths

Description

A helper function for easy length retrieval

Usage

```
txLen(Gtf = NULL, changedFiveUTRs = NULL)
```

Arguments

Gtf a TxDb object of a gtf file

changedFiveUTRs

a GRangesList object of leaders. Only add this if you used cage data or other things to change the leaders, therefore we need it to update transcript lengths.

Value

a vector of transcript lengths

txNames	<i>Get transcript names from orf names</i>
---------	--

Description

names must either be a column called names, or the names of the grl object

Usage

```
txNames(grl, unique = FALSE)
```

Arguments

grl	a GRangesList grouped by ORF or GRanges object
unique	a boolean, if true unique the names, used if several orfs map to same transcript and you only want the unique groups

Value

a character vector of transcript names, without `_*` naming

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),
  ranges = IRanges(c(7, 14), width = 3),
  strand = c("+", "+"))
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),
  ranges = IRanges(c(4, 1), c(9, 3)),
  strand = c("-", "-"))
grl <- GRangesList(tx1_1 = gr_plus, tx2_1 = gr_minus)
# there are 2 orfs, both the first on each transcript
txNames(grl)
```

txNamesWithLeaders	<i>Get the transcripts that have minimum lengths of leaders and cds.</i>
--------------------	--

Description

Filter transcripts to those who have 5' UTR, CDS, 3' UTR of some lengths, pick the longest per gene.

Usage

```
txNamesWithLeaders(txdb, minFiveUTR = 30L, minCDS = 150L,
  minThreeUTR = 30L)
```

Arguments

txdb	a TxDb object from gtf
minFiveUTR	(integer) minimum bp for 5' UTR during filtering for the transcripts
minCDS	(integer) minimum bp for CDS during filtering for the transcripts
minThreeUTR	(integer) minimum bp for 3' UTR during filtering for the transcripts

Value

a character vector of valid transcript names

Examples

```
gtf_file <- system.file("extdata", "annotations.gtf", package = "ORFik")
txdb <- GenomicFeatures::makeTxDbFromGFF(gtf_file, format = "gtf")
txNames <- txNamesWithLeaders(txdb)
```

txSeqsFromFa	<i>Get transcript sequence from a GRangesList and a faFile or BSgenome</i>
--------------	--

Description

A small safety wrapper around `GenomicFeatures::extractTranscriptSeqs`

Usage

```
txSeqsFromFa(grl, faFile, is.sorted = FALSE)
```

Arguments

<code>grl</code>	a <code>GRangesList</code> object
<code>faFile</code>	<code>FaFile</code> or <code>BSgenome</code> used to find the transcripts,
<code>is.sorted</code>	a speedup, if you know the ranges are sorted

Value

a `DNASTringSet` of the transcript sequences

uniqueGroups	<i>Get the unique set of groups in a GRangesList</i>
--------------	--

Description

Sometimes `GRangesList` groups might be identical, for example ORFs from different isoforms can have identical ranges. Use this function to reduce these groups to unique elements in `GRangesList` `grl`, without names and metacolumns.

Usage

```
uniqueGroups(grl)
```

Arguments

<code>grl</code>	a <code>GRangesList</code>
------------------	----------------------------

Value

a GRangesList of unique orfs

Examples

```
gr1 <- GRanges("1", IRanges(1,10), "+")
gr2 <- GRanges("1", IRanges(20, 30), "+")
# make a grl with duplicated ORFs (gr1 twice)
grl <- GRangesList(tx1_1 = gr1, tx2_1 = gr2, tx3_1 = gr1)
uniqueGroups(grl)
```

uniqueOrder

Get unique ordering for GRangesList groups

Description

This function can be used to calculate unique numerical identifiers for each of the [GRangesList](#) elements. Elements of [GRangesList](#) are unique when the [GRanges](#) inside are not duplicated, so ranges differences matter as well as sorting of the ranges.

Usage

```
uniqueOrder(grl)
```

Arguments

grl a [GRangesList](#)

Value

an integer vector of indices of unique groups

See Also

[uniqueGroups](#)

Examples

```
gr1 <- GRanges("1", IRanges(1,10), "+")
gr2 <- GRanges("1", IRanges(20, 30), "+")
# make a grl with duplicated ORFs (gr1 twice)
grl <- GRangesList(tx1_1 = gr1, tx2_1 = gr2, tx3_1 = gr1)
uniqueOrder(grl) # remember ordering

# example on unique ORFs
uniqueORFs <- uniqueGroups(grl)
# now the orfs are unique, let's map back to original set:
reMappedGr1 <- uniqueORFs[uniqueOrder(grl)]
```

unlistGr1	<i>Safe unlist</i>
-----------	--------------------

Description

Same as [AnnotationDbi::unlist2()], keeps names correctly. One difference is that if gr1 have no names, it will not make integer names, but keep them as null.

Usage

```
unlistGr1(gr1)
```

Arguments

gr1 a GRangesList

Value

a GRanges object

Examples

```
ORF <- GRanges(seqnames = "1",
               ranges = IRanges(start = c(1, 10, 20),
                               end = c(5, 15, 25)),
               strand = "+")
gr1 <- GRangesList(tx1_1 = ORF)
unlistGr1(gr1)
```

upstreamOfPerGroup	<i>Get rest of objects upstream</i>
--------------------	-------------------------------------

Description

Per group get the part upstream of position defined in upstreamOf upstream(tx, ORFik:::stopSites(cds, asGR = F)) will return the 5' utrs per transcript, usually used for interesting parts of the transcripts, like upstream open reading frames(uorf). downstreamOf +/- 1 is start/end site of transformed tx's, depending on strand

Usage

```
upstreamOfPerGroup(tx, upstreamOf)
```

Arguments

tx a [GRangesList](#), usually of Transcripts to be changed
upstreamOf a vector of integers, for each group in tx, where is the new stop point of last valid exon.

Value

a GRangesList of upstream part

validExtension	<i>Helper function to check valid combinations of extension and cage-FiveUTRs</i>
----------------	---

Description

Helper function to check valid combinations of extension and cageFiveUTRs

Usage

```
validExtension(extension, cageFiveUTRs)
```

Arguments

extension	a numeric/integer to reassign 5' utrs.
cageFiveUTRs	a GRangesList, if you used cage-data to extend 5' utrs,

Value

NULL, stop if invalid object

validGRL	<i>Helper Function to check valid GRangesList input</i>
----------	---

Description

Helper Function to check valid GRangesList input

Usage

```
validGRL(class, type = "gr1", checkNULL = FALSE)
```

Arguments

class	as character vector the given class of supposed GRangesList object
type	a character vector, is it gtf, cds, 5', 3', for messages.
checkNULL	should NULL classes be checked and return indices of these?

Value

either NULL or indices (checkNULL == TRUE)

widthPerGroup	<i>Get list of widths per granges group</i>
---------------	---

Description

Get list of widths per granges group

Usage

```
widthPerGroup(gr1, keep.names = TRUE)
```

Arguments

gr1 a [GRangesList](#)
keep.names a boolean, keep names or not

Value

an integer vector (named/unnamed) of widths

Examples

```
gr_plus <- GRanges(seqnames = c("chr1", "chr1"),  
                  ranges = IRanges(c(7, 14), width = 3),  
                  strand = c("+", "+"))  
gr_minus <- GRanges(seqnames = c("chr2", "chr2"),  
                    ranges = IRanges(c(4, 1), c(9, 3)),  
                    strand = c("-", "-"))  
gr1 <- GRangesList(tx1 = gr_plus, tx2 = gr_minus)  
widthPerGroup(gr1)
```

Index

- addFirstCdsOnLeaderEnds, 5
- addNewTSSOnLeaders, 5
- assignAnnotations, 6
- assignFirstExons, 6
- assignFirstExonsStartSite, 7
- assignLastExonsStopSite, 7
- asTX, 8

- bedToGR, 8

- changePointAnalysis, 9
- checkRFP, 9
- checkRNA, 10
- codonSumsPerGroup, 10
- computeFeatures, 11, 13, 19, 20, 22, 32–34, 39–41, 43, 50, 52, 56, 57, 66, 68
- computeFeaturesCage, 11, 12, 19, 20, 22, 32–34, 39–41, 43, 50, 52, 56, 57, 66, 68
- coverageByWindow, 14
- coveragePerTiling, 15

- defineIsoform, 16
- defineTrailer, 16
- detectRibosomeShifts, 17
- disengagementScore, 11, 13, 18, 20, 22, 32–34, 39–41, 43, 50, 52, 56, 57, 66, 68
- distToCds, 11, 13, 19, 19, 22, 32–34, 39–41, 43, 50, 52, 56, 57, 66, 68
- downstreamN, 20
- downstreamOfPerGroup, 21

- entropy, 11, 13, 19, 20, 21, 32–34, 39–41, 43, 50, 52, 56, 57, 66, 68
- extendLeaders, 22
- extendsTSSexons, 23

- filterCage, 23
- findCageUTRFivelen, 24
- findFa, 24
- findMapORFs, 25, 27, 28, 61, 63
- findMaxPeaks, 26
- findNewTSS, 26
- findORFs, 25, 27, 28, 61, 63

- findORFsFasta, 25, 27, 28, 61, 63
- firstEndPerGroup, 29
- firstExonPerGroup, 29
- firstStartPerGroup, 30
- fixSeqnames, 31
- floss, 11, 13, 19, 20, 22, 31, 33, 34, 39–41, 43, 50, 52, 56, 57, 66, 68
- fpkm, 11, 13, 19, 20, 22, 32, 32, 34, 39–41, 43, 50, 52, 56, 57, 66, 68
- fpkm_calc, 11, 13, 19, 20, 22, 32, 33, 33, 34, 39–41, 43, 50, 52, 56, 57, 66, 68
- fractionLength, 11, 13, 19, 20, 22, 32–34, 34, 39–41, 43, 50, 52, 56, 57, 66, 68
- fread.bed, 35

- getStartStopWindows, 35
- GRanges, 71
- GRangesList, 7, 8, 11, 12, 15, 19–22, 25, 29–32, 34, 37, 38, 42–47, 49–51, 53, 56–67, 69–72, 74
- groupGRangesBy, 36
- gSort, 37

- hasHits, 38

- insideOutsideORF, 11, 13, 19, 20, 22, 32–34, 38, 40, 41, 43, 50, 52, 56, 57, 66, 68
- IRanges, 27
- IRangesList, 27
- is.gr_or_grl, 40
- is.grl, 39
- isInFrame, 11, 13, 19, 20, 22, 32–34, 39, 40, 41, 43, 50, 52, 56, 57, 66, 68
- isOverlapping, 11, 13, 19, 20, 22, 32–34, 39, 40, 41, 43, 50, 52, 56, 57, 66, 68
- isPeriodic, 42

- kozakSequenceScore, 11, 13, 19, 20, 22, 32–34, 39–41, 42, 50, 52, 56, 57, 66, 68

- lastExonEndPerGroup, 43
- lastExonPerGroup, 44
- lastExonStartPerGroup, 44

makeExonRanks, 45
makeORFNames, 46
mapToGRanges, 46
matchNaming, 47
matchSeqLevels, 47
metaWindow, 48

numExonsPerGroup, 48

orfID, 49
ORFik (ORFik-package), 4
ORFik-package, 4
orfScore, 11, 13, 19, 20, 22, 32–34, 39–41, 43, 50, 52, 56, 57, 66, 68

parseCigar, 51

rankOrder, 11, 13, 19, 20, 22, 32–34, 39–41, 43, 50, 51, 56, 57, 66, 68
reassignTSSbyCage, 52
reduceKeepAttr, 53
regroupRleList, 54
removeMetaCols, 55
riboSeqReadWidths, 55
ribosomeReleaseScore, 11, 13, 19, 20, 22, 32–34, 39–41, 43, 50, 52, 56, 57, 66, 68
ribosomeStallingScore, 11, 13, 19, 20, 22, 32–34, 39–41, 43, 50, 52, 56, 57, 66, 68

seqnamesPerGroup, 58
shiftFootprints, 58
sort.GenomicRanges, 59
sortPerGroup, 22, 59
startCodons, 60
startDefinition, 25, 27, 28, 61, 63
startSites, 61
stopCodons, 62
stopDefinition, 25, 27, 28, 61, 63
stopSites, 63
strandBool, 64
strandPerGroup, 65
subset_to_frame, 66
subsetCoverage, 11, 13, 19, 20, 22, 32–34, 39–41, 43, 50, 52, 56, 57, 65, 68

tile1, 66
translationalEff, 11, 13, 19, 20, 22, 32–34, 39–41, 43, 50, 52, 56, 57, 66, 67
TxDb, 19
txLen, 68
txNames, 69
txNamesWithLeaders, 69

txSeqsFromFa, 70

uniqueGroups, 70
uniqueOrder, 71
unlistGr1, 72
upstreamOfPerGroup, 72

validExtension, 73
validGRL, 73

widthPerGroup, 74