

Package ‘DelayedMatrixStats’

May 24, 2024

Type Package

Title Functions that Apply to Rows and Columns of 'DelayedMatrix' Objects

Version 1.27.1

Date 2024-04-23

Description A port of the 'matrixStats' API for use with DelayedMatrix objects from the 'DelayedArray' package. High-performing functions operating on rows and columns of DelayedMatrix objects, e.g. col / rowMedians(), col / rowRanks(), and col / rowSds(). Functions optimized per data type and for subsetted calculations such that both memory usage and processing time is minimized.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Depends MatrixGenerics (>= 1.15.1), DelayedArray (>= 0.27.10)

Imports methods, sparseMatrixStats (>= 1.13.2), Matrix (>= 1.5-0), S4Vectors (>= 0.17.5), IRanges (>= 2.25.10)

Suggests testthat, knitr, rmarkdown, BiocStyle, microbenchmark, profmem, HDF5Array, matrixStats (>= 1.0.0)

VignetteBuilder knitr

URL <https://github.com/PeteHaitch/DelayedMatrixStats>

BugReports <https://github.com/PeteHaitch/DelayedMatrixStats/issues>

biocViews Infrastructure, DataRepresentation, Software

git_url <https://git.bioconductor.org/packages/DelayedMatrixStats>

git_branch devel

git_last_commit 0d321c2

git_last_commit_date 2024-05-20

Repository Bioconductor 3.20

Date/Publication 2024-05-24

Author Peter Hickey [aut, cre] (<<https://orcid.org/0000-0002-8153-6258>>),
Hervé Pagès [ctb],
Aaron Lun [ctb]

Maintainer Peter Hickey <peter.hickey@gmail.com>

Contents

colAlls,DelayedMatrix-method	2
colAnyNAs,DelayedMatrix-method	5
colAvgsPerRowSet,DelayedMatrix-method	7
colCollapse,DelayedMatrix-method	8
colCounts,DelayedMatrix-method	10
colCummaxs,DelayedMatrix-method	12
colDiffs,DelayedMatrix-method	15
colIQRDiffs,DelayedMatrix-method	17
colIQRs,DelayedMatrix-method	21
colLogSumExps,DelayedMatrix-method	23
colMads,DelayedMatrix-method	25
colMeans2,DelayedMatrix-method	27
colMedians,DelayedMatrix-method	29
colOrderStats,DelayedMatrix-method	31
colProds,DelayedMatrix-method	33
colQuantiles,DelayedMatrix-method	35
colRanks,DelayedMatrix-method	37
colSums2,DelayedMatrix-method	39
colTabulates,DelayedMatrix-method	41
colVars,DelayedMatrix-method	43
colWeightedMads,DelayedMatrix-method	45
colWeightedMeans,DelayedMatrix-method	47
colWeightedMedians,DelayedMatrix-method	48
colWeightedSds,DelayedMatrix-method	50
DelayedMatrixStats	53
from_DelayedArray_to_simple_seed_class	53
reexports	54
subset_by_Nindex	54

Index	56
--------------	-----------

colAlls,DelayedMatrix-method

Check if all elements in a row (column) of a matrix-like object are equal to a value

Description

Check if all elements in a row (column) of a matrix-like object are equal to a value.

Usage

```
## S4 method for signature 'DelayedMatrix'
colAlls(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
colAnys(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowAlls(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowAnys(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

Arguments

x	A NxK DelayedMatrix .
rows, cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
value	The value to search for.
na.rm	If TRUE , missing values (NA or Nan) are omitted from the calculations.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If TRUE (default), names attributes of result are set. Else if FALSE , no naming support is done.

Details

The S4 methods for x of type **matrix**, **array**, **table**, or **numeric** call **matrixStats::rowAlls** / **matrixStats::colAlls**.

Value

Returns a **logical vector** of length N (K).

Author(s)

Peter Hickey

See Also

- **matrixStats::rowAlls()** and **matrixStats::colAlls()** which are used when the input is a **matrix** or **numeric** vector.
- For checks if *any* element is equal to a value, see **rowAny()**.
- **base::all()**.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                    as.integer((0:4) ^ 2),
                                    seq(-5L, -1L, 1L)),
                                    ncol = 3))
# A DelayedMatrix with a 'SolidRleArraySeed' seed
dm_Rle <- RleArray(Rle(c(rep(1L, 5),
                           as.integer((0:4) ^ 2),
                           seq(-5L, -1L, 1L))),
```

```

dim = c(5, 3))

colAlls(dm_matrix, value = 1)
colAnys(dm_matrix, value = 2)
rowAlls(dm_Rle, value = 1)
rowAnys(dm_Rle, value = 2)

```

colAnyNAs,DelayedMatrix-method

Check if any elements in a row (column) of a matrix-like object is missing

Description

Check if any elements in a row (column) of a matrix-like object is missing.

Usage

```

## S4 method for signature 'DelayedMatrix'
colAnyNAs(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowAnyNAs(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>force_block_processing</code>	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads

	one or more (depending on \link[DelayedArray]{getAutoBlockSize}()) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
...	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>TRUE</code> (default), names attributes of result are set. Else if <code>FALSE</code> , no naming support is done.

Details

The S4 methods for `x` of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowAnyNAs` / `matrixStats::colAnyNAs`.

Value

Returns a `logical vector` of length `N` (`K`).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowAnyNAs()` and `matrixStats::colAnyNAs()` which are used when the input is a `matrix` or `numeric` vector.
- For checks if any element is equal to a value, see `rowAnys()`.
- `base::is.na()` and `base::any()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                    as.integer((0:4) ^ 2),
                                    seq(-5L, -1L, 1L)),
                                    ncol = 3))
# A DelayedMatrix with a 'HDF5ArraySeed' seed
# NOTE: Requires that the HDF5Array package is installed
library(HDF5Array)
dm_HDF5 <- writeHDF5Array(matrix(c(rep(1L, 5),
                                    as.integer((0:4) ^ 2),
                                    seq(-5L, -1L, 1L)),
                                    ncol = 3))

dm_matrix[dm_matrix > 3] <- NA
colAnyNAs(dm_matrix)
dm_HDF5[dm_HDF5 > 3] <- NA
rowAnyNAs(dm_HDF5)
```

colAvgsPerRowSet,DelayedMatrix-method

Calculates for each row (column) a summary statistic for equally sized subsets of columns (rows)

Description

Calculates for each row (column) a summary statistic for equally sized subsets of columns (rows).

Usage

```
## S4 method for signature 'DelayedMatrix'
colAvgsPerRowSet(
  X,
  W = NULL,
  cols = NULL,
  S,
  FUN = colMeans,
  ...,
  force_block_processing = FALSE,
  na.rm = NA,
  tFUN = FALSE
)

## S4 method for signature 'DelayedMatrix'
rowAvgsPerColSet(
  X,
  W = NULL,
  rows = NULL,
  S,
  FUN = rowMeans,
  ...,
  force_block_processing = FALSE,
  na.rm = NA,
  tFUN = FALSE
)
```

Arguments

X	A NxM DelayedMatrix .
W	An optional numeric NxM matrix of weights.
S	An integer KxJ matrix that specifying the J subsets. Each column hold K column (row) indices for the corresponding subset. The range of values is [1, M] ([1,N]).
FUN	A row-by-row (column-by-column) summary statistic function. It is applied to to each column (row) subset of X that is specified by S.
...	Additional arguments passed to specific methods.

force_block_processing

FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on \link[DelayedArray]{getAutoBlockSize}()) columns (`colFoo()`) or rows (`rowFoo()`) into memory as an ordinary `base::array`.

`na.rm` (logical) Argument passed to `FUN()` as `na.rm = na.rm`. If NA (default), then `na.rm = TRUE` is used if X or S holds missing values, otherwise `na.rm = FALSE`.

`tFUN` If TRUE, X is transposed before it is passed to `FUN`.

`rows, cols` A `vector` indicating the subset (and/or columns) to operate over. If `NULL`, no subsetting is done.

Details

The S4 methods for x of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowAvgsPerColSet` / `matrixStats::colAvgsPerRowSet`.

Value

Returns a numeric JxN (MxJ) matrix.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowAvgsPerColSet()` and `matrixStats::colAvgsPerRowSet()` which are used when the input is a `matrix` or `numeric` vector.

Examples

```
# A DelayedMatrix with a 'DataFrame' seed
dm_DF <- DelayedArray(S4Vectors::DataFrame(C1 = rep(1L, 5),
                                             C2 = as.integer((0:4) ^ 2),
                                             C3 = seq(-5L, -1L, 1L)))
colAvgsPerRowSet(dm_DF, S = matrix(1:2, ncol = 2))

rowAvgsPerColSet(dm_DF, S = matrix(1:2, ncol = 1))
```

colCollapse,DelayedMatrix-method

Extract one cell from each row (column) of a matrix-like object

Description

Extract one cell from each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colCollapse(
  x,
  idxs,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowCollapse(
  x,
  idxs,
  rows = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>idxs</code>	An index vector with the position to extract. It is recycled to match the number of rows (column)
<code>force_block_processing</code>	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If TRUE (default), names attributes of result are set. Else if FALSE , no naming support is done.
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.

Details

The S4 methods for `x` of type [matrix](#), [array](#), [table](#), or [numeric](#) call `matrixStats::rowCollapse` / `matrixStats::colCollapse`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowCollapse()` and `matrixStats::colCollapse()` which are used when the input is a matrix or numeric vector.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))
# A DelayedMatrix with a 'HDF5ArraySeed' seed
# NOTE: Requires that the HDF5Array package is installed
library(HDF5Array)
dm_HDF5 <- writeHDF5Array(matrix(c(rep(1L, 5),
                                    as.integer((0:4) ^ 2),
                                    seq(-5L, -1L, 1L)),
                                    ncol = 3))

# Extract the 4th row as a vector
# NOTE: An ordinary vector is returned regardless of the backend of
#       the DelayedMatrix object
colCollapse(dm_matrix, 4)
colCollapse(dm_HDF5, 4)

# Extract the 2nd column as a vector
# NOTE: An ordinary vector is returned regardless of the backend of
#       the DelayedMatrix object
rowCollapse(dm_matrix, 2)
rowCollapse(dm_HDF5, 2)
```

colCounts,DelayedMatrix-method

Count how often an element in a row (column) of a matrix-like object is equal to a value

Description

Count how often an element in a row (column) of a matrix-like object is equal to a value.

Usage

```
## S4 method for signature 'DelayedMatrix'
colCounts(
  x,
```

```

rows = NULL,
cols = NULL,
value = TRUE,
na.rm = FALSE,
force_block_processing = FALSE,
...,
useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowCounts(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

```

Arguments

x	A NxK DelayedMatrix .
rows, cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
value	The value to search for.
na.rm	If TRUE , missing values (NA or NaN) are omitted from the calculations.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on \link[DelayedArray]{getAutoBlockSize}()) columns (colFoo()) or rows (rowFoo()) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If TRUE (default), names attributes of result are set. Else if FALSE , no naming support is done.

Details

The S4 methods for x of type [matrix](#), [array](#), [table](#), or [numeric](#) call [matrixStats::rowCounts](#) / [matrixStats::colCounts](#).

Value

Returns a [integer vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowCounts()` and `matrixStats::colCounts()` which are used when the input is a matrix or numeric vector.
- For checks if any element is equal to a value, see `rowAny()`. To check if all elements are equal, see `rowAlls()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                    as.integer((0:4) ^ 2),
                                    seq(-5L, -1L, 1L)),
                                    ncol = 3))
# A DelayedMatrix with a 'DataFrame' seed
dm_DF <- DelayedArray(S4Vectors::DataFrame(C1 = rep(1L, 5),
                                             C2 = as.integer((0:4) ^ 2),
                                             C3 = seq(-5L, -1L, 1L)))

colCounts(dm_matrix, value = 1)
# Only count those in the first 4 rows
colCounts(dm_matrix, rows = 1:4, value = 1)

rowCounts(dm_DF, value = 5)
# Only count those in the odd-numbered rows of the 2nd column
rowCounts(dm_DF, rows = seq(1, nrow(dm_DF), 2), cols = 2, value = 5)
```

colCummaxs,DelayedMatrix-method

Calculates the cumulative maxima for each row (column) of a matrix-like object

Description

Calculates the cumulative maxima for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colCummaxs(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
```

```
useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
colCummins(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
colCumprods(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
colCumsums(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowCummaxs(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowCummins(
  x,
  rows = NULL,
  cols = NULL,
```

```

force_block_processing = FALSE,
...
useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowCumprods(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowCumsums(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...
  useNames = TRUE
)

```

Arguments

- `x` A NxK [DelayedMatrix](#).
- `rows, cols` A [vector](#) indicating the subset of rows (and/or columns) to operate over. If [NULL](#), no subsetting is done.
- `force_block_processing` `FALSE` (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to `TRUE` (typically not advised). The block-processing strategy loads one or more (depending on `\link[DelayedArray]{getAutoBlockSize}()`) columns (`colFoo()`) or rows (`rowFoo()`) into memory as an ordinary [base::array](#).
- `...` Additional arguments passed to specific methods.
- `useNames` If `TRUE` (default), names attributes of result are set. Else if `FALSE`, no naming support is done.

Details

The S4 methods for `x` of type [matrix](#), [array](#), [table](#), or [numeric](#) call `matrixStats::rowCummaxs` / `matrixStats::colCummaxs`.

Value

Returns a [numeric matrix](#)with the same dimensions as `x`.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowCummaxs()` and `matrixStats::colCummaxs()` which are used when the input is a matrix or numeric vector.
- For single maximum estimates, see `rowMaxs()`.
- `base::cummax()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                    as.integer((0:4) ^ 2),
                                    seq(-5L, -1L, 1L)),
                                    ncol = 3))

# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                           as.integer((0:4) ^ 2),
                                           seq(-5L, -1L, 1L)),
                                           ncol = 3))

colCummaxs(dm_matrix)

colCummins(dm_matrix)

colCumprods(dm_matrix)

colCumsums(dm_matrix)

# Only use rows 2-4
rowCummaxs(dm_Matrix, rows = 2:4)

# Only use rows 2-4
rowCummins(dm_Matrix, rows = 2:4)

# Only use rows 2-4
rowCumprods(dm_Matrix, rows = 2:4)

# Only use rows 2-4
rowCumsums(dm_Matrix, rows = 2:4)
```

colDiffs,DelayedMatrix-method

Calculates the difference between each element of a row (column) of a matrix-like object

Description

Calculates the difference between each element of a row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colDiffs(
  x,
  rows = NULL,
  cols = NULL,
  lag = 1L,
  differences = 1L,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowDiffs(
  x,
  rows = NULL,
  cols = NULL,
  lag = 1L,
  differences = 1L,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>lag</code>	An integer specifying the lag.
<code>differences</code>	An integer specifying the order of difference.
<code>force_block_processing</code>	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If TRUE (default), names attributes of result are set. Else if FALSE , no naming support is done.

Details

The S4 methods for x of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowDiffs` / `matrixStats::colDiffs`.

Value

Returns a `numeric matrix` with one column (row) less than x: $Nx(K - 1)$ or $(N - 1)xK$.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowDiffs()` and `matrixStats::colDiffs()` which are used when the input is a `matrix` or `numeric` vector.
- `base::diff()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                    as.integer((0:4) ^ 2),
                                    seq(-5L, -1L, 1L)),
                                    ncol = 3))
# A DelayedMatrix with a 'HDF5ArraySeed' seed
# NOTE: Requires that the HDF5Array package is installed
library(HDF5Array)
dm_HDF5 <- writeHDF5Array(matrix(c(rep(1L, 5),
                                    as.integer((0:4) ^ 2),
                                    seq(-5L, -1L, 1L)),
                                    ncol = 3))

colDiffs(dm_matrix)

rowDiffs(dm_HDF5)
# In reverse column order
rowDiffs(dm_HDF5, cols = seq(ncol(dm_HDF5), 1, -1))
```

colIQRDiffs,DelayedMatrix-method

Calculates the interquartile range of the difference between each element of a row (column) of a matrix-like object

Description

Calculates the interquartile range of the difference between each element of a row (column) of a matrix-like object.

Usage

```

## S4 method for signature 'DelayedMatrix'
colIQRDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
colMadDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
colSdDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
colVarDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,

```

```
force_block_processing = FALSE,
...,
useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowIQRDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowMadDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowSdDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowVarDiffs(
  x,
  rows = NULL,
```

```

cols = NULL,
na.rm = FALSE,
diff = 1L,
trim = 0,
force_block_processing = FALSE,
...
useNames = TRUE
)

```

Arguments

<code>x</code>	A NxK <code>DelayedMatrix</code> .
<code>rows, cols</code>	A <code>vector</code> indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>na.rm</code>	If <code>TRUE</code> , missing values (<code>NA</code> or <code>Nan</code>) are omitted from the calculations.
<code>diff</code>	An integer specifying the order of difference.
<code>trim</code>	A double in [0,1/2] specifying the fraction of observations to be trimmed from each end of (sorted) <code>x</code> before estimation.
<code>force_block_processing</code>	<code>FALSE</code> (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to <code>TRUE</code> (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>TRUE</code> (default), names attributes of result are set. Else if <code>FALSE</code> , no naming support is done.

Details

The S4 methods for `x` of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowIQRDiffs` / `matrixStats::colIQRDiffs`.

Value

Returns a `numeric vector` of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowIQRDiffs()` and `matrixStats::colIQRDiffs()` which are used when the input is a `matrix` or `numeric` vector.
- For the direct interquartile range see also `rowIQRs`.

Examples

```
# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                         as.integer((0:4) ^ 2),
                                         seq(-5L, -1L, 1L)),
                                         ncol = 3)))
# A DelayedMatrix with a 'SolidRleArraySeed' seed
dm_Rle <- RleArray(Rle(c(rep(1L, 5),
                         as.integer((0:4) ^ 2),
                         seq(-5L, -1L, 1L))),
                     dim = c(5, 3))

colIQRDiffs(dm_Matrix)

colMadDiffs(dm_Matrix)

colSdDiffs(dm_Matrix)

colVarDiffs(dm_Matrix)

# Only using rows 2-4
rowIQRDiffs(dm_Rle, rows = 2:4)

# Only using rows 2-4
rowMadDiffs(dm_Rle, rows = 2:4)

# Only using rows 2-4
rowSdDiffs(dm_Rle, rows = 2:4)

# Only using rows 2-4
rowVarDiffs(dm_Rle, rows = 2:4)
```

colIQRs,DelayedMatrix-method

Calculates the interquartile range for each row (column) of a matrix-like object

Description

Calculates the interquartile range for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colIQRs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
```

```

force_block_processing = FALSE,
...
useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowIQRs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...
  useNames = TRUE
)

```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>na.rm</code>	If <code>TRUE</code> , missing values (<code>NA</code> or <code>Nan</code>) are omitted from the calculations.
<code>force_block_processing</code>	<code>FALSE</code> (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to <code>TRUE</code> (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>TRUE</code> (default), names attributes of result are set. Else if <code>FALSE</code> , no naming support is done.

Details

The S4 methods for `x` of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowIQRs` / `matrixStats::colIQRs`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowIQRs()` and `matrixStats::colIQRs()` which are used when the input is a matrix or numeric vector.
- For a non-robust analog, see `rowSds()`. For a more robust version see `rowMads()`
- `stats::IQR()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))
# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                             as.integer((0:4) ^ 2),
                                             seq(-5L, -1L, 1L)),
                                             ncol = 3))

colIQRs(dm_matrix)

# Only using rows 2-4
rowIQRs(dm_matrix, rows = 2:4)
```

colLogSumExps,DelayedMatrix-method

Accurately calculates the logarithm of the sum of exponentials for each row (column) of a matrix-like object

Description

Accurately calculates the logarithm of the sum of exponentials for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colLogSumExps(
  lx,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

```
## S4 method for signature 'DelayedMatrix'
rowLogSumExps(
  lx,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

Arguments

<code>lx</code>	A NxK DelayedMatrix . Typically, lx are $\log(x)$ values.
<code>rows, cols</code>	A vector indicating the subset (and/or columns) to operate over. If NULL , no subsetting is done.
<code>na.rm</code>	If TRUE , missing values (NA or NaN) are omitted from the calculations.
<code>force_block_processing</code>	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If TRUE (default), names attributes of result are set. Else if FALSE , no naming support is done.

Details

The S4 methods for x of type [matrix](#), [array](#), [table](#), or [numeric](#) call `matrixStats::rowLogSumExps` / `matrixStats::colLogSumExps`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowLogSumExps()` and `matrixStats::colLogSumExps()` which are used when the input is a `matrix` or `numeric` vector.
- [rowSums2\(\)](#)

Examples

```
x <- DelayedArray(matrix(runif(10), ncol = 2))
colLogSumExps(log(x))
rowLogSumExps(log(x))
```

colMads,DelayedMatrix-method

Calculates the median absolute deviation for each row (column) of a matrix-like object

Description

Calculates the median absolute deviation for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colMads(
  x,
  rows = NULL,
  cols = NULL,
  center = NULL,
  constant = 1.4826,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
colSds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  center = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowMads(
  x,
  rows = NULL,
  cols = NULL,
  center = NULL,
```

```

constant = 1.4826,
na.rm = FALSE,
force_block_processing = FALSE,
...,
useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowSds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  center = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>center</code>	(optional) the center, defaults to the row means
<code>constant</code>	A scale factor. See <code>stats:::mad()</code> for details.
<code>na.rm</code>	If TRUE , missing values (NA or NaN) are omitted from the calculations.
<code>force_block_processing</code>	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If TRUE (default), names attributes of result are set. Else if FALSE , no naming support is done.

Details

The S4 methods for `x` of type [matrix](#), [array](#), [table](#), or [numeric](#) call `matrixStats::rowMads` / `matrixStats::colMads`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowMads()` and `matrixStats::colMads()` which are used when the input is a matrix or numeric vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- For non-robust standard deviation estimates, see `rowSds()`.

Examples

```
# A DelayedMatrix with a 'data.frame' seed
dm_df <- DelayedArray(data.frame(C1 = rep(1L, 5),
                                C2 = as.integer((0:4) ^ 2),
                                C3 = seq(-5L, -1L, 1L)))
# A DelayedMatrix with a 'DataFrame' seed
dm_DF <- DelayedArray(S4Vectors::DataFrame(C1 = rep(1L, 5),
                                              C2 = as.integer((0:4) ^ 2),
                                              C3 = seq(-5L, -1L, 1L)))

colMads(dm_df)
colSds(dm_df)
rowMads(dm_DF)
rowSds(dm_DF)
```

colMeans2,DelayedMatrix-method

Calculates the mean for each row (column) of a matrix-like object

Description

Calculates the mean for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colMeans2(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
```

```

useNames = TRUE
)

## S4 method for signature 'Matrix'
colMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = TRUE)

## S4 method for signature 'SolidRleArraySeed'
colMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = TRUE)

## S4 method for signature 'DelayedMatrix'
rowMeans2(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'Matrix'
rowMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = TRUE)

```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>na.rm</code>	If TRUE , missing values (NA or NaN) are omitted from the calculations.
<code>force_block_processing</code>	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If TRUE (default), names attributes of result are set. Else if FALSE , no naming support is done.

Details

The S4 methods for `x` of type [matrix](#), [array](#), [table](#), or [numeric](#) call `matrixStats::rowMeans2 / matrixStats::colMeans2`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowMeans2()` and `matrixStats::colMeans2()` which are used when the input is a matrix or numeric vector.
- See also `rowMeans()` for the corresponding function in base R.
- For variance estimates, see `rowVars()`.
- See also the base R version `base::rowMeans()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                    as.integer((0:4) ^ 2),
                                    seq(-5L, -1L, 1L)),
                                    ncol = 3))
# A DelayedMatrix with a 'SolidRleArraySeed' seed
dm_Rle <- RleArray(Rle(c(rep(1L, 5),
                        as.integer((0:4) ^ 2),
                        seq(-5L, -1L, 1L))),
                        dim = c(5, 3))

colMeans2(dm_matrix)

# NOTE: Temporarily use verbose output to demonstrate which method is
#       which method is being used
options(DelayedMatrixStats.verbose = TRUE)
# By default, this uses a seed-aware method for a DelayedMatrix with a
# 'SolidRleArraySeed' seed
rowMeans2(dm_Rle)
# Alternatively, can use the block-processing strategy
rowMeans2(dm_Rle, force_block_processing = TRUE)
options(DelayedMatrixStats.verbose = FALSE)
```

colMedians,DelayedMatrix-method

Calculates the median for each row (column) of a matrix-like object

Description

Calculates the median for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colMedians(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowMedians(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>na.rm</code>	If <code>TRUE</code> , missing values (<code>NA</code> or <code>Nan</code>) are omitted from the calculations.
<code>force_block_processing</code>	<code>FALSE</code> (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to <code>TRUE</code> (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>TRUE</code> (default), names attributes of result are set. Else if <code>FALSE</code> , no naming support is done.

Details

The S4 methods for `x` of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowMedians` / `matrixStats::colMedians`.

Value

Returns a `numeric vector` of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowMedians()` and `matrixStats::colMedians()` which are used when the input is a matrix or numeric vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.

Examples

```
# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                         as.integer((0:4) ^ 2),
                                         seq(-5L, -1L, 1L)),
                                         ncol = 3))

colMedians(dm_Matrix)

rowMedians(dm_Matrix)
```

colOrderStats,DelayedMatrix-method

Calculates an order statistic for each row (column) of a matrix-like object

Description

Calculates an order statistic for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colOrderStats(
  x,
  rows = NULL,
  cols = NULL,
  which,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowOrderStats(
  x,
  rows = NULL,
```

```
cols = NULL,  
which,  
force_block_processing = FALSE,  
...  
useNames = TRUE  
)
```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>which</code>	An integer index in [1,K] ([1,N]) indicating which order statistic to be returned
<code>force_block_processing</code>	<code>FALSE</code> (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to <code>TRUE</code> (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>TRUE</code> (default), names attributes of result are set. Else if <code>FALSE</code> , no naming support is done.

Details

The S4 methods for `x` of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowOrderStats` / `matrixStats::colOrderStats`.

Value

Returns a numeric vector of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowOrderStats()` and `matrixStats::colOrderStats()` which are used when the input is a matrix or numeric vector.

Examples

```
colOrderStats(dm_Matrix, cols = 2:3, which = 1)

# Different algorithms, specified by `which`, may give different results
rowOrderStats(dm_Matrix, which = 1)
rowOrderStats(dm_Matrix, which = 2)
```

colProds,DelayedMatrix-method*Calculates the product for each row (column) of a matrix-like object***Description**

Calculates the product for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colProds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  method = c("direct", "expSumLog"),
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'SolidRleArraySeed'
colProds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  method = c("direct", "expSumLog"),
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowProds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  method = c("direct", "expSumLog"),
  force_block_processing = FALSE,
```

```

  ...,
useNames = TRUE
)

```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>na.rm</code>	If <code>TRUE</code> , missing values (<code>NA</code> or <code>Nan</code>) are omitted from the calculations.
<code>method</code>	A character vector of length one that specifies the how the product is calculated. Note, that this is not a generic argument and not all implementation have to provide it.
<code>force_block_processing</code>	<code>FALSE</code> (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to <code>TRUE</code> (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>TRUE</code> (default), names attributes of result are set. Else if <code>FALSE</code> , no naming support is done.

Details

The S4 methods for `x` of type [matrix](#), [array](#), [table](#), or [numeric](#) call `matrixStats::rowProds` / `matrixStats::colProds`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowProds()` and `matrixStats::colProds()` which are used when the input is a `matrix` or `numeric` vector.
- For sums across rows (columns), see `rowSums2()` (`colSums2()`)
- `base::prod()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))
# A DelayedMatrix with a 'HDF5ArraySeed' seed
# NOTE: Requires that the HDF5Array package is installed
library(HDF5Array)
dm_HDF5 <- writeHDF5Array(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

colProds(dm_matrix)

rowProds(dm_matrix)
```

colQuantiles,DelayedMatrix-method

Calculates quantiles for each row (column) of a matrix-like object

Description

Calculates quantiles for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colQuantiles(
  x,
  rows = NULL,
  cols = NULL,
  probs = seq(from = 0, to = 1, by = 0.25),
  na.rm = FALSE,
  type = 7L,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE,
  drop = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowQuantiles(
  x,
  rows = NULL,
  cols = NULL,
  probs = seq(from = 0, to = 1, by = 0.25),
```

```

na.rm = FALSE,
type = 7L,
force_block_processing = FALSE,
...,
useNames = TRUE,
drop = TRUE
)

```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>probs</code>	A numeric vector of J probabilities in [0, 1].
<code>na.rm</code>	If <code>TRUE</code> , missing values (<code>NA</code> or <code>Nan</code>) are omitted from the calculations.
<code>type</code>	An integer specifying the type of estimator. See <code>stats::quantile()</code> . for more details.
<code>force_block_processing</code>	<code>FALSE</code> (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to <code>TRUE</code> (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>TRUE</code> (default), names attributes of result are set. Else if <code>FALSE</code> , no naming support is done.
<code>drop</code>	If <code>TRUE</code> a vector is returned if $J == 1$.

Details

The S4 methods for `x` of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowQuantiles` / `matrixStats::colQuantiles`.

Value

a `numeric` NxJ (KxJ) `matrix`, where N (K) is the number of rows (columns) for which the J values are calculated.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowQuantiles()` and `matrixStats::colQuantiles()` which are used when the input is a `matrix` or `numeric` vector.
- `stats::quantile`

Examples

```
# A DelayedMatrix with a 'data.frame' seed
dm_df <- DelayedArray(data.frame(C1 = rep(1L, 5),
                                C2 = as.integer((0:4) ^ 2),
                                C3 = seq(-5L, -1L, 1L)))

# colnames, if present, are preserved as rownames on output
colQuantiles(dm_df)

# Input has no rownames so output has no rownames
rowQuantiles(dm_df)
```

colRanks,DelayedMatrix-method

Calculates the rank of the elements for each row (column) of a matrix-like object

Description

Calculates the rank of the elements for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colRanks(
  x,
  rows = NULL,
  cols = NULL,
  ties.method = c("max", "average", "first", "last", "random", "max", "min", "dense"),
  preserveShape = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowRanks(
  x,
  rows = NULL,
  cols = NULL,
  ties.method = c("max", "average", "first", "last", "random", "max", "min", "dense"),
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>ties.method</code>	A character string specifying how ties are treated. Note that the default specifies fewer options than the original matrixStats package.
<code>preserveShape</code>	If <code>TRUE</code> the output matrix has the same shape as the input <code>x</code> . Note, that this is not a generic argument and not all implementation of this function have to provide it.
<code>force_block_processing</code>	<code>FALSE</code> (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to <code>TRUE</code> (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>TRUE</code> (default), names attributes of result are set. Else if <code>FALSE</code> , no naming support is done.

Details

The S4 methods for `x` of type [matrix](#), [array](#), [table](#), or [numeric](#) call `matrixStats::rowRanks` / `matrixStats::colRanks`.

The `matrixStats::rowRanks()` function can handle a lot of different values for the `ties.method` argument. Users of the generic function should however only rely on `max` and `average` because the other ones are not guaranteed to be implemented:

`max` for values with identical values the maximum rank is returned

`average` for values with identical values the average of the ranks they cover is returned. Note, that in this case the return value is of type [numeric](#).

Value

a matrix of type [integer](#) is returned unless `ties.method = "average"`. It has dimensions 'NxJ' ($K \times J$) [matrix](#), where N (K) is the number of rows (columns) of the input `x`.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowRanks()` and `matrixStats::colRanks()` which are used when the input is a [matrix](#) or [numeric](#) vector.
- [base::rank](#)

Examples

```
# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                         as.integer((0:4) ^ 2),
                                         seq(-5L, -1L, 1L)),
                                         ncol = 3))

colRanks(dm_Matrix)

rowRanks(dm_Matrix)
```

colSums2,DelayedMatrix-method

Calculates the sum for each row (column) of a matrix-like object

Description

Calculates the sum for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colSums2(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'Matrix'
colSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = TRUE)

## S4 method for signature 'SolidRleArraySeed'
colSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = TRUE)

## S4 method for signature 'DelayedMatrix'
rowSums2(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
```

```
)
## S4 method for signature 'Matrix'
rowSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = TRUE)
```

Arguments

<code>x</code>	A NxK DelayedMatrix .
<code>rows, cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>na.rm</code>	If <code>TRUE</code> , missing values (<code>NA</code> or <code>NaN</code>) are omitted from the calculations.
<code>force_block_processing</code>	<code>FALSE</code> (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to <code>TRUE</code> (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>TRUE</code> (default), names attributes of result are set. Else if <code>FALSE</code> , no naming support is done.

Details

The S4 methods for `x` of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowSums2 / matrixStats::colSums2`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowSums2()` and `matrixStats::colSums2()` which are used when the input is a `matrix` or `numeric` vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- `base::sum()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))
```

```

# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                         as.integer((0:4) ^ 2),
                                         seq(-5L, -1L, 1L)),
                                         ncol = 3))

colSums2(dm_Matrix)

# NOTE: Temporarily use verbose output to demonstrate which method is
#       which method is being used
options(DelayedMatrixStats.verbose = TRUE)
# By default, this uses a seed-aware method for a DelayedMatrix with a
# 'SolidRleArraySeed' seed
rowSums2(dm_Matrix)
# Alternatively, can use the block-processing strategy
rowSums2(dm_Matrix, force_block_processing = TRUE)
options(DelayedMatrixStats.verbose = FALSE)

```

colTabulates,DelayedMatrix-method*Tabulates the values in a matrix-like object by row (column)***Description**

Tabulates the values in a matrix-like object by row (column).

Usage

```

## S4 method for signature 'DelayedMatrix'
colTabulates(
  x,
  rows = NULL,
  cols = NULL,
  values = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowTabulates(
  x,
  rows = NULL,
  cols = NULL,
  values = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

```

Arguments

x	A NxK DelayedMatrix .
rows, cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
values	the values to search for.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If TRUE (default), names attributes of result are set. Else if FALSE , no naming support is done.

Details

The S4 methods for x of type [matrix](#), [array](#), [table](#), or [numeric](#) call [matrixStats::rowTabulates](#) / [matrixStats::colTabulates](#).

Value

a [numeric](#) NxJ (KxJ) [matrix](#), where N (K) is the number of rows (columns) for which the J values are calculated.

Author(s)

Peter Hickey

See Also

- [matrixStats::rowTabulates\(\)](#) and [matrixStats::colTabulates\(\)](#) which are used when the input is a [matrix](#) or [numeric](#) vector.
- [base::table\(\)](#)

Examples

```
# A DelayedMatrix with a 'DataFrame' seed
dm_DF <- DelayedArray(S4Vectors::DataFrame(C1 = rep(1L, 5),
                                             C2 = as.integer((0:4) ^ 2),
                                             C3 = seq(-5L, -1L, 1L)))

colTabulates(dm_DF)

rowTabulates(dm_DF)
```

colVars,DelayedMatrix-method

Calculates the variance for each row (column) of a matrix-like object

Description

Calculates the variance for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colVars(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  center = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowVars(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  center = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

Arguments

x	A NxK DelayedMatrix .
rows, cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , missing values (NA or Nan) are omitted from the calculations.
center	(optional) the center, defaults to the row means.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on \link[DelayedArray]{getAutoBlockSize}()) columns (colFoo()) or rows (rowFoo()) into memory as an ordinary base::array .

- ... Additional arguments passed to specific methods.
- `useNames` If `TRUE` (default), names attributes of result are set. Else if `FALSE`, no naming support is done.

Details

The S4 methods for `x` of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowVars / matrixStats::colVars`.

Value

Returns a `numeric vector` of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowVars()` and `matrixStats::colVars()` which are used when the input is a `matrix` or `numeric` vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- For standard deviation estimates, see `rowSds()`.
- `stats::var()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                    as.integer((0:4) ^ 2),
                                    seq(-5L, -1L, 1L)),
                                    ncol = 3))
# A DelayedMatrix with a 'HDF5ArraySeed' seed
# NOTE: Requires that the HDF5Array package is installed
library(HDF5Array)
dm_HDF5 <- writeHDF5Array(matrix(c(rep(1L, 5),
                                    as.integer((0:4) ^ 2),
                                    seq(-5L, -1L, 1L)),
                                    ncol = 3))

colVars(dm_matrix)

rowVars(dm_matrix)
```

colWeightedMads,DelayedMatrix-method

Calculates the weighted median absolute deviation for each row (column) of a matrix-like object

Description

Calculates the weighted median absolute deviation for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colWeightedMads(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  constant = 1.4826,
  center = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowWeightedMads(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  constant = 1.4826,
  center = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

Arguments

- x A NxK [DelayedMatrix](#).
- w A [numeric](#) vector of length K (N) that specifies by how much each element is weighted.
- rows,cols A [vector](#) indicating the subset of rows (and/or columns) to operate over. If [NULL](#), no subsetting is done.

na.rm	If TRUE , missing values (NA or Nan) are omitted from the calculations.
constant	A scale factor. See <code>stats:::mad()</code> for details.
center	(optional) the center, defaults to the row means
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
...	Additional arguments passed to specific methods.
useNames	If TRUE (default), names attributes of result are set. Else if FALSE , no naming support is done.

Details

The S4 methods for x of type `matrix`, `array`, `table`, or `numeric` call `matrixStats:::rowWeightedMads` / `matrixStats:::colWeightedMads`.

Value

Returns a `numeric vector` of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats:::rowWeightedMads()` and `matrixStats:::colWeightedMads()` which are used when the input is a `matrix` or `numeric` vector.
- See also `rowMads` for the corresponding unweighted function.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

colWeightedMads(dm_matrix, w = 1:5)

rowWeightedMads(dm_matrix, w = 3:1)
```

colWeightedMeans,DelayedMatrix-method
Calculates the weighted mean for each row (column) of a matrix-like object

Description

Calculates the weighted mean for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colWeightedMeans(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowWeightedMeans(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

Arguments

x	A NxK DelayedMatrix .
w	A numeric vector of length K (N) that specifies by how much each element is weighted.
rows, cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , missing values (NA or NaN) are omitted from the calculations.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by

	setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on \link[DelayedArray]{getAutoBlockSize}()) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
...	Additional arguments passed to specific methods.
useNames	If TRUE (default), names attributes of result are set. Else if FALSE, no naming support is done.

Details

The S4 methods for `x` of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowWeightedMeans` / `matrixStats::colWeightedMeans`.

Value

Returns a `numeric vector` of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowWeightedMeans()` and `matrixStats::colWeightedMeans()` which are used when the input is a `matrix` or `numeric vector`.
- See also `rowMeans2` for the corresponding unweighted function.

Examples

```
# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                         as.integer((0:4) ^ 2),
                                         seq(-5L, -1L, 1L)),
                                         ncol = 3))

colWeightedMeans(dm_Matrix)
# Specifying weights inversely proportional to rowwise variances
colWeightedMeans(dm_Matrix, w = 1 / rowVars(dm_Matrix))
rowWeightedMeans(dm_Matrix, w = 1:3)
```

colWeightedMedians,DelayedMatrix-method

Calculates the weighted median for each row (column) of a matrix-like object

Description

Calculates the weighted median for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colWeightedMedians(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowWeightedMedians(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

Arguments

<code>x</code>	A NxK <code>DelayedMatrix</code> .
<code>w</code>	A <code>numeric</code> vector of length K (N) that specifies by how much each element is weighted.
<code>rows, cols</code>	A <code>vector</code> indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>na.rm</code>	If <code>TRUE</code> , missing values (<code>NA</code> or <code>Nan</code>) are omitted from the calculations.
<code>force_block_processing</code>	<code>FALSE</code> (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to <code>TRUE</code> (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
<code>...</code>	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>TRUE</code> (default), names attributes of result are set. Else if <code>FALSE</code> , no naming support is done.

Details

The S4 methods for `x` of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowWeightedMedians` / `matrixStats::colWeightedMedians`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- [matrixStats::rowWeightedMedians\(\)](#) and [matrixStats::colWeightedMedians\(\)](#) which are used when the input is a [matrix](#) or [numeric vector](#).
- See also [rowMedians](#) for the corresponding unweighted function.

Examples

```
# A DelayedMatrix with a 'SolidRleArraySeed' seed
dm_Rle <- RleArray(Rle(c(rep(1L, 5),
                        as.integer((0:4) ^ 2),
                        seq(-5L, -1L, 1L))),
                     dim = c(5, 3))

# Specifying weights inversely proportional to rowwise MADs
colWeightedMedians(dm_Rle, w = 1 / rowMads(dm_Rle))
```

colWeightedSds,DelayedMatrix-method

Calculates the weighted standard deviation for each row (column) of a matrix-like object

Description

Calculates the weighted standard deviation for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colWeightedSds(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)
```

```

## S4 method for signature 'DelayedMatrix'
colWeightedVars(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowWeightedSds(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

## S4 method for signature 'DelayedMatrix'
rowWeightedVars(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = TRUE
)

```

Arguments

x	A NxK DelayedMatrix .
w	A numeric vector of length K (N) that specifies by how much each element is weighted.
rows, cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , missing values (NA or NaN) are omitted from the calculations.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads

	one or more (depending on \link[DelayedArray]{getAutoBlockSize}()) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
...	Additional arguments passed to specific methods.
<code>useNames</code>	If <code>TRUE</code> (default), names attributes of result are set. Else if <code>FALSE</code> , no naming support is done.

Details

The S4 methods for `x` of type `matrix`, `array`, `table`, or `numeric` call `matrixStats::rowWeightedSds` / `matrixStats::colWeightedSds`.

Value

Returns a `numeric vector` of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowWeightedSds()` and `matrixStats::colWeightedSds()` which are used when the input is a `matrix` or `numeric` vector.
- See also `rowSds` for the corresponding unweighted function.

Examples

```
# A DelayedMatrix with a 'SolidRleArraySeed' seed
dm_Rle <- RleArray(Rle(c(rep(1L, 5),
                        as.integer((0:4) ^ 2),
                        seq(-5L, -1L, 1L))),
                     dim = c(5, 3))

colWeightedSds(dm_Rle, w = 1 / rowMeans2(dm_Rle))

# Specifying weights inversely proportional to rowwise means
colWeightedVars(dm_Rle, w = 1 / rowMeans2(dm_Rle))

# Specifying weights inversely proportional to columnwise means
rowWeightedSds(dm_Rle, w = 1 / colMeans2(dm_Rle))

# Specifying weights inversely proportional to columnwise means
rowWeightedVars(dm_Rle, w = 1 / colMeans2(dm_Rle))
```

DelayedMatrixStats	<i>DelayedMatrixStats: Functions that apply to rows and columns of DelayedMatrix objects.</i>
--------------------	---

Description

DelayedMatrixStats is a port of the **matrixStats** API to work with *DelayedMatrix* objects from the **DelayedArray** package. High-performing functions operating on rows and columns of *DelayedMatrix* objects, e.g. `colMedians()` / `rowMedians()`, `colRanks()` / `rowRanks()`, and `colSds()` / `rowSds()`. Functions optimized per data type and for subsetted calculations such that both memory usage and processing time is minimized.

Author(s)

Maintainer: Peter Hickey <peter.hickey@gmail.com> ([ORCID](#))

Other contributors:

- Hervé Pagès <hpages.on.github@gmail.com> [contributor]
- Aaron Lun <infinite.monkeys.with.keyboards@gmail.com> [contributor]

See Also

Useful links:

- <https://github.com/PeteHaitch/DelayedMatrixStats>
- Report bugs at <https://github.com/PeteHaitch/DelayedMatrixStats/issues>

<code>from_DelayedArray_to_simple_seed_class</code>	<i>Coerce DelayedArray to its 'simple seed' form</i>
---	--

Description

Coerce DelayedArray to its 'simple seed' form

Usage

```
from_DelayedArray_to_simple_seed_class(x, drop = FALSE, do_transpose = TRUE)
```

Arguments

<code>x</code>	A DelayedArray
<code>drop</code>	If TRUE the result is coerced to the lowest possible dimension
<code>do_transpose</code>	Should transposed input be physically transposed?

Details

Like `DelayedArray:::from_DelayedArray_to_array` but returning an object of the same class as `seedClass(x)` instead of an *array*. In doing so, all delayed operations are realised (including subsetting).

Value

An object of the same class as `seedClass(x)`.

Note

Can be more efficient to leave the transpose implicit (`do_transpose = FALSE`) and switch from a `row*()` method to a `col*()` method (or vice versa).

Only works on [DelayedArray](#) objects with 'simple seeds'

reexports

Objects exported from other packages

Description

These objects are imported from other packages. Follow the links below to see their documentation.

[DelayedArray](#) [colMaxs](#), [colMins](#), [colRanges](#), [rowMaxs](#), [rowMins](#), [rowRanges](#)

`subset_by_Nindex`

`subset_by_Nindex`

Description

`subset_by_Nindex()` is an internal generic function not aimed to be used directly by the user. It is basically an S4 generic for `DelayedArray:::subset_by_Nindex`.

Usage

```
subset_by_Nindex(x, Nindex)
```

Arguments

<code>x</code>	An array-like object.
<code>Nindex</code>	An unnamed list of subscripts as positive integer vectors, one vector per dimension in <code>x</code> . Empty and missing subscripts (represented by <code>integer(0)</code> and <code>NULL</code> list elements, respectively) are allowed. The subscripts can contain duplicated indices. They cannot contain NAs or non-positive values.

Details

`subset_by_Nindex(x, Nindex)` conceptually performs the operation `x[Nindex[1], ..., Nindex[length(Nindex)]]`. `subset_by_Nindex()` methods need to support empty and missing subscripts, e.g., `subset_by_Nindex(x, list(NULL, integer(0)))` must return an $M \times 0$ object of class `class(x)` and `subset_by_Nindex(x, list(integer(0), integer(0)))` a 0×0 object of class `class(x)`.

Also, subscripts are allowed to contain duplicate indices so things like `subset_by_Nindex(x, list(c(1:3, 3:1), 2L))` need to be supported.

Value

A object of class `class(x)` of the appropriate type (e.g., `integer`, `double`, etc.). For example, if `x` is a `data.frame` representing an $M \times N$ matrix of integers, `subset_by_Nindex(x, list(NULL, 2L))` must return its 2nd column as a `data.frame` with M rows and 1 column of type `integer`.

Index

* **internal**

- DelayedMatrixStats, 53
- from_DelayedArray_to_simple_seed_class, 53
- reexports, 54

- all, 4
- any, 6
- array, 4, 6, 8, 9, 11, 14, 17, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 49, 52
- base::array, 4, 6, 8, 9, 11, 14, 16, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 43, 46, 48, 49, 52
- base::rank, 38

- colAlls, 4
- colAlls, DelayedMatrix-method, 2
- colAnyNAs, 6
- colAnyNAs, DelayedMatrix-method, 5
- colAnys, DelayedMatrix-method
 - (colAlls, DelayedMatrix-method), 2
- colAvegsPerRowSet, 8
- colAvegsPerRowSet, DelayedMatrix-method, 7
- colCollapse, 9, 10
- colCollapse, DelayedMatrix-method, 8
- colCounts, 11, 12
- colCounts, DelayedMatrix-method, 10
- colCummaxs, 14, 15
- colCummaxs, DelayedMatrix-method, 12
- colCummins, DelayedMatrix-method
 - (colCummaxs, DelayedMatrix-method), 12
- colCumprods, DelayedMatrix-method
 - (colCummaxs, DelayedMatrix-method), 12

- colCumsums, DelayedMatrix-method
 - (colCummaxs, DelayedMatrix-method), 12
- colDiffs, 17
- colDiffs, DelayedMatrix-method, 15
- colIQRDiffs, 20
- colIQRDiffs, DelayedMatrix-method, 17
- colIQRs, 22, 23
- colIQRs, DelayedMatrix-method, 21
- colLogSumExps, 24
- colLogSumExps, DelayedMatrix-method, 23
- colMadDiffs, DelayedMatrix-method
 - (colIQRDiffs, DelayedMatrix-method), 17
- colMads, 26, 27
- colMads, DelayedMatrix-method, 25
- colMaxs, 54
- colMaxs (reexports), 54
- colMeans2, 28, 29
- colMeans2, DelayedMatrix-method, 27
- colMeans2, Matrix-method
 - (colMeans2, DelayedMatrix-method), 27
- colMeans2, SolidRleArraySeed-method
 - (colMeans2, DelayedMatrix-method), 27
- colMedians, 30, 31
- colMedians, DelayedMatrix-method, 29
- colMins, 54
- colMins (reexports), 54
- colOrderStats, 32
- colOrderStats, DelayedMatrix-method, 31
- colProds, 34
- colProds, DelayedMatrix-method, 33
- colProds, SolidRleArraySeed-method
 - (colProds, DelayedMatrix-method), 33
- colQuantiles, 36
- colQuantiles, DelayedMatrix-method, 35

colRanges, 54
 colRanges (reexports), 54
 colRanks, 38
 colRanks,DelayedMatrix-method, 37
 colSdDiffs,DelayedMatrix-method
 (colIQRDiffs,DelayedMatrix-method),
 17
 colSds,DelayedMatrix-method
 (colMads,DelayedMatrix-method),
 25
 colSums2, 40
 colSums2(), 34
 colSums2,DelayedMatrix-method, 39
 colSums2,Matrix-method
 (colSums2,DelayedMatrix-method),
 39
 colSums2,SolidRleArraySeed-method
 (colSums2,DelayedMatrix-method),
 39
 colTabulates, 42
 colTabulates,DelayedMatrix-method, 41
 colVarDiffs,DelayedMatrix-method
 (colIQRDiffs,DelayedMatrix-method),
 17
 colVars, 44
 colVars,DelayedMatrix-method, 43
 colWeightedMads, 46
 colWeightedMads,DelayedMatrix-method,
 45
 colWeightedMeans, 48
 colWeightedMeans,DelayedMatrix-method,
 47
 colWeightedMedians, 49, 50
 colWeightedMedians,DelayedMatrix-method,
 48
 colWeightedSds, 52
 colWeightedSds,DelayedMatrix-method,
 50
 colWeightedVars,DelayedMatrix-method
 (colWeightedSds,DelayedMatrix-method),
 50
 cummax, 15

 data.frame, 55
 DelayedArray, 53, 54
 DelayedMatrix, 4, 5, 7, 9, 11, 14, 16, 20, 22,
 24, 26, 28, 30, 32, 34, 36, 38, 40, 42,
 43, 45, 47, 49, 51
 DelayedMatrixStats, 53

 DelayedMatrixStats-package
 (DelayedMatrixStats), 53
 diff, 17

 FALSE, 4, 6, 9, 11, 14, 16, 20, 22, 24, 26, 28,
 30, 32, 34, 36, 38, 40, 42, 44, 46, 48,
 49, 52
 from_DelayedArray_to_simple_seed_class,
 53

 integer, 7, 11, 38
 IQR, 23
 is.na, 6

 logical, 4, 6

 mad, 26, 46
 matrix, 4, 6, 8, 9, 11, 14, 17, 20, 22, 24, 26,
 28, 30, 32, 34, 36, 38, 40, 42, 44, 46,
 48, 49, 52

 NA, 4, 11, 20, 22, 24, 26, 28, 30, 34, 36, 40, 43,
 46, 47, 49, 51
 NaN, 4, 11, 20, 22, 24, 26, 28, 30, 34, 36, 40,
 43, 46, 47, 49, 51
 NULL, 4, 5, 8, 9, 11, 14, 16, 20, 22, 24, 26, 28,
 30, 32, 34, 36, 38, 40, 42, 43, 45, 47,
 49, 51
 numeric, 4, 6, 8, 9, 11, 14, 17, 20, 22, 24, 26,
 28, 30, 32, 34, 36, 38, 40, 42, 44–52

 prod, 34

 quantile, 36

 reexports, 54
 rowAlls, 4, 12
 rowAlls,DelayedMatrix-method
 (colAlls,DelayedMatrix-method),
 2
 rowAnyNAs, 6
 rowAnyNAs,DelayedMatrix-method
 (colAnyNAs,DelayedMatrix-method),
 5
 rowAnys, 4, 6, 12
 rowAnys,DelayedMatrix-method
 (colAlls,DelayedMatrix-method),
 2
 rowAvgsPerColSet, 8

rowAvgsPerColSet,DelayedMatrix-method
 (colAvgsPerRowSet,DelayedMatrix-method),
 7
 rowCollapse, 9, 10
 rowCollapse,DelayedMatrix-method
 (colCollapse,DelayedMatrix-method),
 8
 rowCounts, 11, 12
 rowCounts,DelayedMatrix-method
 (colCounts,DelayedMatrix-method),
 10
 rowCummaxs, 14, 15
 rowCummaxs,DelayedMatrix-method
 (colCummaxs,DelayedMatrix-method),
 12
 rowCummins,DelayedMatrix-method
 (colCummins,DelayedMatrix-method),
 12
 rowCumprods,DelayedMatrix-method
 (colCummaxs,DelayedMatrix-method),
 12
 rowCumsums,DelayedMatrix-method
 (colCummaxs,DelayedMatrix-method),
 12
 rowDiffs, 17
 rowDiffs,DelayedMatrix-method
 (colDiffs,DelayedMatrix-method),
 15
 rowIQRDiffs, 20
 rowIQRDiffs,DelayedMatrix-method
 (colIQRDiffs,DelayedMatrix-method),
 17
 rowIQRs, 20, 22, 23
 rowIQRs,DelayedMatrix-method
 (colIQRs,DelayedMatrix-method),
 21
 rowLogSumExps, 24
 rowLogSumExps,DelayedMatrix-method
 (colLogSumExps,DelayedMatrix-method),
 23
 rowMadDiffs,DelayedMatrix-method
 (colIQRDiffs,DelayedMatrix-method),
 17
 rowMads, 26, 27, 46
 rowMads(), 23
 rowMads,DelayedMatrix-method
 (colMads,DelayedMatrix-method),
 25
 rowMaxs, 15, 54
 rowMaxs (reexports), 54
 rowMeans, 27, 29, 31, 40, 44
 rowMeans2, 27–29, 31, 40, 44, 48
 rowMeans2,DelayedMatrix-method
 (colMeans2,DelayedMatrix-method),
 27
 rowMeans2,Matrix-method
 (colMeans2,DelayedMatrix-method),
 27
 rowMedians, 30, 31, 50
 rowMedians,DelayedMatrix-method
 (colMedians,DelayedMatrix-method),
 29
 rowMins, 54
 rowMins (reexports), 54
 rowOrderStats, 32
 rowOrderStats,DelayedMatrix-method
 (colOrderStats,DelayedMatrix-method),
 31
 rowProds, 34
 rowProds,DelayedMatrix-method
 (colProds,DelayedMatrix-method),
 33
 rowQuantiles, 36
 rowQuantiles,DelayedMatrix-method
 (colQuantiles,DelayedMatrix-method),
 35
 rowRanges, 54
 rowRanges (reexports), 54
 rowRanks, 38
 rowRanks,DelayedMatrix-method
 (colRanks,DelayedMatrix-method),
 37
 rowSdDiffs,DelayedMatrix-method
 (colIQRDiffs,DelayedMatrix-method),
 17
 rowSds, 23, 27, 44, 52
 rowSds,DelayedMatrix-method
 (colMads,DelayedMatrix-method),
 25
 rowSums2, 34, 40
 rowSums2(), 24
 rowSums2,DelayedMatrix-method
 (colSums2,DelayedMatrix-method),
 39
 rowSums2,Matrix-method
 (colSums2,DelayedMatrix-method),

39
rowTabulates, 42
rowTabulates, DelayedMatrix-method
 (colTabulates, DelayedMatrix-method),
 41
rowVarDiffs, DelayedMatrix-method
 (colIQRDiffs, DelayedMatrix-method),
 17
rowVars, 29, 44
rowVars, DelayedMatrix-method
 (colVars, DelayedMatrix-method),
 43
rowWeightedMads, 46
rowWeightedMads, DelayedMatrix-method
 (colWeightedMads, DelayedMatrix-method),
 45
rowWeightedMeans, 48
rowWeightedMeans, DelayedMatrix-method
 (colWeightedMeans, DelayedMatrix-method),
 47
rowWeightedMedians, 49, 50
rowWeightedMedians, DelayedMatrix-method
 (colWeightedMedians, DelayedMatrix-method),
 48
rowWeightedSds, 52
rowWeightedSds, DelayedMatrix-method
 (colWeightedSds, DelayedMatrix-method),
 50
rowWeightedVars, DelayedMatrix-method
 (colWeightedSds, DelayedMatrix-method),
 50

stats::quantile, 36
subset_by_Nindex, 54
sum, 40

table, 4, 6, 8, 9, 11, 14, 17, 20, 22, 24, 26, 28,
 30, 32, 34, 36, 38, 40, 42, 44, 46, 48,
 49, 52
TRUE, 4, 6, 9, 11, 14, 16, 20, 22, 24, 26, 28, 30,
 32, 34, 36, 38, 40, 42–44, 46–49, 51,
 52

var, 44
vector, 4–6, 8, 9, 11, 14, 16, 20, 22, 24, 26,
 28, 30, 32, 34, 36, 38, 40, 42–52