

Package ‘GOSemSim’

October 9, 2013

Type Package

Title GO-terms Semantic Similarity Measures

Version 1.18.0

Author Guangchuang Yu

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Description Implemented five methods proposed by Resnik, Schlicker, Jiang, Lin and Wang respectively for estimating GO semantic similarities. Support many species, including Anopheles, Arabidopsis, Bovine, Canine, Chicken, Chimp, Coelocolor, E coli strain K12 and Sakai, Fly, Human, Malaria, Mouse, Pig, Rhesus, Rat, Worm, Xenopus, Yeast, and Zebrafish.

Depends R (>= 2.10), Rcpp

LinkingTo Rcpp

Imports methods, AnnotationDbi, GO.db, org.Hs.eg.db

Suggests DOSE, clusterProfiler, BiocInstaller

biocViews GO, Clustering, Pathways, NetworkAnalysis

Collate

'clusterSim.R' 'combineMethods.R' 'computeIC.R' 'ICMethods.R' 'gene2GO.R' 'geneSim.R' 'goSim.R' 'termSim.R' 'Wpackage.R' 'mgeneSim.R' 'mgoSim.R' 'mclusterSim.R'

License GPL-2

URL <http://bioinformatics.oxfordjournals.org/content/26/7/976.full>

R topics documented:

GOSemSim-package	2
clusterSim	3
combineScores	4
geneSim	5
goSim	6
IC	7
infoContentMethod	7
loadICdata	8
mclusterSim	8
mgeneSim	9
mgoSim	10
termSim	11
wangMethod	12

Index	13
--------------	-----------

GOSemSim-package	<i>Gene Ontology-based Semantic Similarity Measures</i>
------------------	---

Description

Implementation of semantic similarity measures to estimate the functional similarities among Gene Ontology terms and gene products

Details

Quantitative measure of functional similarities among gene products is important for post-genomics study. and widely used in gene function prediction, cluster analysis and pathway modeling. This package is designed to estimate the GO terms' and genes' semantic similarities. Implemented five methods proposed by Resnik, Schlicker, Jiang, Lin and Wang respectively. Support many species, including Anopheles, Arabidopsis, Bovine, Canine, Chicken, Chimp, E coli strain K12 and strain Sakai, Fly, Human, Malaria, Mouse, Pig, Rhesus, Rat, Worm, Xenopus, Yeast, Zebrafish.

Package: GOSemSim
 Type: Package
 Version: 1.6.0
 Date: 09-11-2012
 biocViews: GO, Clustering, Pathways, Anopheles_gambiae, Arabidopsis_thaliana, Bos_taurus, Caenorhabditis_elegans, Canis_familiaris, Chimp, Chicken, E_coli, E_coli_strain_K12, E_coli_strain_Sakai, Fly, Human, Malaria, Mouse, Pig, Rhesus, Rat, Worm, Xenopus, Yeast, Zebrafish
 Depends:
 Imports: methods, AnnotationDbi, GO.db, org.Hs.eg.db, org.Ag.eg.db, org.At.tair.db, org.Bt.eg.db, org.Ce.eg.db, org.Cf.eg.db
 Suggests: clusterProfiler
 License: GPL Version 2

Author(s)

Guangchuang Yu

Maintainer: Guangchuang Yu <guangchuangyu@gmail.com>

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[goSim](#) [mgoSim](#) [geneSim](#) [mgeneSim](#) [clusterSim](#) [mclusterSim](#)

 clusterSim

Semantic Similarity Between Two Gene Clusters

Description

Given two gene clusters, this function calculates semantic similarity between them.

Usage

```
clusterSim(cluster1, cluster2, ont = "MF",
           organism = "human", measure = "Wang", drop = "IEA",
           combine = "BMA")
```

Arguments

cluster1	A set of gene IDs.
cluster2	Another set of gene IDs.
ont	One of "MF", "BP", and "CC" subontologies.
measure	One of "Resnik", "Lin", "Rel", "Jiang" and "Wang" methods.
organism	One of "anopheles", "arabidopsis", "bovine", "canine", "chicken", "chimp", "coelicolor", "ecolik12", "ecsakai", "fly", "human", "malaria", "mouse", "pig", "rat", "rhesus", "worm", "xenopus", "yeast" and "zebrafish".
drop	A set of evidence codes based on which certain annotations are dropped. Use NULL to keep all GO annotations.
combine	One of "max", "average", "rcmax", "BMA" methods, for combining semantic similarity scores of multiple GO terms associated with protein or multiple proteins associated with protein cluster.

Value

similarity

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[goSim](#) [mgoSim](#) [geneSim](#) [mgeneSim](#) [mclusterSim](#)

Examples

```
## cluster1 <- c("835", "5261", "241", "994")
## cluster2 <- c("307", "308", "317", "321", "506", "540", "378", "388", "396")
## clusterSim(cluster1, cluster2, ont="MF", organism="human", measure="Wang")
```

combineScores

combining similarity matrix to similarity score

Description

Functions for combining similarity matrix to similarity score

Usage

```
combineScores(SimScores, combine)
```

Arguments

SimScores	similarity matrix
combine	combine method

Value

similarity value

Author(s)

Guangchuang Yu <http://ygc.name>

geneSim *Semantic Similarity Between two Genes*

Description

Given two genes, this function will calculate the semantic similarity between them, and return their semantic similarity and the corresponding GO terms

Usage

```
geneSim(gene1, gene2, ont = "MF", organism = "human",
        measure = "Wang", drop = "IEA", combine = "BMA")
```

Arguments

gene1	Entrez gene id.
gene2	Another entrez gene id.
ont	One of "MF", "BP", and "CC" subontologies.
organism	One of "anopheles", "arabidopsis", "bovine", "canine", "chicken", "chimp", "coelicolor", "ecolik12", "ecsakai", "fly", "human", "malaria", "mouse", "pig", "rat", "rhesus", "worm", "xenopus", "yeast" and "zebrafish".
measure	One of "Resnik", "Lin", "Rel", "Jiang" and "Wang" methods.
drop	A set of evidence codes based on which certain annotations are dropped. Use NULL to keep all GO annotations.
combine	One of "max", "average", "rmax", "BMA" methods, for combining semantic similarity scores of multiple GO terms associated with protein or multiple proteins associated with protein cluster.

Value

list of similarity value and corresponding GO.

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[goSim](#) [mgoSim](#) [mgeneSim](#) [clusterSim](#) [mclusterSim](#)

Examples

```
geneSim("241", "251", ont="MF", organism="human", measure="Wang")
```

`goSim`*Semantic Similarity Between Two GO Terms*

Description

Given two GO IDs, this function calculates their semantic similarity.

Usage

```
goSim(GO1, GO2, ont = "MF", organism = "human",  
      measure = "Wang")
```

Arguments

GO1	GO ID 1.
GO2	GO ID 2.
ont	One of "MF", "BP", and "CC" subontologies.
organism	One of "anopheles", "arabidopsis", "bovine", "canine", "chicken", "chimp", "coelicolor", "ecoli12", "ecsakai", "fly", "human", "malaria", "mouse", "pig", "rat", "rhesus", "worm", "xenopus", "yeast" and "zebrafish".
measure	One of "Resnik", "Lin", "Rel", "Jiang" and "Wang" methods.

Value

similarity

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[mgoSim](#) [geneSim](#) [mgeneSim](#) [clusterSim](#) [mclusterSim](#)

Examples

```
goSim("GO:0004022", "GO:0005515", ont="MF", measure="Wang")
```

 IC *Information content of GO terms*

Description

These datasets are the information contents of GOterms.

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

 infoContentMethod *information content based methods*

Description

Information Content Based Methods for semantic similarity measuring

Usage

```
infoContentMethod(ID1, ID2, ont = "DO", method,
  organism = "human")
```

Arguments

ID1	Ontology Term
ID2	Ontology Term
ont	Ontology
method	one of "Resnik", "Jiang", "Lin" and "Rel".
organism	one of supported species

Details

implemented for methods proposed by Resnik, Jiang, Lin and Schlicker.

Value

semantic similarity score

Author(s)

Guangchuang Yu <http://ygc.name>

loadICdata	<i>Load IC data</i>
------------	---------------------

Description

Load Information Content data to DOSEnv environment

Usage

```
loadICdata(organism, ont)
```

Arguments

organism	"human"
ont	"DO"

Value

NULL

Author(s)

Guangchuang Yu <http://ygc.name>

mclusterSim	<i>Pairwise Semantic Similarities for a List of Gene Clusters</i>
-------------	---

Description

Given a list of gene clusters, this function calculates pairwise semantic similarities.

Usage

```
mclusterSim(clusters, ont = "MF", organism = "human",
  measure = "Wang", drop = "IEA", combine = "BMA")
```

Arguments

clusters	A list of gene clusters.
ont	One of "MF", "BP", and "CC" subontologies.
measure	One of "Resnik", "Lin", "Rel", "Jiang" and "Wang" methods.
organism	One of "anopheles", "arabidopsis", "bovine", "canine", "chicken", "chimp", "coelicolor", "ecolik12", "ecsakai", "fly", "human", "malaria", "mouse", "pig", "rat", "rhesus", "worm", "xenopus", "yeast" and "zebrafish".

drop	A set of evidence codes based on which certain annotations are dropped. Use NULL to keep all GO annotations.
combine	One of "max", "average", "rmax", "BMA" methods, for combining semantic similarity scores of multiple GO terms associated with protein or multiple proteins associated with protein cluster.

Value

similarity matrix

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[goSim](#) [mgoSim](#) [geneSim](#) [mgeneSim](#) [clusterSim](#)

Examples

```
## cluster1 <- c("835", "5261", "241")
## cluster2 <- c("578", "582")
## cluster3 <- c("307", "308", "317")
## clusters <- list(a=cluster1, b=cluster2, c=cluster3)
## mclusterSim(clusters, ont="MF", organism="human", measure="Wang")
```

mgeneSim

Pairwise Semantic Similarity for a List of Genes

Description

Given a list of genes, this function calculates pairwise semantic similarities.

Usage

```
mgeneSim(genes, ont = "MF", organism = "human",
         measure = "Wang", drop = "IEA", combine = "BMA",
         verbose = TRUE)
```

Arguments

genes	A list of entrez gene IDs.
ont	One of "MF", "BP", and "CC" subontologies.
measure	One of "Resnik", "Lin", "Rel", "Jiang" and "Wang" methods.

organism	One of "anopheles", "arabidopsis", "bovine", "canine", "chicken", "chimp", "coelicolor", "ecolik12", "ecsakai", "fly", "human", "malaria", "mouse", "pig", "rat", "rhesus", "worm", "xenopus", "yeast" and "zebrafish".
drop	A set of evidence codes based on which certain annotations are dropped. Use NULL to keep all GO annotations.
combine	One of "max", "average", "rcmax", "BMA" methods, for combining semantic similarity scores of multiple GO terms associated with protein or multiple proteins associated with protein cluster.
verbose	show progress bar or not.

Value

similarity matrix

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[goSim](#) [mgoSim](#) [geneSim](#) [clusterSim](#) [mclusterSim](#)

Examples

```
mgeneSim(c("835", "5261", "241"), ont="MF", organism="human", measure="Wang")
```

mgoSim

Semantic Similarity Between two GO terms lists

Description

Given two GO term sets, this function will calculate the semantic similarity between them, and return their semantic similarity

Usage

```
mgoSim(GO1, GO2, ont = "MF", organism = "human",
        measure = "Wang", combine = "BMA")
```

Arguments

GO1	A set of go terms.
GO2	Another set of go terms.
ont	One of "MF", "BP", and "CC" subontologies.
organism	One of "anopheles", "arabidopsis", "bovine", "canine", "chicken", "chimp", "coelicolor", "ecolik12", "ecsakai", "fly", "human", "malaria", "mouse", "pig", "rat", "rhesus", "worm", "xenopus", "yeast" and "zebrafish".
measure	One of "Resnik", "Lin", "Rel", "Jiang" and "Wang" methods.
combine	One of "max", "average", "rcmax", "BMA" methods, for combining semantic similarity scores of multiple GO terms associated with protein or multiple proteins associated with protein cluster.

Value

similarity

References

Yu et al. (2010) GOSemSim: an R package for measuring semantic similarity among GO terms and gene products *Bioinformatics* (Oxford, England), 26:7 976–978, April 2010. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/cgi/content/abstract/26/7/976> PMID: 20179076

See Also

[goSim](#) [geneSim](#) [mgeneSim](#) [clusterSim](#) [mclusterSim](#)

Examples

```
go1 <- c("GO:0004022", "GO:0004024", "GO:0004023")
go2 <- c("GO:0009055", "GO:0020037")
mgoSim("GO:0003824", go2, measure="Wang")
mgoSim(go1, go2, ont="MF", organism="human", measure="Wang")
```

termSim

termSim

Description

measuring similarities between two term vectors.

Usage

```
termSim(t1, t2, method = "Wang", organism = "human", ont)
```

Arguments

t1	term vector
t2	term vector
method	one of "Wang", "Resnik", "Rel", "Jiang", and "Lin".
organism	only "human" supported
ont	ontology

Details

provide two term vectors, this function will calculate their similarities.

Value

score matrix

Author(s)

Guangchuang Yu <http://ygc.name>

wangMethod

wangMethod

Description

Method Wang for semantic similarity measuring

Usage

```
wangMethod(ID1, ID2, ont)
```

Arguments

ID1	Ontology Term
ID2	Ontology Term
ont	Ontology

Value

semantic similarity score

Author(s)

Guangchuang Yu <http://ygc.name>

Index

*Topic **datasets**

IC, [7](#)

*Topic **manip**

clusterSim, [3](#)

geneSim, [5](#)

goSim, [6](#)

mclusterSim, [8](#)

mgeneSim, [9](#)

mgoSim, [10](#)

*Topic **package**

GOSemSim-package, [2](#)

clusterSim, [3](#), [3](#), [5](#), [6](#), [9–11](#)

combineScores, [4](#)

geneSim, [3](#), [4](#), [5](#), [6](#), [9–11](#)

GOSemSim (GOSemSim-package), [2](#)

GOSemSim-package, [2](#)

goSim, [3–5](#), [6](#), [9–11](#)

IC, [7](#)

Info_Contents_anopheles_BP (IC), [7](#)

Info_Contents_anopheles_CC (IC), [7](#)

Info_Contents_anopheles_MF (IC), [7](#)

Info_Contents_arabidopsis_BP (IC), [7](#)

Info_Contents_arabidopsis_CC (IC), [7](#)

Info_Contents_arabidopsis_MF (IC), [7](#)

Info_Contents_bovine_BP (IC), [7](#)

Info_Contents_bovine_CC (IC), [7](#)

Info_Contents_bovine_MF (IC), [7](#)

Info_Contents_canine_BP (IC), [7](#)

Info_Contents_canine_CC (IC), [7](#)

Info_Contents_canine_MF (IC), [7](#)

Info_Contents_chicken_BP (IC), [7](#)

Info_Contents_chicken_CC (IC), [7](#)

Info_Contents_chicken_MF (IC), [7](#)

Info_Contents_chimp_BP (IC), [7](#)

Info_Contents_chimp_CC (IC), [7](#)

Info_Contents_chimp_MF (IC), [7](#)

Info_Contents_coelicolor_BP (IC), [7](#)

Info_Contents_coelicolor_CC (IC), [7](#)

Info_Contents_coelicolor_MF (IC), [7](#)

Info_Contents_ecolik12_BP (IC), [7](#)

Info_Contents_ecolik12_CC (IC), [7](#)

Info_Contents_ecolik12_MF (IC), [7](#)

Info_Contents_ecsakai_BP (IC), [7](#)

Info_Contents_ecsakai_CC (IC), [7](#)

Info_Contents_ecsakai_MF (IC), [7](#)

Info_Contents_fly_BP (IC), [7](#)

Info_Contents_fly_CC (IC), [7](#)

Info_Contents_fly_MF (IC), [7](#)

Info_Contents_human_BP (IC), [7](#)

Info_Contents_human_CC (IC), [7](#)

Info_Contents_human_MF (IC), [7](#)

Info_Contents_malaria_BP (IC), [7](#)

Info_Contents_malaria_CC (IC), [7](#)

Info_Contents_malaria_MF (IC), [7](#)

Info_Contents_mouse_BP (IC), [7](#)

Info_Contents_mouse_CC (IC), [7](#)

Info_Contents_mouse_MF (IC), [7](#)

Info_Contents_pig_BP (IC), [7](#)

Info_Contents_pig_CC (IC), [7](#)

Info_Contents_pig_MF (IC), [7](#)

Info_Contents_rat_BP (IC), [7](#)

Info_Contents_rat_CC (IC), [7](#)

Info_Contents_rat_MF (IC), [7](#)

Info_Contents_rhesus_BP (IC), [7](#)

Info_Contents_rhesus_CC (IC), [7](#)

Info_Contents_rhesus_MF (IC), [7](#)

Info_Contents_worm_BP (IC), [7](#)

Info_Contents_worm_CC (IC), [7](#)

Info_Contents_worm_MF (IC), [7](#)

Info_Contents_xenopus_BP (IC), [7](#)

Info_Contents_xenopus_CC (IC), [7](#)

Info_Contents_xenopus_MF (IC), [7](#)

Info_Contents_yeast_BP (IC), [7](#)

Info_Contents_yeast_CC (IC), [7](#)

Info_Contents_yeast_MF (IC), [7](#)

Info_Contents_zebrafish_BP (IC), [7](#)

Info_Contents_zebrafish_CC (IC), [7](#)
Info_Contents_zebrafish_MF (IC), [7](#)
infoContentMethod, [7](#)

loadICdata, [8](#)

mclusterSim, [3-6](#), [8](#), [10](#), [11](#)
mgeneSim, [3-6](#), [9](#), [9](#), [11](#)
mgoSim, [3-6](#), [9](#), [10](#), [10](#)

termSim, [11](#)

wangMethod, [12](#)