

# BSgenome.Hsapiens.UCSC.hg19

April 4, 2014

---

BSgenome.Hsapiens.UCSC.hg19

*Homo sapiens (Human) full genome (UCSC version hg19)*

---

## Description

Homo sapiens (Human) full genome as provided by UCSC (hg19, Feb. 2009) and stored in Biostrings objects.

## Note

This BSgenome data package was made from the following source data files:

sequences: chromFa.zip, upstream1000.zip, upstream2000.zip, upstream5000.zip  
from <http://hgdownload.cse.ucsc.edu/goldenPath/hg19/bigZips/>  
AGAPS masks: <http://hgdownload.cse.ucsc.edu/goldenPath/hg19/database/gap.txt.gz>  
RM masks: <http://hgdownload.cse.ucsc.edu/goldenPath/hg19/bigZips/chromOut.tar.gz>  
TRF masks: <http://hgdownload.cse.ucsc.edu/goldenPath/hg19/bigZips/chromTrf.tar.gz>

See [?BSgenomeForge](#) and the BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the BSgenome software package for how to make a BSgenome data package.

## Author(s)

The Bioconductor Dev Team

## See Also

[BSgenome-class](#), [DNAString-class](#), [available.genomes](#), [BSgenomeForge](#)

**Examples**

```
BSgenome.Hsapiens.UCSC.hg19
genome <- BSgenome.Hsapiens.UCSC.hg19
seqlengths(genome)
genome$chr1 # same as genome[["chr1"]]

if ("AGAPS" %in% masknames(genome)) {

  ## Check that the assembly gaps contain only Ns:
  checkOnlyNsInGaps <- function(seq)
  {
    ## Replace all masks by the inverted AGAPS mask
    masks(seq) <- gaps(masks(seq)["AGAPS"])
    unique_letters <- uniqueLetters(seq)
    if (any(unique_letters != "N"))
      stop("assembly gaps contain more than just Ns")
  }

  ## A message will be printed each time a sequence is removed
  ## from the cache:
  options(verbose=TRUE)

  for (seqname in seqnames(genome)) {
    cat("Checking sequence", seqname, "... ")
    seq <- genome[[seqname]]
    checkOnlyNsInGaps(seq)
    cat("OK\n")
  }
}

## See the GenomeSearching vignette in the BSgenome software
## package for some examples of genome-wide motif searching using
## Biostrings and the BSgenome data packages:
if (interactive())
  vignette("GenomeSearching", package="BSgenome")
```

# Index

\*Topic **data**

BSgenome.Hsapiens.UCSC.hg19, [1](#)

\*Topic **package**

BSgenome.Hsapiens.UCSC.hg19, [1](#)

available.genomes, [1](#)

BSgenome-class, [1](#)

BSgenome.Hsapiens.UCSC.hg19, [1](#)

BSgenome.Hsapiens.UCSC.hg19-package  
(BSgenome.Hsapiens.UCSC.hg19),  
[1](#)

BSgenomeForge, [1](#)

DNASTring-class, [1](#)

Hsapiens (BSgenome.Hsapiens.UCSC.hg19),  
[1](#)