

Package ‘interactiveDisplay’

April 8, 2026

Type Package

Title Package for enabling powerful shiny web displays of Bioconductor objects

Version 1.48.0

Date 2021-11-17

Imports interactiveDisplayBase (>= 1.7.3), shiny, RColorBrewer, ggplot2, reshape2, plyr, gridSVG, XML, Category, AnnotationDbi

Depends R (>= 2.10), methods, BiocGenerics, grid

Suggests RUnit, hgu95av2.db, knitr, GenomicRanges, SummarizedExperiment, GOstats, ggbio, GO.db, Gviz, rtracklayer, metagenomeSeq, gplots, vegan, Biobase

Enhances rstudio

Description The interactiveDisplay package contains the methods needed to generate interactive Shiny based display methods for Bioconductor objects.

License Artistic-2.0

Collate 'interactiveDisplay.R' 'ExpressionSet.R' 'GRanges.R' 'GRangesList.R' 'SummarizedExperiment.R' 'gridsvgjs.R' 'bicgo.R' 'gridtweak.R' 'simplenet.R' 'MRExperiment.R' 'altgr.R' 'zzz.R'

VignetteBuilder knitr

biocViews GO, GeneExpression, Microarray, Sequencing, Classification, Network, QualityControl, Visualization, Visualization, Genetics, DataRepresentation, GUI, AnnotationData, ShinyApps

RoxygenNote 7.1.1

PackageStatus Deprecated

git_url <https://git.bioconductor.org/packages/interactiveDisplay>

git_branch RELEASE_3_22

git_last_commit a68c9ad

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2026-04-07

Author Bioconductor Package Maintainer [cre],
Shawn Balcome [aut],
Marc Carlson [ctb]

Maintainer Bioconductor Package Maintainer <maintainer@bioconductor.org>

Contents

altgr	2
bicgo	3
display	4
expr	5
gridsvgjs	5
gridtweak	6
mmgr	7
mmgrl	7
se	7
simplenet	8
Index	9

altgr

altgr: Open a Shiny Application for ...

Description

This opens a shiny visualization application in the browser based on ...

Usage

```
altgr(object, ...)
```

Arguments

object	data object to display
...	additional arguments passed to methods; currently unused.

Value

Any ...

See Also

<http://bioconductor.org/packages/2.13/bioc/html/interactiveDisplay.html>

Examples

```
if(interactive()) {  
  
  ## Open an browser application for the purpose of manually biclustering an  
  ## ExpressionSet object and obtaining a GO summary for a specific bicluster.  
  
  data(mmgr)  
  altgr(mmgr)  
  
}
```

bicgo

bicgo: Open a Shiny Application for manual/interactive biclustering and GO exploration

Description

This opens a shiny visualization application in the browser based on the submitted ExpressionSet object.

Usage

```
bicgo(object, ...)
```

Arguments

object	data object to display
...	additional arguments passed to methods; currently unused.

Value

Any ExpressionSet object.

See Also

<http://bioconductor.org/packages/2.13/bioc/html/interactiveDisplay.html>

Examples

```
if(interactive()) {  
  
  ## Open an browser application for the purpose of manually biclustering an  
  ## ExpressionSet object and obtaining a GO summary for a specific bicluster.  
  
  data(expr)  
  bicgo(expr)  
  
}
```

display*display: Open a Shiny application for a Bioconductor object*

Description

This opens a shiny visualization application in the browser based on the submitted object.

Usage

```
display(object, ...)
```

Arguments

<code>object</code>	data object to display
<code>...</code>	additional arguments passed to methods; currently unused.

Value

Usually some variation of the initial input object, but it may be altered by the display widget (subset for example).

Author(s)

Shawn Balcome and Marc Carlson

See Also

<http://bioconductor.org/packages/2.13/bioc/html/interactiveDisplay.html>

Examples

```
if(interactive()) {  
  
  ## draw a RangedSummarizedExperiment object  
  data(se)  
  display(se)  
  
  ## draw a GRanges object  
  data(mmgr)  
  display(mmgr)  
  
  ## some display methods allow subsetting.  
  ## To take advantage, just use an assignment operator like this:  
  mmgr2 <- display(mmgr)  
  
  ## draw a GRangesList object  
  data(mmgr1)  
  display(mmgr1)  
  
  ## draw an ExpressionSet object  
  data(expr)  
  display(expr)
```

```
## draw an MExperiment object (placeholder!!!)
data(mr)
display(mr)

}
```

expr

An Example ExpressionSet object

Description

The expression data are real but anonymized. The data are from an experiment that used Affymetrix U95v2 chips. The data were processed by dChip and then exported to R for analysis. The data illustrate ExpressionSet-class, with assayData containing the required matrix element exprs and an additional matrix se.exprs. se.exprs has the same dimensions as exprs. The phenoData and standard error estimates (se.exprs) are made up. The information in the "description" slot is fake.

Details

The data for 26 cases, labeled A to Z and 500 genes. Each case has three covariates: sex (male/female); type (case/control); and score (testing score).

Examples

```
data(expr)
```

gridsvgjs

gridsvgjs: Open a Shiny Application for a Grid Plot

Description

This opens a shiny visualization application in the browser based on the submitted plot.

Usage

```
gridsvgjs(object, ...)
```

Arguments

object	data object to display
...	additional arguments passed to methods; currently unused.

Value

Any grid based plot. For example: a plot produced with lattice, ggplot2 or biobase libraries.

See Also

<http://bioconductor.org/packages/2.13/bioc/html/interactiveDisplay.html>

Examples

```
if(interactive()) {  
  
  ## Send a grid based plot to a browser as a Javascript interactive SVG  
  
  library(ggplot2)  
  data(mtcars)  
  qp <- qplot(mpg, data=mtcars, geom="density", fill=factor(cyl), alpha=I(.4))  
  gridsvgjs(qp)  
  
}
```

gridtweak

gridtweak: Open a Shiny Application for the purpose of tweaking grid plots

Description

This opens a shiny visualization application in the browser.

Usage

```
gridtweak(...)
```

Arguments

... additional arguments passed to methods; currently unused.

Value

Any grid based plot. For example: a plot produced with lattice, ggplot2 or biobase libraries.

See Also

<http://bioconductor.org/packages/2.13/bioc/html/interactiveDisplay.html>

Examples

```
if(interactive()) {  
  
  ## Send a grid based plot to a browser as a Javascript interactive SVG  
  
  gridtweak()  
  
}
```

`mmgr`*An Example GRanges Object*

Description

A toy GRanges object for demonstration purposes.

Examples

```
data(mmgr)
```

`mmgr1`*An Example GRangesList Object*

Description

A toy GRangesList dataset derived from the GRanges dataset in this package for purposes of demonstration.

Details

The GRanges dataset was submitted to `display()`, subsetted and several iterations of the results were fused into a GRangesList object. This is fake data.

Examples

```
data(mmgr1)
```

`se`*An Example RangedSummarizedExperiment Object*

Description

A toy RangedSummarizedExperiment object for demonstration purposes.

Examples

```
data(se)
```

simplenet

simplenet: Open a Shiny Application for ...

Description

This opens a shiny visualization application in the browser based on ...

Usage

```
simplenet(object, ...)
```

Arguments

object	data object to display
...	additional arguments passed to methods; currently unused.

Value

Any ...

See Also

<http://bioconductor.org/packages/2.13/bioc/html/interactiveDisplay.html>

Examples

```
if(interactive()) {  
  
  ## Open an browser application for the purpose of manually biclustering an  
  ## ExpressionSet object and obtaining a GO summary for a specific bicluster.  
  
  simplenet(mtcars)  
  
}
```

Index

* datasets

expr, 5
mmgr, 7
mmgr1, 7
se, 7

* methods

altgr, 2
bicgo, 3
display, 4
gridsvgjs, 5
gridtweak, 6
simplenet, 8

altgr, 2
altgr, ANY-method (altgr), 2

bicgo, 3
bicgo, ANY-method (bicgo), 3

display, 4
display, ANY-method (display), 4
display, ExpressionSet-method (display),
4
display, GRanges-method (display), 4
display, GRangesList-method (display), 4
display, missing-method (display), 4
display, MRexperiment-method (display), 4
display, RangedSummarizedExperiment-method
(display), 4

expr, 5

gridsvgjs, 5
gridsvgjs, ANY-method (gridsvgjs), 5
gridtweak, 6
gridtweak, ANY-method (gridtweak), 6

mmgr, 7
mmgr1, 7

se, 7
simplenet, 8
simplenet, ANY-method (simplenet), 8