

Package ‘mzR’

April 12, 2018

Type Package

Title parser for netCDF, mzXML, mzData and mzML and mzIdentML files
(mass spectrometry data)

Version 2.12.0

Author Bernd Fischer, Steffen Neumann, Laurent Gatto, Qiang Kou

Maintainer Bernd Fischer <b.fischer@dkfz.de>,
Steffen Neumann <sneumann@ipb-halle.de>,
Laurent Gatto <l390@cam.ac.uk>,
Qiang Kou <qkou@umail.iu.edu>

Description mzR provides a unified API to the common file formats and parsers available for mass spectrometry data. It comes with a wrapper for the ISB random access parser for mass spectrometry mzXML, mzData and mzML files. The package contains the original code written by the ISB, and a subset of the proteowizard library for mzML and mzIdentML. The netCDF reading code has previously been used in XCMS.

License Artistic-2.0

LazyLoad yes

Depends Rcpp (>= 0.10.1), methods, utils

Imports Biobase, BiocGenerics (>= 0.13.6), ProtGenerics (>= 1.9.1)

Suggests msdata (>= 0.15.1), RUnit, mzID, BiocStyle (>= 2.5.19),
knitr, XML

VignetteBuilder knitr

LinkingTo Rcpp, zlibbioc

RcppModules Ramp, Pwiz, Ident

SystemRequirements C++11, GNU make, NetCDF

URL <https://github.com/sneumann/mzR/>

BugReports <https://github.com/sneumann/mzR/issues/>

biocViews Infrastructure, DataImport, Proteomics, Metabolomics,
MassSpectrometry

RoxygenNote 6.0.1

NeedsCompilation yes

R topics documented:

mzR-package	2
copyWriteMSData	3
isolationWindow-methods	4
metadata	5
mzR-class	6
openMSfile	8
peaks	10
pwiz.version	12
writeMSData	12

Index	14
--------------	-----------

mzR-package	<i>parser for mzXML, mzData, mzML and mzid files (mass spectrometry data)</i>
-------------	---

Description

The mzR package is a library purely for accessing mass spectrometry data in a wide range of formats. Several backend libraries are used, such as the ISB random access parser (RAMP) and ProteoWizard (pwiz) for mass spectrometry mzXML, mzData, mzML and mzid files. The package contains the original RAMP code written by the ISB, and a subset of the proteowizard library for mzML and mzid.

Details

Further information is available in the following vignette:

mzR mzR, Ramp, mzXML, mzData, mzML (source, pdf)

Author(s)

Bernd Fischer, Steffen Neumann, Laurent Gatto, Qiang Kou

Maintainers: Bernd Fischer <bernd.fischer@embl.de>, Steffen Neumann <sneumann@ipb-halle.de>, Laurent Gatto <lgr390@cam.ac.uk>, Qiang Kou <qkou@umail.iu.edu>

References

Nat Biotechnol. 2012 Oct 10;30(10):918-20. doi: 10.1038/nbt.2377. A cross-platform toolkit for mass spectrometry and proteomics. Chambers MC, Maclean B, Burke R, Amodei D, Ruderman DL, Neumann S, Gatto L, Fischer B, Pratt B, Egertson J, Hoff K, Kessner D, Tasman N, Shulman N, Frewen B, Baker TA, Brusniak MY, Paulse C, Creasy D, Flashner L, Kani K, Moulding C, Seymour SL, Nuwaysir LM, Lefebvre B, Kuhlmann F, Roark J, Rainer P, Detlev S, Hemenway T, Huhmer A, Langridge J, Connolly B, Chadick T, Holly K, Eckels J, Deutsch EW, Moritz RL, Katz JE, Agus DB, Maccoss M, Tabb DL, Mallick P. <http://www.ncbi.nlm.nih.gov/pubmed/23051804>

copyWriteMSData	<i>Write MS spectrum data to a MS file copying metadata from the originating file</i>
-----------------	---

Description

Copy general information from the originating MS file and write this, along with the provided spectra data, to a new file. The expected workflow is the following: data is first loaded from an MS file, e.g. using [peaks](#) and [header](#) methods, processed in R and then saved again to an MS file providing the (eventually) manipulated spectra and header data with arguments `header` and `data`.

Usage

```
copyWriteMSData(object, file, original_file, header, backend =  
  "pwiz", outformat = "mzml", rtime_seconds = TRUE, software_processing)
```

Arguments

<code>object</code>	list containing for each spectrum one matrix with columns <code>mz</code> (first column) and <code>intensity</code> (second column). See also peaks for the method that reads such data from an MS file.
<code>file</code>	character(1) defining the name of the file.
<code>original_file</code>	character(1) with the name of the original file from which the spectrum data was first read.
<code>header</code>	data.frame with the header data for the spectra. Has to be in the format as the data.frame returned by the header method.
<code>backend</code>	character(1) defining the backend that should be used for writing. Currently only "pwiz" backend is supported.
<code>outformat</code>	character(1) the format of the output file. One of "mzml" or "mzxml".
<code>rtime_seconds</code>	logical(1) whether the retention time is provided in seconds or minutes (defaults to TRUE).
<code>software_processing</code>	list of character vectors (or single character vector). Each character vector providing information about the software that was used to process the data with optional additional description of processing steps. The length of each character vector has to be ≥ 3 : the first element being the name of the software, the second string its version and the third element the MS CV ID of the software (or "MS:-1" if not known). All additional elements are optional and represent the MS CV ID of each processing step performed with the software.

Note

`copyWriteMSData` supports at present copying data from `mzXML` and `mzML` and exporting to `mzML`. Copying and exporting to `mzXML` can fail for some input files.

The intention of this function is to copy data from an existing file and save it along with eventually modified data to a new file. To write new MS data files use the [writeMSData](#) function instead.

Author(s)

Johannes Rainer

See Also

`writeMSData` for a function to save MS data to a new mzML or mzXML file.

Examples

```
## Open a MS file and read the spectrum and header information
library(msdata)
fl <- system.file("threonine", "threonine_i2_e35_pH_tree.mzXML",
  package = "msdata")
ms_fl <- openMSfile(fl, backend = "pwiz")

## Get the spectra
pks <- spectra(ms_fl)
## Get the header
hdr <- header(ms_fl)

## Modify the spectrum data adding 100 to each intensity.
pks <- lapply(pks, function(z) {
  z[, 2] <- z[, 2] + 100
  z
})

## Copy metadata and additional information from the originating file
## and save it, along with the modified data, to a new mzML file.
out_file <- tempfile()
copyWriteMSData(pks, file = out_file, original_file = fl,
  header = hdr)
```

isolationWindow-methods

Returns the ion selection isolation window

Description

The methods return matrices of lower (column low) and upper (column high) isolation window offsets. Matrices are returned as a list of length equal to the number of input files (provided as file names of raw mass spectrometry data objects, see below). By default (i.e when `unique. = TRUE`), only unique offsets are returned, as they are expected to be identical for all spectra per acquisition. If this is not the case, a message is displayed.

Methods

`signature(object = "character", unique. = "logical", simplify = "logical")` Returns the isolation window for the file object. By default, only unique isolation windows are returned per file (`unique = TRUE`); if set to `FALSE`, a matrix with as many rows as there are MS2 spectra. If only one file passed as an input and `simplify` is set to `TRUE` (default), the resulting list of length 1 is simplified to a matrix.

`signature(object = "mzRpwiz", unique. = "logical", simplify = "logical")` As above for `mzRpwiz` objects.

`signature(object = "mzRramp", unique. = "logical", simplify = "logical")` As above for `mzRramp` object.

Author(s)

Laurent Gatto <lg390@cam.ac.uk> based on the functionality from the `msPurity:::get_isolation_offsets` function.

Examples

```
library("msdata")
f <- msdata::proteomics(full.names = TRUE,
                        pattern = "TMT_Erwinia_1uLSike_Top10HCD_isol2_45stepped_60min_01.mzML.gz")
isolationWindow(f)

rw <- openMSfile(f)
isolationWindow(rw)
str(isolationWindow(rw, unique = FALSE))
```

metadata

Access the metadata from an mzR object.

Description

Accessors to the analytical setup metadata of a run. `runInfo` will show a summary of the experiment as a named list, including `scanCount`, `lowMZ`, `highMZ`, `dStartTime`, `dEndTime` and `startTimeStamp`. Note that `startTimeStamp` can only be extracted from *mzML* files using the *pwiz* backend or from *CDF* files. A NA is reported if its value is not available. The `instrumentInfo` method returns a named list including instrument manufacturer, model, ionisation technique, analyzer and detector. `mzRpwiz` will give more additional information including information on sample, software using and original source file. These individual pieces of information can also be directly accessed by the specific methods. `mzidInfo` is used for the `mzR` object created from a `mzid` file. It returns basic information on this `mzid` file including file provider, creation date, software, database, enzymes and spectra data format. The `mzidInfo` will return the scoring results in identification. It will return different results for different searching software used.

Usage

```
runInfo(object)
chromatogramsInfo(object)
analyzer(object)
detector(object)
instrumentInfo(object)
ionisation(object)
softwareInfo(object)
sampleInfo(object)
sourceInfo(object)
model(object)
mzidInfo(object)
modifications(object, ...)
psms(object, ...)
substitutions(object)
database(object, ...)
enzymes(object)
tolerance(object)
score(x, ...)
para(object)
```

Arguments

object	An instantiated mzR object.
x	An instantiated mzR object.
...	Additional arguments, currently ignored.

Author(s)

Steffen Neumann, Laurent Gatto and Qiang Kou

See Also

See for example [peaks](#) to access the data for the spectra in a "mzR" class.

Examples

```
library(msdata)

file <- system.file("microtofq/MM8.mzML", package = "msdata")
mz <- openMSfile(file)
fileName(mz)
instrumentInfo(mz)
runInfo(mz)
close(mz)

file <- system.file("cdf/ko15.CDF", package = "msdata")
mz <- openMSfile(file, backend = "netCDF")
fileName(mz)
instrumentInfo(mz)
runInfo(mz)
close(mz)

file <- system.file("mzid", "Tandem.mzid.gz", package="msdata")
mzid <- openIDfile(file)
softwareInfo(mzid)
enzymes(mzid)
```

mzR-class

Class mzR and sub-classes

Description

The class mzR is the main class for the common mass spectrometry formats. It is a virtual class and thus not supposed to be instantiated directly.

The sub-classes implement specific APIs to access the underlying data and metadata in the files. Currently, mzRramp and mzRpwiz are available implementations. mzRramp uses the ISB 'RAMP' random access C/C++ API, and mzRpwiz uses Proteowizard to access the relevant information in mzData, mzXML and mzML files.

Additional sub-classes using the proteowizard API and netCDF are planned.

Objects from the Class

mzR is a virtual class, so instances cannot be created.

Objects can be created by calls of the form `new("mzRramp", ...)`, but more often they will be created with [openMSfile](#).

After creating a mzR, you can write it into a file. mzXML, mzML, mgf formats are supported.

Slots

fileName: Object of class character storing the original filename used when the instance was created.

backend: One of the implemented backends or NULL.

__classVersion__: Object of class "Versioned", from Biobase.

Extends

Class ["Versioned"](#), directly.

Methods

For methods to access raw data (spectra and chromatograms), see [peaks](#).

Methods currently implemented for mzR

fileName signature(object = "mzR"): ...

Methods currently implemented for mzRramp

analyzer signature(object = "mzRramp"): ...

close signature(con = "mzRramp"): ...

detector signature(object = "mzRramp"): ...

fileName signature(object = "mzRramp"): ...

initializeRamp signature(object = "mzRramp"): ...

instrumentInfo signature(object = "mzRramp"): ...

ionisation signature(object = "mzRramp"): ...

isInitialized signature(object = "mzRramp"): ...

length signature(x = "mzRramp"): ...

manufacturer signature(object = "mzRramp"): ...

model signature(object = "mzRramp"): ...

runInfo signature(object = "mzRramp"): ...

Methods currently implemented for mzRpwiz

analyzer signature(object = "mzRpwiz"): ...

detector signature(object = "mzRpwiz"): ...

instrumentInfo signature(object = "mzRpwiz"): ...

ionisation signature(object = "mzRpwiz"): ...

length signature(x = "mzRpwiz"): ...

manufacturer signature(object = "mzRpwiz"): ...

model signature(object = "mzRpwiz"): ...
runInfo signature(object = "mzRpwiz"): ...
chromatogramsInfo signature(object = "mzRpwiz"): ...

Methods currently implemented for mzRident

mzidInfo signature(object = "mzRident"): ...
psms signature(object = "mzRident"): ...
modifications signature(object = "mzRident"): ...
substitutions signature(object = "mzRident"): ...
database signature(x = "mzRident"): ...
enzymes signature(object = "mzRident"): ...
sourceInfo signature(object = "mzRident"): ...
tolerance signature(object = "mzRident"): ...
score signature(object = "mzRident"): ...
para signature(object = "mzRident"): ...

Author(s)

Steffen Neumann, Laurent Gatto, Qiang Kou

References

RAMP: <http://tools.proteomecenter.org/wiki/index.php?title=Software:RAMP> Proteowizard: <http://proteowizard.sourceforge.net/>

Examples

```
library(msdata)
filepath <- system.file("microtofq", package = "msdata")
file <- list.files(filepath, pattern="MM14.mzML",
                  full.names=TRUE, recursive = TRUE)
mzml <- openMSfile(file)
close(mzml)

## using the pwiz backend
mzml <- openMSfile(file, backend = "pwiz")
```

openMSfile

Create and check mzR objects from netCDF, mzXML, mzData or mzML files.

Description

The openMSfile constructor will create a new format-specific mzR object, open 'filename' file and all header information is loaded as a Rcpp module and made accessible through the ramp or pwiz slot of the resulting object.

The openIDfile constructor will create a new format-specific mzR object, open 'filename' file and all information is loaded as a Rcpp module. The mzid format is supported through pwiz backend. Only mzIdentML 1.1 is supported.

Usage

```
openMSfile(filename, backend=c("pwiz", "Ramp", "netCDF"), verbose = FALSE)

initializeRamp(object)

isInitialized(object)

fileName(object, ...)

openIDfile(filename, verbose = FALSE)
```

Arguments

filename	Path name of the netCDF, mzData, mzXML or mzML file to read/write.
backend	A character specifying with backend API to use. Currently 'Ramp', 'netCDF' and 'pwiz' (default) are available.
object	An instantiated mzR object.
verbose	Enable verbose output.
...	Additional arguments, currently ignored.

Author(s)

Steffen Neumann, Laurent Gatto, Qiang Kou

Examples

```
library(msdata)
filepath <- system.file("microtofq", package = "msdata")
file <- list.files(filepath, pattern="MM14.mzML",
                  full.names=TRUE, recursive = TRUE)
mz <- openMSfile(file)
fileName(mz)
runInfo(mz)
close(mz)

## Not run:
## to use another backend
mz <- openMSfile(file, backend = "pwiz")
mz

## End(Not run)

file <- system.file("mzid", "Tandem.mzid.gz", package="msdata")
mzid <- openIDfile(file)
softwareInfo(mzid)
enzymes(mzid)
```

peaks

*Access the raw data from an mzR object.***Description**

Access the MS raw data. The `peaks`, `spectra` (can be used interchangeably) and `peaksCount` functions return the (m/z, intensity) pairs and the number peaks in the spectrum/spectra. `peaks` and `spectra` return a single matrix if `scans` is a numeric of length 1 and a list of matrices if several scans are asked for or no `scans` argument is provided (i.e all spectra in the object are returned). `peaksCount` will return a numeric of length n.

The `header` function returns a list containing `seqNum`, `acquisitionNum`, `msLevel`, `peaksCount`, `totIonCurrent`, `retentionTime` (in seconds), `basePeakMZ`, `basePeakIntensity`, `collisionEnergy`, `ionisationEnergy`, `lowM`, `highMZ`, `precursorScanNum`, `precursorMZ`, `precursorCharge`, `precursorIntensity`, `mergedScan`, `mergedResultScanNum`, `mergedResultStartScanNum`, `mergedResultEndScanNum`, `spectrumId` and `injectionTime` (ion injection time, in seconds) when available in the original file. If multiple scans are queried, a `data.frame` is returned with the scans reported along the rows.

The `get3Dmap` function performs a simple resampling between `lowMz` and `highMz` with `resMz` resolution. A matrix of dimensions `length(scans)` times `seq(lowMz, highMz, resMz)` is returned.

The `chromatogram` (chromatograms) accessors return chromatograms for the MS file handle. If a single index is provided, as `data.frame` containing the retention time (1st column) and intensities (2nd column) is returned. The name of the former is always `time`, while the latter will depend on the run parameters.

If more than 1 or no chromatogram indices are provided, then a list of chromatograms is returned; either those passed as argument or all of them. By default, the first (and possibly only) chromatogram is the total ion count, which can also be accessed with the `tic` method.

The `nChrom` function returns the number of chromatograms, including the total ion chromatogram.

Note that access to chromatograms is only supported in the `pwiz` backend.

Usage

```
header(object, scans, ...)
```

```
peaksCount(object, scans, ...)
```

```
peaks(object, ...)
```

```
spectra(object, ...) ## same as peaks
```

```
get3Dmap(object, scans, lowMz, highMz, resMz, ...)
```

```
chromatogram(object, ...)
```

```
chromatograms(object, ...) ## same as chromatogram
```

```
tic(object, ...)
```

```
nChrom(object)
```

Arguments

object	An instantiated mzR object.
scans	A numeric specifying which scans to return. Optional for the header, peaks, scans and peaksCount methods. If omitted, the requested data for all peaks is returned.
lowMz, highMz	Numerics defining the m/z range to be returned.
resMz	a numeric defining the m/z resolution.
...	Other arguments. A scan parameter can be passed to peaks.

Details

The column `acquisitionNum` in the `data.frame` returned by the `header` method contains the index during the scan in which the signal from the spectrum was measured. The `pwiz` backend extracts this number from the spectrum's ID provided in the `mzML` file. In contrast, column `seqNum` contains the index of each spectrum within the file and is thus consecutively numbered. Spectra from files with multiple MS levels are linked to each other *via* their `acquisitionNum`: column `precursorScanNum` of an e.g. MS level 2 spectrum contains the `acquisitionNum` of the related MS level 1 spectrum.

Note

Spectrum identifiers are only specified in `mzML` files, thus, for all other file types the column `"spectrumId"` of the result `data.frame` returned by `header` contains `"scan="` followed by the acquisition number of the spectrum. Also, only the `pwiz` backend supports extraction of the spectra's IDs from `mzML` files. Thus, only `mzML` files read with `backend = "pwiz"` provide the spectrum IDs defined in the file. The content of the spectrum identifier depends on the vendor and the instrument acquisition settings and is reported here as a character, in its raw form, without further parsing.

Author(s)

Steffen Neumann and Laurent Gatto

See Also

[instrumentInfo](#) for metadata access and the `"mzR"` class.

[writeMSData](#) and [copyWriteMSData](#) for functions to write MS data in `mzML` or `mzXML` format.

Examples

```
library(msdata)
filepath <- system.file("microtofq", package = "msdata")
file <- list.files(filepath, pattern="MM14.mzML",
                  full.names=TRUE, recursive = TRUE)
mz <- openMSfile(file)
runInfo(mz)
colnames(header(mz))
close(mz)

## A shotgun LCMSMS experiment
f <- proteomics(full.names = TRUE,
                pattern = "TMT_Erwinia_1uLSike_Top10HCD_isol2_45stepped_60min_01.mzML.gz")
x <- openMSfile(f, backend = "pwiz")
x
```

```

nChrom(x)
head(tic(x))
head(chromatogram(x, 1L)) ## same as tic(x)
str(chromatogram(x)) ## as a list

## An MRM experiment
f <- proteomics(full.names = TRUE, pattern = "MRM")
x <- openMSfile(f, backend = "pwiz")
x
nChrom(x)
head(tic(x))
head(chromatogram(x, 1L)) ## same as tic(x)
str(chromatogram(x, 10:12))

```

pwiz.version	<i>Get the version number of pwiz backend.</i>
--------------	--

Description

Get the version number of pwiz backend.

Usage

```
pwiz.version()
```

writeMSData	<i>Write MS spectrum data to an MS file</i>
-------------	---

Description

writeMSData exports the MS spectrum data provided with parameters header and data to an MS file in mzML or mzXML format.

Usage

```

## S4 method for signature 'list,character'
writeMSData(object, file, header,
            backend = "pwiz", outformat = "mzml", rtime_seconds = TRUE,
            software_processing)

```

Arguments

object	list containing for each spectrum one matrix with columns mz (first column) and intensity (second column). See also peaks for the method that reads such data from an MS file.
file	character(1) defining the name of the file.
header	data.frame with the header data for the spectra. Has to be in the format as the data.frame returned by the header method.

backend	character(1) defining the backend that should be used for writing. Currently only "pwiz" backend is supported.
outformat	character(1) the format of the output file. One of "mzml" or "mzxml".
rtime_seconds	logical(1) whether the retention time is provided in seconds or minutes (defaults to TRUE).
software_processing	list of character vectors (or single character vector). Each character vector providing information about the software that was used to process the data with optional additional description of processing steps. The length of each character vector has to be ≥ 3 : the first element being the name of the software, the second string its version and the third element the MS CV ID of the software (or "MS:-1" if not known). All additional elements are optional and represent the MS CV ID of each processing step performed with the software.

Author(s)

Johannes Rainer

See Also

[copyWriteMSData](#) for a function to copy general information from a MS data file and writing eventually modified MS data from that originating file.

Examples

```
## Open a MS file and read the spectrum and header information
library(msdata)
f1 <- system.file("threonine", "threonine_i2_e35_pH_tree.mzXML",
  package = "msdata")
ms_f1 <- openMSfile(f1, backend = "pwiz")

## Get the spectra
pks <- spectra(ms_f1)
## Get the header
hdr <- header(ms_f1)

## Modify the spectrum data adding 100 to each intensity.
pks <- lapply(pks, function(z) {
  z[, 2] <- z[, 2] + 100
  z
})

## Write the data to a mzML file.
out_file <- tempfile()
writeMSData(object = pks, file = out_file, header = hdr)
```

Index

*Topic **classes**

mzR-class, 6

*Topic **methods**

isolationWindow-methods, 4

*Topic **package, file**

mzR-package, 2

analyzer (metadata), 5

analyzer, mzRnetCDF-method (mzR-class), 6

analyzer, mzRp wiz-method (mzR-class), 6

analyzer, mzRramp-method (mzR-class), 6

chromatogram (peaks), 10

chromatogram, mzRp wiz-method (peaks), 10

chromatograms (peaks), 10

chromatograms, mzRp wiz-method (peaks), 10

chromatogramsInfo (metadata), 5

chromatogramsInfo, mzRp wiz-method (mzR-class), 6

class:mzR (mzR-class), 6

class:mzRident (mzR-class), 6

class:mzRnetCDF (mzR-class), 6

class:mzRp wiz (mzR-class), 6

class:mzRramp (mzR-class), 6

close (mzR-class), 6

close, mzRnetCDF-method (mzR-class), 6

close, mzRp wiz-method (mzR-class), 6

close, mzRramp-method (mzR-class), 6

copyWriteMSData, 3, 11, 13

database (metadata), 5

database, mzRident-method (mzR-class), 6

detector (metadata), 5

detector, mzRnetCDF-method (mzR-class), 6

detector, mzRp wiz-method (mzR-class), 6

detector, mzRramp-method (mzR-class), 6

enzymes (metadata), 5

enzymes, mzRident-method (mzR-class), 6

fileName (openMSfile), 8

fileName, mzR-method (mzR-class), 6

get3Dmap (peaks), 10

get3Dmap, mzRp wiz-method (peaks), 10

get3Dmap, mzRramp-method (peaks), 10

header, 3, 10, 12

header (peaks), 10

header, mzRnetCDF, missing-method (peaks), 10

header, mzRnetCDF, numeric-method (peaks), 10

header, mzRp wiz, missing-method (peaks), 10

header, mzRp wiz, numeric-method (peaks), 10

header, mzRramp, missing-method (peaks), 10

header, mzRramp, numeric-method (peaks), 10

initializeRamp (openMSfile), 8

initializeRamp, mzRramp-method (mzR-class), 6

instrumentInfo, 11

instrumentInfo (metadata), 5

instrumentInfo, mzRnetCDF-method (mzR-class), 6

instrumentInfo, mzRp wiz-method (mzR-class), 6

instrumentInfo, mzRramp-method (mzR-class), 6

ionisation (metadata), 5

ionisation, mzRnetCDF-method (mzR-class), 6

ionisation, mzRp wiz-method (mzR-class), 6

ionisation, mzRramp-method (mzR-class), 6

isInitialized (openMSfile), 8

isInitialized, mzRnetCDF-method (mzR-class), 6

isInitialized, mzRramp-method (mzR-class), 6

isolationWindow

(isolationWindow-methods), 4

isolationWindow, character-method

(isolationWindow-methods), 4

isolationWindow, mzRp wiz-method

(isolationWindow-methods), 4

- isolationWindow, mzRramp-method
(isolationWindow-methods), 4
- isolationWindow-methods, 4
- length (mzR-class), 6
- length, mzRident-method (mzR-class), 6
- length, mzRnetCDF-method (mzR-class), 6
- length, mzRpwiz-method (mzR-class), 6
- length, mzRramp-method (mzR-class), 6
- manufacturer (metadata), 5
- manufacturer, mzRnetCDF-method
(mzR-class), 6
- manufacturer, mzRpwiz-method
(mzR-class), 6
- manufacturer, mzRramp-method
(mzR-class), 6
- metadata, 5
- model (metadata), 5
- model, mzRnetCDF-method (mzR-class), 6
- model, mzRpwiz-method (mzR-class), 6
- model, mzRramp-method (mzR-class), 6
- modifications (metadata), 5
- modifications, mzRident-method
(mzR-class), 6
- mzidInfo (metadata), 5
- mzidInfo, mzRident-method (mzR-class), 6
- mzR, 6, 11
- mzR (mzR-package), 2
- mzR-class, 6
- mzR-package, 2
- mzRident-class (mzR-class), 6
- mzRnetCDF-class (mzR-class), 6
- mzRpwiz-class (mzR-class), 6
- mzRramp-class (mzR-class), 6
- nChrom (peaks), 10
- openIDfile (openMSfile), 8
- openMSfile, 7, 8
- para (metadata), 5
- para, mzRident-method (mzR-class), 6
- peaks, 3, 6, 7, 10, 12
- peaks, mzRnetCDF-method (peaks), 10
- peaks, mzRpwiz-method (peaks), 10
- peaks, mzRramp-method (peaks), 10
- peaksCount (peaks), 10
- peaksCount, mzRpwiz, missing-method
(peaks), 10
- peaksCount, mzRpwiz, numeric-method
(peaks), 10
- peaksCount, mzRramp, missing-method
(peaks), 10
- peaksCount, mzRramp, numeric-method
(peaks), 10
- psms (metadata), 5
- psms, mzRident-method (mzR-class), 6
- pwiz.version, 12
- runInfo (metadata), 5
- runInfo, mzRnetCDF-method (mzR-class), 6
- runInfo, mzRpwiz-method (mzR-class), 6
- runInfo, mzRramp-method (mzR-class), 6
- sampleInfo (metadata), 5
- sampleInfo, mzRpwiz-method (mzR-class), 6
- score (metadata), 5
- score, mzRident-method (mzR-class), 6
- softwareInfo (metadata), 5
- softwareInfo, mzRident-method
(mzR-class), 6
- softwareInfo, mzRpwiz-method
(mzR-class), 6
- sourceInfo (metadata), 5
- sourceInfo, mzRident-method (mzR-class),
6
- sourceInfo, mzRpwiz-method (mzR-class), 6
- spectra (peaks), 10
- spectra, mzRnetCDF-method (peaks), 10
- spectra, mzRpwiz-method (peaks), 10
- spectra, mzRramp-method (peaks), 10
- substitutions (metadata), 5
- substitutions, mzRident-method
(mzR-class), 6
- tic (peaks), 10
- tic, mzRpwiz-method (peaks), 10
- tolerance (metadata), 5
- tolerance, mzRident-method (mzR-class), 6
- Versioned, 7
- writeMSData, 3, 4, 11, 12
- writeMSData, list, character-method
(writeMSData), 12