

Package ‘easyreporting’

December 30, 2024

Type Package

Title Helps creating report for improving Reproducible Computational Research

Version 1.18.0

Description An S4 class for facilitating the automated creation of rmarkdown files inside other packages/software even without knowing rmarkdown language. Best if implemented in functions as ``recursive" style programming.

License Artistic-2.0

Encoding UTF-8

biocViews ReportWriting

LazyData false

BugReports <https://github.com/drighelli/easyreporting/issues>

Imports rmarkdown, methods, tools, shiny, rlang

Suggests distill, BiocStyle, knitr, readxl, edgeR, limma, EDASeq, statmod

RoxygenNote 7.1.1

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/easyreporting>

git_branch RELEASE_3_20

git_last_commit 6762dd5

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-12-30

Author Dario Righelli [cre, aut]

Maintainer Dario Righelli <dario.righelli@gmail.com>

Contents

| | |
|--|---|
| addResource | 2 |
| addResource,easyreporting-method | 3 |
| compile | 4 |
| compile,easyreporting-method | 4 |
| easyreporting | 5 |

| | |
|--|----|
| erGUIVolcano | 6 |
| getBibliography | 6 |
| getBibliography,easyreporting-method | 7 |
| getOptionsList | 8 |
| getOptionsList,easyreporting-method | 8 |
| getReportFilename | 9 |
| getReportFilename,easyreporting-method | 9 |
| initReportFilename | 10 |
| initReportFilename,easyreporting-method | 11 |
| makeOptionsList | 12 |
| mkdCodeChunkCommented | 13 |
| mkdCodeChunkCommented,easyreporting-method | 14 |
| mkdCodeChunkComplete | 15 |
| mkdCodeChunkComplete,easyreporting-method | 15 |
| mkdCodeChunkEnd | 16 |
| mkdCodeChunkEnd,easyreporting-method | 17 |
| mkdCodeChunkSt | 18 |
| mkdCodeChunkSt,easyreporting-method | 19 |
| mkdCodeChunkTitledCommented | 20 |
| mkdCodeChunkTitledCommented,easyreporting-method | 21 |
| mkdGeneralMsg | 22 |
| mkdGeneralMsg,easyreporting-method | 22 |
| mkdGeneralTitledMsg | 23 |
| mkdGeneralTitledMsg,easyreporting-method | 24 |
| mkdSetGlobalOpts | 24 |
| mkdSetGlobalOpts,easyreporting-method | 25 |
| mkdSourceFiles | 25 |
| mkdSourceFiles,easyreporting-method | 26 |
| mkdTitle | 26 |
| mkdTitle,easyreporting-method | 27 |
| mkdVariableAssignment | 28 |
| mkdVariableAssignment,easyreporting-method | 28 |
| setBibliography | 29 |
| setBibliography,easyreporting-method | 30 |
| setOptionsList | 31 |
| setOptionsList,easyreporting-method | 32 |

Index **34**

| | |
|-------------|--------------------|
| addResource | <i>addResource</i> |
|-------------|--------------------|

Description

addResource

Usage

addResource(object, source, reference, description)

Arguments

| | |
|-------------|--|
| object | an easyreporting class instance |
| source | a string indicating the reference (i.e. "GEO") |
| reference | a string indicanting the reference of the source (i.e. "GSE60231") |
| description | a natural language description |

Value

an easyreporting class instance

Examples

```
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
rd <- addResource(rd, source="GEO", "GSE60231", "Transcriptome of BMDC to different antigen delivery systems")
## Not run:
compile(rd)

## End(Not run)
```

addResource,easyreporting-method
addResource

Description

addResource

Usage

```
## S4 method for signature 'easyreporting'
addResource(object, source, reference, description)
```

Arguments

| | |
|-------------|--|
| object | an easyreporting class instance |
| source | a string indicating the reference (i.e. "GEO") |
| reference | a string indicanting the reference of the source (i.e. "GSE60231") |
| description | a natural language description |

Value

an easyreporting class instance

Examples

```
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
rd <- addResource(rd, source="GEO", "GSE60231", "Transcriptome of BMDC to different antigen delivery systems")
## Not run:
compile(rd)

## End(Not run)
```

compile

compile

Description

prints the sessionInfo and compiles the produced rmarkdown file into an HTML report.

Usage

```
compile(object)
```

Arguments

object an easyreporting class object

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report", title="example_report",
                    author=c("It's me"))
compile(rd)
## End(Not run)
```

`compile,easyreporting-method`*compile*

Description

prints the sessionInfo and compiles the rmarkdown file

Usage

```
## S4 method for signature 'easyreporting'
compile(object)
```

Arguments

object an easyreporting class object

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report", title="example_report",
                    author=c("It's me"))
compile(rd)

## End(Not run)
```

easyreporting

easyreporting

Description

An S4 class for managing rmarkdown report. Each instance describes an rmarkdown file.

Usage

```
easyreporting(
  filenamePath,
  title,
  author,
  optionList = NULL,
  documentType = "rmarkdown::html_document",
  bibfile = ""
)

easyreporting(
  filenamePath,
  title,
  author,
  optionList = NULL,
  documentType = "rmarkdown::html_document",
  bibfile = ""
)
```

Arguments

| | |
|--------------|---|
| filenamePath | the path with the name of the rmarkdown. |
| title | the title of the report section. |
| author | the author(s) of the report. |
| optionList | a list of options for the general rmarkdown document. |
| documentType | type of report final document, if author(s) is a person it will be <code>distill::distill_article</code> (<code>rmarkdown::html_document</code> default) |
| bibfile | a bibfile for bibliography. |

Value

an S4 `easyreporting` class instance

Slots

filenamePath the path with the name of the rmarkdown.
 title the title of the report section.
 author the author(s) of the report.
 type of report final document, if author(s) is a person it will be `distill::distill_article`
 (`rmarkdown::html_document` default)
 bibfile a bibfile for bibliography.
 optionList a list of options for the general rmarkdown document.

Examples

```
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author="It's me")
```

| | |
|--------------|---------------------|
| erGUIVolcano | <i>erGUIVolcano</i> |
|--------------|---------------------|

Description

executes a Shiny GUI to perform a volcano plot and trace its executed functions.

Usage

```
erGUIVolcano()
```

Value

none

Examples

```
## Not run:
erGUIVolcano()

## End(Not run)
```

| | |
|-----------------|------------------------|
| getBibliography | <i>getBibliography</i> |
|-----------------|------------------------|

Description

returns the bibfile name attached to the object

Usage

```
getBibliography(object)
```

Arguments

object an easyreporting class object

Value

none

Examples

```
## Not run:  
TBD  
  
## End(Not run)
```

getBibliography,easyreporting-method
getBibliography

Description

returns the bibfile name attached to the object

Usage

```
## S4 method for signature 'easyreporting'  
getBibliography(object)
```

Arguments

object an easyreporting class object

Value

none

Examples

```
example(easyreporting)  
getBibliography(rd)
```

`getOptionsList` *getOptionsList*

Description

returns the optionList from the easyreporting class (see the makeOptionList function for more details).

Usage

```
getOptionsList(object)
```

Arguments

object an easyreporting class object

Value

a list of options

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report", title="example_report",
                    author=c("It's me"))
optList <- getOptionsList(rd)

## End(Not run)
```

`getOptionsList,easyreporting-method`
getOptionsList

Description

returns the optionList from the easyreporting class

Usage

```
## S4 method for signature 'easyreporting'
getOptionsList(object)
```

Arguments

object an easyreporting class object

Value

a list of options

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report", title="example_report",
                    author=c("It's me"))
optList <- getOptionsList(rd)

## End(Not run)
```

`getReportFilename` *getReportFilename*

Description

returns the filename with its path of the report generated by easyreporting

Usage

```
getReportFilename(object)
```

Arguments

object an easyreporting class object

Value

a string of report file name with path

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
(rep <- getReportFilename(rd))

## End(Not run)
```

`getReportFilename`, easyreporting-method
getReportFilename

Description

returns the report filename with path

Usage

```
## S4 method for signature 'easyreporting'
getReportFilename(object)
```

Arguments

object an easyreporting class object

Value

a string of report file name with path

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
(rep <- getReportFilename(rd))

## End(Not run)
```

`initReportFilename` *initReportFilename*

Description

`initReportFilename`

Usage

```
initReportFilename(
  object,
  filepath = NULL,
  title = NULL,
  author = NULL,
  optionList = NULL,
  bibfile = NULL,
  documentType = NULL,
  resources = NULL
)
```

Arguments

object an easyreporting class object

filepath the name of the report with or without the path

author the name of the report author

documentType type of report final document. (html is default)

mainTitle the title of the report

Value

an easyreporting class object

```
initReportFilename,easyreporting-method
    initReportFilename
```

Description

internal funtion usefull to init the report for the first time.

Usage

```
## S4 method for signature 'easyreporting'
initReportFilename(
  object,
  filepath = NULL,
  title = NULL,
  author = NULL,
  optionList = NULL,
  bibfile = "",
  documentType = "rmarkdown::html_document"
)
```

Arguments

| | |
|--------------|---|
| object | an easyreporting class object |
| filepath | the name of the report with or without the path |
| author | the name of the report author as a person format (where expected comment named fields are ORCID, url, affiliation, affiliation_url). In case author is a character, it will be reported as it is. |
| bibfile | a bibfile for bibliography. |
| documentType | type of report final document, if author(s) is a person it will be <code>distill::distill_article</code> (<code>rmarkdown::html_document</code> default) |
| mainTitle | the title of the report |

Value

an easyreporting class object

See Also

[person](#)

| | |
|-----------------|------------------------|
| makeOptionsList | <i>makeOptionsList</i> |
|-----------------|------------------------|

Description

makes an list of rmarkdown options

Usage

```
makeOptionsList(
  cacheFlag = TRUE,
  evalFlag = TRUE,
  echoFlag = TRUE,
  warningFlag = FALSE,
  showMessages = FALSE,
  includeFlag = TRUE,
  collapseFlag = FALSE,
  purlFlag = TRUE,
  errorFlag = TRUE,
  messageFlag = TRUE,
  highlightFlag = TRUE,
  promptFlag = FALSE,
  stripWhiteFlag = TRUE,
  tidyFlag = FALSE
)
```

Arguments

| | |
|----------------|--|
| cacheFlag | boolean for caching chunk data (default TRUE) |
| evalFlag | boolean for evaluating the code chunk in the compiled version (default TRUE) |
| echoFlag | boolean for showing the code chunk (default TRUE) |
| warningFlag | boolean for showing the chunk warnings (default FALSE) |
| showMessages | boolean for showing the chunk warnings in compiled version (default FALSE) |
| includeFlag | boolean for including the code chunk in the compiled version (default TRUE) |
| collapseFlag | boolean for collapsing the code chunk in the compiled version (default FALSE), |
| purlFlag | boolean for extracting the code chunk as R code in a separate R file (default TRUE), |
| errorFlag | boolean for including the error generated by the code chunk in the compiled version (default TRUE), |
| messageFlag | boolean for including the code chunk messages in the compiled version (default TRUE), |
| highlightFlag | boolean for highlighting the code chunk in the compiled version (default TRUE), |
| promptFlag | boolean for including a ">" for the code chunk in the compiled version (default FALSE), |
| stripWhiteFlag | boolean for removing the white spaces at beginning/end of the code chunk in the compiled version (default TRUE), |
| tidyFlag | boolean for creating a tidy code chunk in the compiled version (default FALSE). |

Value

list of rmarkdown options

Examples

```
optList <- makeOptionsList()
```

```
mkdCodeChunkCommented mkdCodeChunkCommented
```

Description

it creates a complete code chunk, adding a natural language comment before of it.

Usage

```
mkdCodeChunkCommented(
  object,
  comment = NULL,
  code,
  optionList = getOptionsList(object),
  sourceFilesList = NULL
)
```

Arguments

| | |
|-----------------|---|
| object | an easyreporting class object |
| comment | a string with the natural language comment for the chunk. |
| code | a string within the code. |
| optionList | a list of options (default is the class options). |
| sourceFilesList | a optional list of files to source inside the chunk. |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
  title="example_report", author=c("It's me"))
optList <- makeOptionsList(includeFlag=TRUE, cacheFlag=TRUE)
mkdCodeChunkCommented(rd,
  comment="This is the comment of the following code chunk",
  code="a <- 1\n b <- 2\n (c <- a+b)\n", optionList=optList,
  sourceFilesList=NULL)

## End(Not run)
```

mkdCodeChunkCommented, easyreporting-method
mkdCodeChunkCommented

Description

it creates a complete code chunk, adding a natural language comment before of it.

Usage

```
## S4 method for signature 'easyreporting'
mkdCodeChunkCommented(
  object,
  comment = NULL,
  code,
  optionList = getOptionsList(object),
  sourceFilesList = NULL
)
```

Arguments

| | |
|------------------------------|---|
| <code>object</code> | an easyreporting class object |
| <code>comment</code> | a string with the natural language comment for the chunk. |
| <code>code</code> | a string within the code. |
| <code>optionList</code> | a list of options (default is the class options). |
| <code>sourceFilesList</code> | a optional list of files to source inside the chunk. |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
  title="example_report", author=c("It's me"))
optList <- makeOptionsList(includeFlag=TRUE, cacheFlag=TRUE)
mkdCodeChunkCommented(rd,
  comment="This is the comment of the following code chunk",
  code=c(quote(a <- 1), quote(b <- 2), quote(c <- a+b)),
  optionList=optList, sourceFilesList=NULL)
mkdCodeChunkCommented(rd,
  comment="This is the comment of the following code chunk",
  code="a <- 1\n b <- 2\n(c <- a+b)\n", optionList=optList,
  sourceFilesList=NULL)

## End(Not run)
```

mkdCodeChunkComplete *mkdCodeChunkComplete*

Description

it creates a complete code chunk.

Usage

```
mkdCodeChunkComplete(  
  object,  
  code,  
  optionList = getOptionsList(object),  
  sourceFilesList = NULL  
)
```

Arguments

| | |
|-----------------|--|
| object | an easyreporting class object |
| code | a string or an expression generated with quote containing a function call or the entire code chunk to trace. |
| optionList | a list of options. |
| sourceFilesList | a list of files to source. |

Value

none

Examples

```
## Not run:  
rd <- easyreporting(filenamePath="./project_report",  
                    title="example_report", author=c("It's me"))  
mkdCodeChunkComplete(rd, code="a <- 1\n b <- 2\n c <- a+b\n print(c)")  
  
## End(Not run)
```

mkdCodeChunkComplete, easyreporting-method
mkdCodeChunkComplete

Description

it creates a complete code chunk.

Usage

```
## S4 method for signature 'easyreporting'
mkdCodeChunkComplete(
  object,
  code,
  optionList = getOptionsList(object),
  sourceFilesList = NULL
)
```

Arguments

`object` an easyreporting class object

`code` a string or an expression (or a list of expressions) generated with `quote` containing a function call or the entire code chunk to trace.

`optionList` a list of options.

`sourceFilesList` a list of files to source.

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
  title="example_report", author=c("It's me"))
mkdCodeChunkComplete(rd, code=c(quote(a <- 1), quote(b <- 2), quote(c<- a+b),
  quote(print(c))))
mkdCodeChunkComplete(rd, code="a <- 1\n b <- 2\n c <- a+b\n print(c)")

## End(Not run)
```

mkdCodeChunkEnd

mkdCodeChunkEnd

Description

it creates a code chunk end. Always use it after a `mkdCodeChunkSt()`

Usage

```
mkdCodeChunkEnd(object)
```

Arguments

`object` an easyreporting class object

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdCodeChunkSt(rd)
## just leaving empty
mkdCodeChunkEnd(rd)

## End(Not run)
```

mkdCodeChunkEnd,easyreporting-method
mkdCodeChunkEnd

Description

it creates a code chunk end. Always use it after a mkdCodeChunkSt()

Usage

```
## S4 method for signature 'easyreporting'
mkdCodeChunkEnd(object)
```

Arguments

object an easyreporting class object

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdCodeChunkSt(rd)
## just leaving empty
mkdCodeChunkEnd(rd)

## End(Not run)
```

| | |
|----------------|-----------------------|
| mkdCodeChunkSt | <i>mkdCodeChunkSt</i> |
|----------------|-----------------------|

Description

it creates a code chunk start. A list of options and files to source for the chunk can optionally be passed to the function.

Usage

```
mkdCodeChunkSt(  
  object,  
  optionList = getOptionsList(object),  
  sourceFilesList = NULL,  
  isComplete = FALSE  
)
```

Arguments

| | |
|-----------------|---|
| object | an easyreporting class object |
| optionList | a list of options |
| sourceFilesList | a list of files that can be sourced inside the code chunk. |
| isComplete | a flag determining if the chunk is already a complete chunk |

Value

none

Examples

```
## Not run:  
rd <- easyreporting(filenamePath="./project_report",  
                    title="example_report", author=c("It's me"))  
  
## no options  
mkdCodeChunkSt(rd)  
## just leaving empty  
mkdCodeChunkEnd(rd)  
  
## setting options  
optList <- makeOptionsList(includeFlag=TRUE)  
mkdCodeChunkSt(rd, optionList=optList)  
## just leaving empty  
mkdCodeChunkEnd(rd)  
  
## End(Not run)
```

```
mkdCodeChunkSt,easyreporting-method  
mkdCodeChunkSt
```

Description

it creates a code chunk start. A list of options and files to source for the chunk can optionally be passed to the function.

Usage

```
## S4 method for signature 'easyreporting'  
mkdCodeChunkSt(  
  object,  
  optionList = getOptionsList(object),  
  sourceFilesList = NULL,  
  isComplete = FALSE  
)
```

Arguments

| | |
|-----------------|---|
| object | an easyreporting class object |
| optionList | a list of options |
| sourceFilesList | a list of files that can be sourced inside the code chunk. |
| isComplete | a flag determining if the chunk is already a complete chunk |

Value

none

Examples

```
## Not run:  
rd <- easyreporting(filenamePath="./project_report",  
                    title="example_report", author=c("It's me"))  
  
## no options  
mkdCodeChunkSt(rd)  
## just leaving empty  
mkdCodeChunkEnd(rd)  
  
## setting options  
optList <- makeOptionsList(includeFlag=TRUE)  
mkdCodeChunkSt(rd, optionList=optList)  
## just leaving empty  
mkdCodeChunkEnd(rd)  
  
## End(Not run)
```

```
mkdCodeChunkTitledCommented
      mkdCodeChunkCommented
```

Description

it creates a complete code chunk, adding a natural language comment before of it.

Usage

```
mkdCodeChunkTitledCommented(
  object,
  title = NULL,
  level = 1,
  comment = NULL,
  code,
  optionList = getOptionsList(object),
  sourceFilesList = NULL
)
```

Arguments

| | |
|-----------------|---|
| object | an easyreporting class object |
| title | the title to assign to the code chunk section |
| level | the level of the title (default is 1) |
| comment | a string with the natural language comment for the chunk. |
| code | a string within the code. |
| optionList | a list of options (default is the class options). |
| sourceFilesList | a optional list of files to source inside the chunk. |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
optList <- makeOptionsList(includeFlag=TRUE, cacheFlag=TRUE)
mkdCodeChunkCommented(rd,
                      comment="This is the comment of the following code chunk",
                      code="a <- 1\n b <- 2\n (c <- a+b)\n", optionList=optList,
                      sourceFilesList=NULL)

## End(Not run)
```

mkdCodeChunkTitledCommented,easyreporting-method
mkdCodeChunkTitledCommented

Description

it creates a complete code chunk, adding a natural language comment before of it.

Usage

```
## S4 method for signature 'easyreporting'
mkdCodeChunkTitledCommented(
  object,
  title = NULL,
  level = 1,
  comment = NULL,
  code,
  optionList = getOptionsList(object),
  sourceFilesList = NULL
)
```

Arguments

| | |
|-----------------|---|
| object | an easyreporting class object |
| title | the title to assign to the code chunk section |
| level | the level of the title (default is 1) |
| comment | a string with the natural language comment for the chunk. |
| code | a string within the code. |
| optionList | a list of options (default is the class options). |
| sourceFilesList | a optional list of files to source inside the chunk. |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
  title="example_report", author=c("It's me"))
optList <- makeOptionsList(includeFlag=TRUE, cacheFlag=TRUE)
mkdCodeChunkTitledCommented(rd, title="Title Example", level=1,
  comment="This is the comment of the following code chunk",
  code="a <- 1\n b <- 2\n(c <- a+b)\n", optionList=optList,
  sourceFilesList=NULL)

## End(Not run)
```

| | |
|---------------|----------------------|
| mkdGeneralMsg | <i>mkdGeneralMsg</i> |
|---------------|----------------------|

Description

It appends a general message to the report, useful for describing a code chunk or a part of the report. Useful for adding natural language comments.

Usage

```
mkdGeneralMsg(object, message)
```

Arguments

| | |
|---------|-------------------------------------|
| object | an easyreporting class object |
| message | the message to append to the report |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdGeneralMsg(rd, message="Writing a paragraph to describe my code chunk")

## End(Not run)
```

| | |
|------------------------------------|----------------------|
| mkdGeneralMsg,easyreporting-method | <i>mkdGeneralMsg</i> |
|------------------------------------|----------------------|

Description

It appends a general message to the report. Useful for adding natural language comments.

Usage

```
## S4 method for signature 'easyreporting'
mkdGeneralMsg(object, message)
```

Arguments

| | |
|---------|-------------------------------------|
| object | an easyreporting class object |
| message | the message to append to the report |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdGeneralMsg(rd, "Writing a paragraph to describe my code chunk")

## End(Not run)
```

mkdGeneralTitledMsg *mkdGeneralTitledMsg*

Description

It appends a a titled section followed by a general message to the report. Useful for adding natural language comments.

Usage

```
mkdGeneralTitledMsg(object, title = NULL, level = 1, message)
```

Arguments

| | |
|---------|--|
| object | an easyreporting class object |
| title | the title of the report section. |
| level | the level (1 to 6) of the title (default is 1) |
| message | the message to append to the report |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdGeneralTitledMsg(rd, title="Generic SubTitle for this message", level=2,
                    message="Writing a paragraph to describe my code chunk")

## End(Not run)
```

```
mkdGeneralTitledMsg, easyreporting-method
      mkdGeneralTitledMsg
```

Description

It appends a a titled section followed by a general message to the report. Useful for adding natural language comments.

Usage

```
## S4 method for signature 'easyreporting'
mkdGeneralTitledMsg(object, title = NULL, level = 1, message)
```

Arguments

| | |
|---------|---|
| object | an easyreporting class object |
| title | the optional title to give to the message section |
| level | the level (1 to 6) of the title (default is 1) |
| message | the message to append to the report |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdGeneralTitledMsg(rd, title="Generic SubTitle for this message", level=2,
                    message="Writing a paragraph to describe my code chunk")

## End(Not run)
```

```
mkdSetGlobalOpts      mkdSetGlobalOpts
```

Description

mkdSetGlobalOpts

Usage

```
mkdSetGlobalOpts(object, optionList = list())
```

Arguments

| | |
|------------|-------------------------------|
| object | an easyreporting class object |
| optionList | a list of options |

Value

an easyreporting class object

mkdSetGlobalOpts, easyreporting-method
mkdSetGlobalOpts

Description

internal function for appending to the report the initial options setup

Usage

```
## S4 method for signature 'easyreporting'  
mkdSetGlobalOpts(object, optionList = list())
```

Arguments

object an easyreporting class object
optionList a list of options

Value

an easyreporting class object

mkdSourceFiles *mkdSourceFiles*

Description

includes a list of source files inside the rmarkdown

Usage

```
mkdSourceFiles(object, ...)
```

Arguments

object an easyreporting class object
... a list of files to source

Value

none

mkdSourceFiles, easyreporting-method
mkdSourceFiles

Description

includes a list of source files inside the rmarkdown

Usage

```
## S4 method for signature 'easyreporting'
mkdSourceFiles(object, ...)
```

Arguments

| | |
|--------|-------------------------------------|
| object | an easyreporting class object |
| ... | a list of files to source with path |

Value

none

mkdTitle *mkdTitle*

Description

Inserts an rmarkdown title inside the report, useful for create distinct sections inside the final respot.

Usage

```
mkdTitle(object, title, level = 1)
```

Arguments

| | |
|--------|---------------------------------------|
| object | an easyreporting class object |
| title | a string within the title. |
| level | a numeric from 1 to 6 (default is 1). |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))

mkdTitle(rd, "First Level Title")
mkdTitle(rd, "Sub-Title", level=2)

## End(Not run)
```

mkdTitle,easyreporting-method
mkdTitle

Description

Inserts an rmarkdown title inside the report.

Usage

```
## S4 method for signature 'easyreporting'
mkdTitle(object, title, level = 1)
```

Arguments

| | |
|--------|---------------------------------------|
| object | an easyreporting class object |
| title | a string within the title. |
| level | a numeric from 1 to 6 (default is 1). |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))

mkdTitle(rd, "First Level Title")
mkdTitle(rd, "Sub-Title", level=2)

## End(Not run)
```

`mkdVariableAssignment` *mkdVariableAssignment*

Description

it includes a variable assignment in the report. NB: a call to the "mkdCodeChunkSt" has to be done before using it.

Usage

```
mkdVariableAssignment(object, variable.name, variable.object.name, show)
```

Arguments

| | |
|-----------------------------------|--|
| <code>object</code> | an easyreporting class object |
| <code>variable.name</code> | a string indicating the name of the variable to store in the report. (This can be changed here, but further uses of the variable needs to take into account the variable name change). |
| <code>variable.object.name</code> | the name of the already existing variable. (This cannot be changed.) |
| <code>show</code> | a boolean indicating if to show the message before writing it into the rmarkdown file. |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
## leaving the default options to the code chunk
mkdCodeChunkSt(rd)
## adding a variable assignment
variable <- 1
mkdVariableAssignment(rd, "variable", "variable", show=TRUE)
mkdCodeChunkEnd(rd)

## End(Not run)
```

`mkdVariableAssignment, easyreporting-method`
mkdVariableAssignment

Description

it includes a variable assignment in the report. NB: a call to the "mkdCodeChunkSt" has to be done before using it.

Usage

```
## S4 method for signature 'easyreporting'
mkdVariableAssignment(
  object,
  variable.name,
  variable.object.name,
  show = FALSE
)
```

Arguments

| | |
|----------------------|--|
| object | an easyreporting class object |
| variable.name | a string indicating the name of the variable to store in the report. (This can be changed here, but further uses of the variable needs to take into account the variable name change). |
| variable.object.name | the name of the already existing variable. (This cannot be changed.) |
| show | a boolean indicating if to show the message before writing it into the rmarkdown file. |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
## leaving the default options to the code chunk
mkdCodeChunkSt(rd)
## adding a variable assignment
variable <- 1
mkdVariableAssignment(rd, "variable", "variable", show=TRUE)
mkdCodeChunkEnd(rd)

## End(Not run)
```

setBibliography

setBibliography

Description

add a bibfile name to the object that will be reflected into the report as a bibliography section

Usage

```
setBibliography(object, bibfile = NULL)
```

Arguments

object an easyreporting class object
bibfile a path string with the name of the bib file

Value

none

Examples

```
## Not run:  
TBD  
  
## End(Not run)
```

setBibliography,easyreporting-method
setBibliography

Description

add a bibfile name to the object that will be reflected into the report as a bibliography section

Usage

```
## S4 method for signature 'easyreporting'  
setBibliography(object, bibfile = NULL)
```

Arguments

object an easyreporting class object
bibfile a string with the name of the bib file

Value

none

Examples

```
## Not run:  
# TBD  
  
## End(Not run)
```

| | |
|----------------|-----------------------|
| setOptionsList | <i>setOptionsList</i> |
|----------------|-----------------------|

Description

set an optionList to the class, it automatically sets the options for the rmarkdown file. Are useful for the interpretation/execution of the code chunks.

Usage

```
setOptionsList(
  object,
  cacheFlag = TRUE,
  evalFlag = TRUE,
  echoFlag = TRUE,
  warningFlag = FALSE,
  showMessages = FALSE,
  includeFlag = TRUE,
  collapseFlag = FALSE,
  purlFlag = TRUE,
  errorFlag = TRUE,
  messageFlag = TRUE,
  highlightFlag = TRUE,
  promptFlag = FALSE,
  stripWhiteFlag = TRUE,
  tidyFlag = FALSE
)
```

Arguments

| | |
|---------------|---|
| object | an easyreporting class object |
| cacheFlag | boolean for caching chunk data (default TRUE) |
| evalFlag | boolean for evaluating the code chunk in the compiled version (default TRUE) |
| echoFlag | boolean for showing the code chunk (default TRUE) |
| warningFlag | boolean for showing the chunk warnings (default FALSE) |
| showMessages | boolean for showing the chunk warnings in compiled version (default FALSE) |
| includeFlag | boolean for including the code chunk in the compiled version (default TRUE) |
| collapseFlag | boolean for collapsing the code chunk in the compiled version (default FALSE), |
| purlFlag | boolean for extracting the code chunk as R code in a separate R file (default TRUE), |
| errorFlag | boolean for including the error generated by the code chunk in the compiled version (default TRUE), |
| messageFlag | boolean for including the code chunk messages in the compiled version (default TRUE), |
| highlightFlag | boolean for highlighting the code chunk in the compiled version (default TRUE), |
| promptFlag | boolean for including a ">" for the code chunk in the compiled version (default FALSE), |

`stripWhiteFlag` boolean for removing the white spaces at beginning/end of the code chunk in the compiled version (default TRUE),

`tidyFlag` boolean for creating a tidy code chunk in the compiled version (default FALSE).

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))

## setting default option
setOptionsList(rd)

## modifying only some options
rd <- setOptionsList(rd, warningFlag=TRUE,
                    showMessages=TRUE, includeFlag=TRUE)

## End(Not run)
```

setOptionsList,easyreporting-method
setOptionsList

Description

set an optionList to the class

Usage

```
## S4 method for signature 'easyreporting'
setOptionsList(
  object,
  cacheFlag = TRUE,
  evalFlag = TRUE,
  echoFlag = TRUE,
  warningFlag = FALSE,
  showMessages = FALSE,
  includeFlag = TRUE,
  collapseFlag = FALSE,
  purlFlag = TRUE,
  errorFlag = TRUE,
  messageFlag = TRUE,
  highlightFlag = TRUE,
  promptFlag = FALSE,
  stripWhiteFlag = TRUE,
  tidyFlag = FALSE
)
```


Arguments

| | |
|----------------|--|
| object | an easyreporting class object |
| cacheFlag | boolean for caching chunk data (default TRUE) |
| evalFlag | boolean for evaluating the code chunk in the compiled version (default TRUE) |
| echoFlag | boolean for showing the code chunk (default TRUE) |
| warningFlag | boolean for showing the chunk warnings (default FALSE) |
| showMessages | boolean for showing the chunk warnings in compiled version (default FALSE) |
| includeFlag | boolean for including the code chunk in the compiled version (default TRUE) |
| collapseFlag | boolean for collapsing the code chunk in the compiled version (default FALSE), |
| pur1Flag | boolean for extracting the code chunk as R code in a separate R file (default TRUE), |
| errorFlag | boolean for including the error generated by the code chunk in the compiled version (default TRUE), |
| messageFlag | boolean for including the code chunk messages in the compiled version (default TRUE), |
| highlightFlag | boolean for highlighting the code chunk in the compiled version (default TRUE), |
| promptFlag | boolean for including a ">" for the code chunk in the compiled version (default FALSE), |
| stripWhiteFlag | boolean for removing the white spaces at beginning/end of the code chunk in the compiled version (default TRUE), |
| tidyFlag | boolean for creating a tidy code chunk in the compiled version (default FALSE). |

Value

none

Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))

## setting default option
setOptionsList(rd)

## modifying only some options
rd <- setOptionsList(rd, warningFlag=TRUE,
                    showMessages=TRUE, includeFlag=TRUE)

## End(Not run)
```

Index

* internal

- initReportFilename, [10](#)
 - initReportFilename, easyreporting-method, [11](#)
 - mkdSetGlobalOpts, [24](#)
 - mkdSetGlobalOpts, easyreporting-method, [25](#)
 - mkdSourceFiles, [25](#)
 - mkdSourceFiles, easyreporting-method, [26](#)
 - setBibliography, easyreporting-method, [30](#)
- addResource, [2](#)
- addResource, easyreporting-method, [3](#)
- compile, [4](#)
- compile, easyreporting-method, [4](#)
- easyreporting, [5](#)
- easyreporting-class (easyreporting), [5](#)
- erGUIVolcano, [6](#)
- getBibliography, [6](#)
- getBibliography, easyreporting-method, [7](#)
- getOptionsList, [8](#)
- getOptionsList, easyreporting-method, [8](#)
- getReportFilename, [9](#)
- getReportFilename, easyreporting-method, [9](#)
- initReportFilename, [10](#)
- initReportFilename, easyreporting-method, [11](#)
- makeOptionsList, [12](#)
- mkdCodeChunkCommented, [13](#)
- mkdCodeChunkCommented, easyreporting-method, [14](#)
- mkdCodeChunkComplete, [15](#)
- mkdCodeChunkComplete, easyreporting-method, [15](#)
- mkdCodeChunkEnd, [16](#)
- mkdCodeChunkEnd, easyreporting-method, [17](#)
- mkdCodeChunkSt, [18](#)
- mkdCodeChunkSt, easyreporting-method, [19](#)
- mkdCodeChunkTitledCommented, [20](#)
- mkdCodeChunkTitledCommented, easyreporting-method, [21](#)
- mkdGeneralMsg, [22](#)
- mkdGeneralMsg, easyreporting-method, [22](#)
- mkdGeneralTitledMsg, [23](#)
- mkdGeneralTitledMsg, easyreporting-method, [24](#)
- mkdSetGlobalOpts, [24](#)
- mkdSetGlobalOpts, easyreporting-method, [25](#)
- mkdSourceFiles, [25](#)
- mkdSourceFiles, easyreporting-method, [26](#)
- mkdTitle, [26](#)
- mkdTitle, easyreporting-method, [27](#)
- mkdVariableAssignment, [28](#)
- mkdVariableAssignment, easyreporting-method, [28](#)
- person, [11](#)
- quote, [15](#), [16](#)
- setBibliography, [29](#)
- setBibliography, easyreporting-method, [30](#)
- setOptionsList, [31](#)
- setOptionsList, easyreporting-method, [32](#)