

Package ‘singscore’

December 31, 2024

Type Package

Title Rank-based single-sample gene set scoring method

Version 1.26.0

Description A simple single-sample gene signature scoring method that uses rank-based statistics to analyze the sample's gene expression profile. It scores the expression activities of gene sets at a single-sample level.

biocViews Software, GeneExpression, GeneSetEnrichment

Depends R (>= 3.6)

Imports methods, stats, graphics, ggplot2, grDevices, ggrepel, GSEABase, plotly, tidyr, plyr, magrittr, reshape, edgeR, RColorBrewer, Biobase, BiocParallel, SummarizedExperiment, matrixStats, reshape2, S4Vectors

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.2.0

Roxygen list(markdown = TRUE)

Collate 'singscore.R' 'rankAndScoring.R' 'permuTest.R'
'generatNullGeneric.R' 'multiScoreGeneric.R' 'plot.R'
'plotRankDensityGeneric.R' 'rankGenesGeneric.R'
'simpleScoreGeneric.R' 'stableGenes.R'

Suggests pkgdown, BiocStyle, hexbin, knitr, rmarkdown, testthat, covr

VignetteBuilder knitr

URL <https://davislaboratory.github.io/singscore>

BugReports <https://github.com/DavisLaboratory/singscore/issues>

git_url <https://git.bioconductor.org/packages/singscore>

git_branch RELEASE_3_20

git_last_commit f97f63c

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-12-30

Author Dharmesh D. Bhuva [aut] (<<https://orcid.org/0000-0002-6398-9157>>),
 Ruqian Lyu [aut, ctb],
 Momeneh Foroutan [aut, ctb] (<<https://orcid.org/0000-0002-1440-0457>>),
 Malvika Kharbanda [aut, cre] (<<https://orcid.org/0000-0001-9726-3023>>)

Maintainer Malvika Kharbanda <kharbanda.m@wehi.edu.au>

Contents

generateNull	2
generateNull_intl	5
getPvals	6
getStableGenes	7
multiScore	8
plotDispersion	10
plotNull	11
plotRankDensity	12
plotRankDensity_intl	13
plotScoreLandscape	14
projectScoreLandscape	15
rankGenes	16
scoredf_ccle_epi	18
scoredf_ccle_mes	18
scoredf_tcga_epi	19
scoredf_tcga_mes	20
simpleScore	20
singscore	23
tgfb_expr_10_se	23
tgfb_gs_dn	24
tgfb_gs_up	24
toy_expr_se	25
toy_gs_dn	26
toy_gs_up	26
Index	27

generateNull	<i>Permutation test for the derived scores of each sample</i>
--------------	---

Description

This function generates a number of random gene sets that have the same number of genes as the scored gene set. It scores each random gene set and returns a matrix of scores for all samples. The empirical scores are used to calculate the empirical p-values and plot the null distribution. The implementation uses `BiocParallel::bplapply()` for easy access to parallel backends. Note that one should pass the same values to the `upSet`, `downSet`, `centerScore` and `bidirectional` arguments as what they provide for the `simpleScore()` function to generate a proper null distribution.

Usage

```
generateNull(  
  upSet,  
  downSet = NULL,  
  rankData,  
  subSamples = NULL,  
  centerScore = TRUE,  
  knownDirection = TRUE,  
  B = 1000,  
  ncores = 1,  
  seed = sample.int(1e+06, 1),  
  useBPPARAM = NULL  
)  
  
## S4 method for signature 'vector,ANY'  
generateNull(  
  upSet,  
  downSet = NULL,  
  rankData,  
  subSamples = NULL,  
  centerScore = TRUE,  
  knownDirection = TRUE,  
  B = 1000,  
  ncores = 1,  
  seed = sample.int(1e+06, 1),  
  useBPPARAM = NULL  
)  
  
## S4 method for signature 'GeneSet,ANY'  
generateNull(  
  upSet,  
  downSet = NULL,  
  rankData,  
  subSamples = NULL,  
  centerScore = TRUE,  
  knownDirection = TRUE,  
  B = 1000,  
  ncores = 1,  
  seed = sample.int(1e+06, 1),  
  useBPPARAM = NULL  
)  
  
## S4 method for signature 'vector,vector'  
generateNull(  
  upSet,  
  downSet = NULL,  
  rankData,  
  subSamples = NULL,  
  centerScore = TRUE,  
  knownDirection = TRUE,  
  B = 1000,  
  ncores = 1,  
  seed = sample.int(1e+06, 1),  
  useBPPARAM = NULL  
)
```

```

    seed = sample.int(1e+06, 1),
    useBPPARAM = NULL
  )

## S4 method for signature 'GeneSet, GeneSet'
generateNull(
  upSet,
  downSet = NULL,
  rankData,
  subSamples = NULL,
  centerScore = TRUE,
  knownDirection = TRUE,
  B = 1000,
  ncores = 1,
  seed = sample.int(1e+06, 1),
  useBPPARAM = NULL
)

```

Arguments

upSet	A GeneSet object or character vector of gene IDs of up-regulated gene set or a gene set where the nature of genes is not known
downSet	A GeneSet object or character vector of gene IDs of down-regulated gene set or NULL where only a single gene set is provided
rankData	A matrix object, ranked gene expression matrix data generated using the rankGenes() function (make sure this matrix is not modified, see details)
subSamples	A vector of sample labels/indices that will be used to subset the rankData matrix. All samples will be scored if not provided
centerScore	A Boolean, specifying whether scores should be centered around 0, default as TRUE. Note: scores never centered if knownDirection = FALSE
knownDirection	A boolean, determining whether the gene set should be considered to be directional or not. A gene set is directional if the type of genes in it are known i.e. up- or down-regulated. This should be set to TRUE if the gene set is composed of both up- AND down-regulated genes. Defaults to TRUE. This parameter becomes irrelevant when both upSet(Colc) and downSet(Colc) are provided.
B	integer, the number of permutation repeats or the number of random gene sets to be generated, default as 1000
ncores	integer, the number of CPU cores the function can use
seed	integer, set the seed for randomisation
useBPPARAM	the backend the function uses, if NULL is provided, the function uses the default parallel backend which is the first on the list returned by <code>BiocParallel::registered()</code> i.e. <code>BiocParallel::registered()[[1]]</code> for your machine. It can be changed explicitly by passing a BPPARAM

Value

A matrix of empirical scores for all samples

Author(s)

Ruqian Lyu

See Also

[Post about BiocParallel](#) `browseVignettes("BiocParallel")`

Examples

```
ranked <- rankGenes(toy_expr_se)
scoredf <- simpleScore(ranked, upSet = toy_gs_up, downSet = toy_gs_dn)

# find out what backends can be registered on your machine
BiocParallel::registered()
# the first one is the default backend
# ncores = ncores <- parallel::detectCores() - 2
permuteResult = generateNull(upSet = toy_gs_up, downSet = toy_gs_dn, ranked,
centerScore = TRUE, B = 10, seed = 1, ncores = 1 )
```

generateNull_intl *Permutation test for the derived scores of each sample*

Description

This function generates a number of random gene sets that have the same number of genes as the scored gene set. It scores each random gene set and returns a matrix of scores for all samples. The empirical scores are used to calculate the empirical p-values and plot the null distribution. The implementation uses `BiocParallel::bplapply()` for easy access to parallel backends. Note that one should pass the same values to the `upSet`, `downSet`, `centerScore` and `knownDirection` arguments as what they provide for the `simpleScore()` function to generate a proper null distribution.

Usage

```
generateNull_intl(
  upSet,
  downSet = NULL,
  rankData,
  subSamples = NULL,
  centerScore = TRUE,
  knownDirection = TRUE,
  B = 1000,
  ncores = 1,
  seed = sample.int(1e+06, 1),
  useBPPARAM = NULL
)
```

Arguments

<code>downSet</code>	A <code>GeneSet</code> object, down regulated gene set
<code>rankData</code>	matrix, outcome of function rankGenes()
<code>centerScore</code>	A Boolean, specifying whether scores should be centered around 0, default as TRUE

knownDirection	A boolean flag, it determines whether the scoring method should derive the scores in a directional manner when the gene signature only contains one set of gene set (passing the gene set via upSet). It is default as TRUE but one can set the argument to be FALSE to derive the score for a single gene set in a unidirectional way. This parameter becomes irrelevant when both upSet and downSet are provided.
B	integer, the number of permutation repeats or the number of random gene sets to be generated, default as 1,000
ncores	integer, the number of CPU cores the function can use
seed	integer, set the seed for randomisation
useBPPARAM	the backend the function uses, if NULL is provided, the function uses the default parallel backend which is the first on the list returned by <code>BiocParallel::registered()</code> i.e <code>BiocParallel::registered()[[1]]</code> for your machine. It can be changed explicitly by passing a BPPARAM

Value

A matrix of empirical scores for all samples

Author(s)

Ruqian Lyu

See Also

[Post about BiocParallel](#) `browseVignettes("BiocParallel")`

getPvals

Estimate the empirical p-values

Description

With null distributions estimated using the `generateNull()` function, p-values are estimated using a one-tailed test. A minimum p-value of $1/B$ can be achieved with B permutations.

Usage

```
getPvals(permuteResult, scoredf, subSamples = NULL)
```

Arguments

permuteResult	A matrix, null distributions for each sample generated using the <code>generateNull()</code> function
scoredf	A dataframe, the scored results of samples under test generated using the <code>simpleScore()</code> function
subSamples	A vector of sample labels/indices that will be used to subset the score matrix. All samples will be scored if not provided

Value

Estimated p-values for enrichment of the signature in each sample. A p-value of $1/B$ indicates that the estimated p-value is less than or equal to $1/B$.

Examples

```
ranked <- rankGenes(toy_expr_se)
scoredf <- simpleScore(ranked, upSet = toy_gs_up, downSet = toy_gs_dn)
# find out what backends can be registered on your machine
BiocParallel::registered()
# the first one is the default backend, and it can be changed explicitly.
# See vignette for more details
permuteResult = generateNull(upSet = toy_gs_up, downSet = toy_gs_dn, ranked,
B =10, seed = 1, useBPPARAM = NULL)

# call the permutation function to generate the empirical scores
# for B times.
pvals <- getPvals(permuteResult,scoredf)
```

`getStableGenes`*Get a list of stably expressed genes*

Description

Get a list of genes that are stably expressed in cancer and normal solid tissue.

Usage

```
getStableGenes(
  n_stable,
  type = c("carcinoma", "blood", "protein"),
  id = c("geneid", "ensembl")
)
```

Arguments

<code>n_stable</code>	numeric, number of stable genes to retrieve
<code>type</code>	character, type of stable genes requested, stable genes in "carcinoma" or stable genes in "blood"
<code>id</code>	character, gene identifier required. This can be either "geneid" for symbols or "ensembl" ensembl id)

Value

a character vector with gene IDs sorted by their expected expression levels in the requested tissue

Examples

```
getStableGenes(5)
getStableGenes(5, id = 'ensembl')
getStableGenes(5, type = 'blood')
```

multiScore

single-sample gene-set scoring method for multiple signatures

Description

This function computes 'singscores' using a ranked gene expression matrix obtained from the [rankGenes\(\)](#) function and a `GeneSetCollection` object or a list of `GeneSet` objects. It returns a list of two matrices containing the scores and dispersions. This function should be used when scoring needs to be performed for multiple signatures. It is faster than applying [simpleScore\(\)](#) across the different signatures independently.

Usage

```
multiScore(
  rankData,
  upSetColc,
  downSetColc,
  subSamples = NULL,
  centerScore = TRUE,
  dispersionFun = mad,
  knownDirection = TRUE
)

## S4 method for signature 'matrix, GeneSetCollection, missing'
multiScore(
  rankData,
  upSetColc,
  downSetColc,
  subSamples = NULL,
  centerScore = TRUE,
  dispersionFun = mad,
  knownDirection = TRUE
)

## S4 method for signature 'matrix, GeneSetCollection, GeneSetCollection'
multiScore(
  rankData,
  upSetColc,
  downSetColc,
  subSamples = NULL,
  centerScore = TRUE,
  dispersionFun = mad,
  knownDirection = TRUE
)

## S4 method for signature 'matrix, list, missing'
multiScore(
  rankData,
  upSetColc,
  downSetColc,
  subSamples = NULL,
```



```

    centerScore = TRUE,
    dispersionFun = mad,
    knownDirection = TRUE
  )

## S4 method for signature 'matrix,list,list'
multiScore(
  rankData,
  upSetColc,
  downSetColc,
  subSamples = NULL,
  centerScore = TRUE,
  dispersionFun = mad,
  knownDirection = TRUE
)

```

Arguments

rankData	A matrix object, ranked gene expression matrix data generated using the rankGenes() function (make sure this matrix is not modified, see details)
upSetColc	A GeneSetCollection object, a list of GeneSet objects, or a list of character vectors of up-regulated (or mixed, see simpleScore) gene sets.
downSetColc	A GeneSetCollection object, a list of GeneSet objects, or a list of character vectors of down-regulated gene sets. NULL otherwise. Names of gene sets within this collection/list should be the same as those of the upSetColc
subSamples	A vector of sample labels/indices that will be used to subset the rankData matrix. All samples will be scored if not provided
centerScore	A Boolean, specifying whether scores should be centered around 0, default as TRUE. Note: scores never centered if knownDirection = FALSE
dispersionFun	A function, dispersion function with default being mad
knownDirection	A boolean, determining whether the gene set should be considered to be directional or not. A gene set is directional if the type of genes in it are known i.e. up- or down-regulated. This should be set to TRUE if the gene set is composed of both up- AND down-regulated genes. Defaults to TRUE. This parameter becomes irrelevant when both upSet(Colc) and downSet(Colc) are provided.

Value

A list of two matrices containing the scores and dispersions

See Also

[rank "GeneSet"](#)

Examples

```

ranked <- rankGenes(toy_expr_se)
GSEABase::setName(toy_gs_up) = "toy_gs_up"
GSEABase::setName(toy_gs_dn) = "toy_gs_dn"
gslist <- list(toy_gs_up, toy_gs_dn)

gscolc <- GSEABase::GeneSetCollection(gslist)
scoredf <- multiScore(ranked, upSetColc = gscolc)

```

plotDispersion *Plot the score v.s. dispersion for all samples*

Description

This function takes the output from the `simpleScore()` function and generates scatter plots of score vs. dispersion for the total score, the up score and the down score of samples. If you wish to use the plotting function but with some customized inputs (instead of outputs from `simpleScore` function), you need to make sure the formats are the same. To be specific, you need to have columns names "TotalScore" "TotalDispersion" "UpScore" "UpDispersion" "DownScore" "DownDispersion" and rows names as samples.

Usage

```
plotDispersion(  
  scoredf,  
  annot = NULL,  
  annot_name = "",  
  sampleLabels = NULL,  
  alpha = 1,  
  size = 1,  
  textSize = 1.2,  
  isInteractive = FALSE  
)
```

Arguments

<code>scoredf</code>	data.frame, generated using the <code>simpleScore()</code> function
<code>annot</code>	any numeric, character or factor annotation provided by the user that needs to be plot. Alternatively, this can be a character specifying the column of <code>scoredf</code> holding the annotation. Annotations must be ordered in the same way as the scores
<code>annot_name</code>	character, legend title for the annotation
<code>sampleLabels</code>	vector of character, sample names to display, ordered in the same way as samples are ordered in the 'scoredf' data.frame and with labels for all samples. Samples whose labels should not be displayed should be left as empty strings or NAs. Default as NULL which means the projected points are not labelled.
<code>alpha</code>	numeric, set the transparency of points
<code>size</code>	numeric, set the size of each point
<code>textSize</code>	numeric, relative text sizes for title, labels, and axis values
<code>isInteractive</code>	Boolean, determine whether the plot is interactive

Value

A ggplot object

Examples

```
ranked <- rankGenes(toy_expr_se)
scoredf <- simpleScore(ranked, upSet = toy_gs_up, downSet = toy_gs_dn)
plotDispersion(scoredf)
plotDispersion(scoredf, isInteractive = TRUE)
```

plotNull	<i>Plot the empirically estimated null distribution and associated p-values</i>
----------	---

Description

This function takes the results from function [generateNull\(\)](#) and plots the density curves of permuted scores for the provided samples via `sampleNames` parameter. It can plot null distribution(s) for a single sample or multiple samples.

Usage

```
plotNull(
  permuteResult,
  scoredf,
  pvals,
  sampleNames = NULL,
  cutoff = 0.01,
  textSize = 2,
  labelSize = 5
)
```

Arguments

<code>permuteResult</code>	A matrix, null distributions for each sample generated using the generateNull() function
<code>scoredf</code>	A dataframe, singscores generated using the simpleScore() function
<code>pvals</code>	A vector, estimated p-values using the getPvals() function <code>permuteResult</code> , <code>scoredf</code> and <code>pvals</code> are the results for the same samples.
<code>sampleNames</code>	A character vector, sample IDs for which null distributions will be plotted
<code>cutoff</code>	numeric, the cutoff value for determining significance
<code>textSize</code>	numeric, size of axes labels, axes values and title
<code>labelSize</code>	numeric, size of label texts

Value

a ggplot object

Author(s)

Ruqian Lyu

Examples

```

ranked <- rankGenes(toy_expr_se)
scoredf <- simpleScore(ranked, upSet = toy_gs_up, downSet = toy_gs_dn)
# find out what backends can be registered on your machine
BiocParallel::registered()
# the first one is the default backend, and it can be changed explicitly.
permuteResult = generateNull(upSet = toy_gs_up, downSet = toy_gs_dn, ranked,
B =10, seed = 1,useBPPARAM = NULL)
# call the permutation function to generate the empirical scores
#for B times.
pvals <- getPvals(permuteResult,scoredf)
# plot for all samples
plotNull(permuteResult,scoredf,pvals,sampleNames = names(pvals))
#plot for the first sample
plotNull(permuteResult,scoredf,pvals,sampleNames = names(pvals)[1])

```

plotRankDensity

Plot the densities of ranks for one sample

Description

This function takes a single-column data frame, which is a single-column subset of the ranked matrix data generated using `rankGenes()` function, and the gene sets of interest as inputs. It plots the density of ranks for genes in the gene set and overlays a barcode plot of these ranks. Ranks are normalized by dividing them by the maximum rank. Densities are estimated using KDE.

Usage

```

plotRankDensity(
  rankData,
  upSet,
  downSet = NULL,
  isInteractive = FALSE,
  textSize = 1.5
)

## S4 method for signature 'ANY,vector,missing'
plotRankDensity(
  rankData,
  upSet,
  downSet = NULL,
  isInteractive = FALSE,
  textSize = 1.5
)

## S4 method for signature 'ANY,GeneSet,missing'
plotRankDensity(
  rankData,
  upSet,
  downSet = NULL,
  isInteractive = FALSE,
  textSize = 1.5
)

```

```

)

## S4 method for signature 'ANY,vector,vector'
plotRankDensity(
  rankData,
  upSet,
  downSet = NULL,
  isInteractive = FALSE,
  textSize = 1.5
)

## S4 method for signature 'ANY,GeneSet,GeneSet'
plotRankDensity(
  rankData,
  upSet,
  downSet = NULL,
  isInteractive = FALSE,
  textSize = 1.5
)

```

Arguments

rankData	one column of the ranked gene expression matrix obtained from the rankGenes() function, use drop = FALSE when subsetting the ranked gene expression matrix, see examples.
upSet	GeneSet object or a vector of gene Ids, up-regulated gene set
downSet	GeneSet object or a vector of gene Ids, down-regulated gene set
isInteractive	Boolean, determine whether the returned plot is interactive
textSize	numeric, set the size of text on the plot

Value

A ggplot object (or a plotly object) with a rank density plot overlaid with a barcode plot

Examples

```

ranked <- rankGenes(toy_expr_se)
plotRankDensity(ranked[,2,drop = FALSE], upSet = toy_gs_up)

```

plotRankDensity_intl *Plot the densities of ranks for one sample*

Description

This function takes a single column data frame, which is a subset of the ranked data obtained from [rankGenes\(\)](#) function and gene sets, and it returns plots visualising the density and the rugs of the ranks.

Usage

```
plotRankDensity_intl(
  rankData,
  upSet,
  downSet = NULL,
  isInteractive = FALSE,
  textSize = 1.2
)
```

Arguments

rankData	one column of the ranked gene expression matrix obtained from the rankGenes() function, use drop = FALSE when subsetting the ranked gene expression matrix, see examples.
upSet	GeneSet object, up regulated gene set
downSet	GeneSet object, down regulated gene set
isInteractive	Boolean, determin whether the returned plot is interactive
textSize	numeric, set the size of text on the plot

Value

A ggplot object (optionally interactive) demonstrating the rank density along with rug plot

See Also

["GeneSet"](#)

plotScoreLandscape *Plot landscape of two gene signatures scores*

Description

This function takes two data frames which are outputs from the simpleScore() function and plots the relationship between the two gene set scores for samples in the gene expression matrix. Scoredf1 and Scoredf2 are two scoring results of the same set of samples against two different gene signatures. If you wish to use the plotting function but with some customized inputs (instead of outputs from the simpleScore function), you need to make sure the formats are the same To be specific, you need to have column names "TotalScore" "TotalDispersion" "UpScore" "UpDispersion" "DownScore" "DownDispersion" and rows names as samples.

Usage

```
plotScoreLandscape(
  scoredf1,
  scoredf2,
  scorenames = c(),
  textSize = 1.2,
  isInteractive = FALSE,
  hexMin = 100
)
```

Arguments

scoredf1	data.frame, result of the simpleScore() function which scores the gene expression matrix against a gene set of interest
scoredf2	data.frame, result of the simpleScore() function which scores the gene expression matrix against another gene set of interest
scorenames	character vector of length 2, names for the two scored gene set/signatures stored in scoredf1 and scoredf2
textSize	numeric, set the text size for the plot, default as 1.5
isInteractive	boolean, whether the plot is interactive default as FALSE
hexMin	integer, the threshold which decides whether hex bin plot or scatter plot is displayed, default as 100

Value

A ggplot object, a scatter plot, demonstrating the relationship between scores from two signatures on the same set of samples.

Examples

```
ranked <- rankGenes(toy_expr_se)
scoredf <- simpleScore(ranked, upSet = toy_gs_up, downSet = toy_gs_dn)
scoredf2 <- simpleScore(ranked, upSet = toy_gs_up)
plotScoreLandscape(scoredf, scoredf2)
```

projectScoreLandscape *Project data on the landscape plot obtained from*
plotScoreLandscape()

Description

This function takes the output (ggplot object) of the function plotScoreLandscape() and a new dataset. It projects the new data points onto the landscape plot and returns a new ggplot object with projected data points.

Usage

```
projectScoreLandscape(  
  plotObj = NULL,  
  scoredf1,  
  scoredf2,  
  annot = NULL,  
  annot_name = NULL,  
  subSamples = NULL,  
  sampleLabels = NULL,  
  isInteractive = FALSE  
)
```

Arguments

plotObj	a ggplot object, resulted from <code>plotScoreLandscape()</code>
scoredf1	data.frame, result of the <code>simpleScore()</code> function which scores the gene expression matrix against a gene set of interest
scoredf2	data.frame, result of the <code>simpleScore()</code> function which scores the gene expression matrix against another gene set of interest. Scores in <code>scoredf1</code> and <code>scoredf2</code> consist of the new data points that will be projected on the <code>plotObj</code> landscape plot.
annot	any numeric, character or factor annotation provided by the user that needs to be plot. Alternatively, this can be a character specifying the column of <code>scoredf1</code> holding the annotation. Annotations must be ordered in the same way as the scores
annot_name	character, legend title for the annotation
subSamples	vector of character or indices for subsetting the <code>scoredfs</code> , default as <code>NULL</code> and all samples in <code>scoredfs</code> will be plotted. The subsetted samples are projected onto the landscape plot of <code>plotObj</code> .
sampleLabels	vector of character, sample names to display, ordered in the same way as samples are ordered in the 'scoredfs' data.frames and with labels for all samples. Samples whose labels should not be displayed should be left as empty strings or NAs. Default as <code>NULL</code> which means the projected points are not labelled.
isInteractive	boolean, whether the plot is interactive default as <code>FALSE</code>

Value

New data points on the already plotted ggplot object from `plotScoreLandscape()`

See Also

`plotScoreLandscape()` @examples `ranked <- rankGenes(toy_expr_se) scoredf1 <- simpleScore(ranked, upSet = toy_gs_up, downSet = toy_gs_dn) scoredf2 <- simpleScore(ranked, upSet = toy_gs_up) psl <- plotScoreLandscape(scoredf1, scoredf2) projectScoreLandscape(psl,scoredf1, scoredf2)`

rankGenes

Rank genes by the gene expression intensities

Description

The `rankGenes` function is a generic function that can deal with multiple types of inputs. Given a matrix of gene expression that has samples in columns, genes in rows, and values being gene expression intensity, `rankGenes` ranks gene expression intensities in each sample.

It can also work with S4 objects that have gene expression matrix as a component (i.e `ExpressionSet`, `DGEList`, `SummarizedExperiment`). It calls the `rank` function in the base package which ranks the gene expression matrix by its absolute expression level. If the input is S4 object of `DGEList`, `ExpressionSet`, or `SummarizedExperiment`, it will extract the gene expression matrix from the object and rank the genes. The default 'tiesMethod' is set to 'min'.

Usage

```
rankGenes(expreMatrix, tiesMethod = "min", stableGenes = NULL)

## S4 method for signature 'matrix'
rankGenes(expreMatrix, tiesMethod = "min", stableGenes = NULL)

## S4 method for signature 'data.frame'
rankGenes(expreMatrix, tiesMethod = "min", stableGenes = NULL)

## S4 method for signature 'DGEList'
rankGenes(expreMatrix, tiesMethod = "min", stableGenes = NULL)

## S4 method for signature 'ExpressionSet'
rankGenes(expreMatrix, tiesMethod = "min", stableGenes = NULL)

## S4 method for signature 'SummarizedExperiment'
rankGenes(expreMatrix, tiesMethod = "min", stableGenes = NULL)
```

Arguments

expreMatrix	matrix, data.frame, ExpressionSet, DGEList or SummarizedExperiment storing gene expression measurements
tiesMethod	character, indicating what method to use when dealing with ties
stableGenes	character, containing a list of stable genes to be used to rank genes using expression of stable genes. This is required when using the stable genes dependent version of singscore (see details in simpleScore). Stable genes for solid cancers (carcinomas) and blood transcriptomes can be obtained using the getStableGenes function

Value

The ranked gene expression matrix that has samples in columns and genes in rows. Unit normalised ranks are returned if data is ranked using stable genes

See Also

[getStableGenes](#), [simpleScore](#), [rank](#), ["ExpressionSet"](#), ["SummarizedExperiment"](#), ["DGEList"](#)

Examples

```
rankGenes(toy_expr_se) # toy_expr_se is a gene expression dataset

# ExpressionSet object
emat <- SummarizedExperiment::assay(toy_expr_se)
e <- Biobase::ExpressionSet(assayData = as.matrix(emat))
rankGenes(e)

#scoring using the stable version of singscore
rankGenes(e, stableGenes = c('2', '20', '25'))

## Not run:
#for real cancer or blood datasets, use getStableGenes()
rankGenes(cancer_expr, stableGenes = getStableGenes(5))
```

```
rankGenes(blood_expr, stableGenes = getStableGenes(5, type = 'blood'))  
## End(Not run)
```

scoredf_ccle_epi	<i>Pre-computed scores of the CCLE dataset against an epithelial gene signature</i>
------------------	---

Description

This data.frame stores pre-computed scores of the CCLE dataset [Barretina et al](#) calculated using the `simpleScore()` function against the epithelial gene signature from [Tan, Tuan Zea et al](#). The data.frame has scores for 55 samples. Please refer to the vignettes for instructions on how to obtain the full datasets.

Usage

```
scoredf_ccle_epi
```

Format

An object of class `data.frame` with 55 rows and 2 columns.

References

Barretina, Jordi, Giordano Caponigro, Nicolas Stransky, Kavitha Venkatesan, Adam A Margolin, Sungjoon Kim, Christopher J Wilson, et al. 2012. “The Cancer Cell Line Encyclopedia Enables Predictive Modelling of Anticancer Drug Sensitivity.” *Nature* 483 (7391): 603–7.

Tan, Tuan Zea, Qing Hao Miow, Yoshio Miki, Tetsuo Noda, Seiichi Mori, Ruby Yun-Ju Huang, and Jean Paul Thiery. 2014–10AD. “Epithelial-Mesenchymal Transition Spectrum Quantification and Its Efficacy in Deciphering Survival and Drug Responses of Cancer Patients.” *EMBO Molecular Medicine* 6 (10). Oxford, UK: BlackWell Publishing Ltd: 1279–93. doi:10.15252/emmm.201404208.

See Also

[scoredf_ccle_mes](#)

scoredf_ccle_mes	<i>Pre-computed scores of the CCLE dataset against a mesenchymal gene signature</i>
------------------	---

Description

This data.frame stores pre-computed scores of the CCLE dataset [Barretina et al](#) calculated using the `simpleScore()` function against the mesenchymal gene signature from [Tan, Tuan Zea et al](#). The data.frame has scores for 55 samples. Please refer to the vignettes for instructions on how to obtain the full datasets.

Usage

```
scoredf_ccle_mes
```

Format

An object of class `data.frame` with 55 rows and 2 columns.

References

Barretina, Jordi, Giordano Caponigro, Nicolas Stransky, Kavitha Venkatesan, Adam A Margolin, Sungjoon Kim, Christopher J Wilson, et al. 2012. “The Cancer Cell Line Encyclopedia Enables Predictive Modelling of Anticancer Drug Sensitivity.” *Nature* 483 (7391): 603–7.

Tan, Tuan Zea, Qing Hao Miow, Yoshio Miki, Tetsuo Noda, Seiichi Mori, Ruby Yun-Ju Huang, and Jean Paul Thiery. 2014–10AD. “Epithelial-Mesenchymal Transition Spectrum Quantification and Its Efficacy in Deciphering Survival and Drug Responses of Cancer Patients.” *EMBO Molecular Medicine* 6 (10). Oxford, UK: BlackWell Publishing Ltd: 1279–93 doi:10.15252/emmm.201404208.

See Also

[scoredf_ccle_epi](#)

scoredf_tcga_epi

Pre-computed scores of the TCGA breast cancer gene expression matrix against an epithelial signature

Description

This `data.frame` stores pre-computed scores of the **TCGA** dataset calculated using the `simpleScore()` function against the epithelial gene signature from **Tan, Tuan Zea et al.** Please refer to the vignettes for instructions on how to obtain the full datasets.

Usage

```
scoredf_tcga_epi
```

Format

An object of class `data.frame` with 1119 rows and 2 columns.

References

Tan, Tuan Zea, Qing Hao Miow, Yoshio Miki, Tetsuo Noda, Seiichi Mori, Ruby Yun-Ju Huang, and Jean Paul Thiery. 2014–10AD. “Epithelial-Mesenchymal Transition Spectrum Quantification and Its Efficacy in Deciphering Survival and Drug Responses of Cancer Patients.” *EMBO Molecular Medicine* 6 (10). Oxford, UK: BlackWell Publishing Ltd: 1279–93 doi:10.15252/emmm.201404208.

See Also

[scoredf_tcga_mes](#)

scoredf_tcga_mes	<i>Pre-computed scores of the TCGA breast cancer gene expression matrix against a mesenchymal signature</i>
------------------	---

Description

This data.frame stores pre-computed scores of the **TCGA** dataset calculated using the `simpleScore()` function against the mesenchymal gene signature from **Tan, Tuan Zea et al.** Please refer to the vignettes for instructions on how to obtain the full datasets.

Usage

```
scoredf_tcga_mes
```

Format

An object of class `data.frame` with 1119 rows and 2 columns.

References

Tan, Tuan Zea, Qing Hao Miow, Yoshio Miki, Tetsuo Noda, Seiichi Mori, Ruby Yun-Ju Huang, and Jean Paul Thiery. 2014–10AD. “Epithelial-Mesenchymal Transition Spectrum Quantification and Its Efficacy in Deciphering Survival and Drug Responses of Cancer Patients.” *EMBO Molecular Medicine* 6 (10). Oxford, UK: BlackWell Publishing Ltd: 1279–93 doi:10.15252/emmm.201404208.

See Also

[scoredf_tcga_epi](#)

simpleScore	<i>single-sample gene-set scoring method</i>
-------------	--

Description

This function computes ‘singscores’ using an **unmodified** ranked gene expression matrix obtained from the `rankGenes()` function and a gene set or a pair of up-regulated and down-regulated gene sets. It returns a data.frame of scores and dispersions for each sample. The gene sets can be in vector format or as GeneSet objects (from GSEABase packages). If samples need to be scored against a single gene set, the `upSet` argument should be used to pass the gene set while the `downSet` argument is set to `NULL`. This setting is ideal for gene sets representing gene ontologies where the nature of the genes is unknown (up- or down-regulated).

Usage

```
simpleScore(
  rankData,
  upSet,
  downSet = NULL,
  subSamples = NULL,
  centerScore = TRUE,
```

```
    dispersionFun = mad,
    knownDirection = TRUE
  )

## S4 method for signature 'matrix,vector,missing'
simpleScore(
  rankData,
  upSet,
  downSet = NULL,
  subSamples = NULL,
  centerScore = TRUE,
  dispersionFun = mad,
  knownDirection = TRUE
)

## S4 method for signature 'matrix,GeneSet,missing'
simpleScore(
  rankData,
  upSet,
  downSet = NULL,
  subSamples = NULL,
  centerScore = TRUE,
  dispersionFun = mad,
  knownDirection = TRUE
)

## S4 method for signature 'matrix,vector,vector'
simpleScore(
  rankData,
  upSet,
  downSet = NULL,
  subSamples = NULL,
  centerScore = TRUE,
  dispersionFun = mad,
  knownDirection = TRUE
)

## S4 method for signature 'matrix,GeneSet,GeneSet'
simpleScore(
  rankData,
  upSet,
  downSet = NULL,
  subSamples = NULL,
  centerScore = TRUE,
  dispersionFun = mad,
  knownDirection = TRUE
)
```

Arguments

rankData A matrix object, ranked gene expression matrix data generated using the [rankGenes\(\)](#) function (make sure this matrix is not modified, see details)

upSet	A GeneSet object or character vector of gene IDs of up-regulated gene set or a gene set where the nature of genes is not known
downSet	A GeneSet object or character vector of gene IDs of down-regulated gene set or NULL where only a single gene set is provided
subSamples	A vector of sample labels/indices that will be used to subset the rankData matrix. All samples will be scored if not provided
centerScore	A Boolean, specifying whether scores should be centered around 0, default as TRUE. Note: scores never centered if knownDirection = FALSE
dispersionFun	A function, dispersion function with default being mad
knownDirection	A boolean, determining whether the gene set should be considered to be directional or not. A gene set is directional if the type of genes in it are known i.e. up- or down-regulated. This should be set to TRUE if the gene set is composed of both up- AND down-regulated genes. Defaults to TRUE. This parameter becomes irrelevant when both upSet(Colc) and downSet(Colc) are provided.

Details

Signature scores can be computed using transcriptome-wide measurements or using a smaller set of measurements. If ranks are computed using the default invocation of rankGenes, the former method is applied where the rank of each gene in the signature is computed relative to all other genes in the dataset. Accuracy of this approximation of the relative expression of a gene will be improved if all or most transcripts are measured in the experiment. This was the approach proposed in the original manuscript of singscore (Foroutan M, Bhuvu DD, et al 2018).

If instead a selected panel of genes is measured (such as from nanostring or RT-qPCR), a different rank approximation methods using a small set of stable genes can be used. This approach only requires measurements of genes in the signature and a small set of stable genes. This approach of scoring can be invoked by producing a rank matrix by passing in the stableGenes argument of rankGenes. Stable genes in solid cancers and in blood can be retrieved using getStableGenes. Upon providing a set of stable genes, rankGenes automatically ranks all genes relative to these stable genes. When simpleScore is provided with a rank matrix constructed using stable genes, it automatically computes scores using a new approach. Details of the set of stable genes, the new rank estimation approach and the new scoring approach will soon be published (manuscript in preparation).

Value

A data.frame consists of singscores and dispersions for all samples

References

Foroutan, M., Bhuvu, D. D., Lyu, R., Horan, K., Cursons, J., & Davis, M. J. (2018). Single sample scoring of molecular phenotypes. BMC bioinformatics, 19(1), 1-10.

See Also

[rankGenes](#), [getStableGenes](#), [rank](#), "GeneSet"

Examples

```
ranked <- rankGenes(toy_expr_se)
scoredf <- simpleScore(ranked, upSet = toy_gs_up, downSet = toy_gs_dn)
# toy_gs_up is a GeneSet object, alternatively a vector of gene ids may also
# be supplied.
```

singscore	<i>singscore: A package for deriving gene-set scores at a single sample level</i>
-----------	---

Description

The package provides functions for calculating gene-set enrichment scores at a single-sample level using gene expression data. It includes functions to perform hypothesis testing and provides visualisations to enable diagnosis of scores and gene sets along with visualisations to enable exploration of results.

tgfb_expr_10_se	<i>An example gene expression dataset</i>
-----------------	---

Description

A microarray gene expression dataset that was originally obtained from the integrated TGFb-EMT data published by (Foroutan et al, 2017). (ComBat corrected values). `tgfb_expr_10` is a subset of the integrated TGFb-EMT data consisting of 10 samples (4 TGFb treated and 6 controls) each with expression values for 11900 genes.

Usage

```
tgfb_expr_10_se
```

Format

A SummarizedExperiment object

Source

[Foroutan et al,2017](#)

References

Foroutan, Momeneh, Joseph Cursons, Soroor Hedyeh-Zadeh, Erik W Thompson, and Melissa J Davis. 2017. "A Transcriptional Program for Detecting Tgfbeta-Induced Emt in Cancer." *Molecular Cancer Research*. American Association for Cancer Research. doi:10.1158/1541-7786.MCR-16-0313.

tgfb_gs_dn	<i>Gene set of down-regulated genes for the TGFb-induced EMT gene signature</i>
------------	---

Description

A GeneSet object that contains the down-regulated genes of the TGFb-induced EMT gene signature that was derived by (Foroutan et al,2017), using two meta-analysis techniques. The gene signature contains an up-regulated gene set (up-set) and a down-regulated gene set (down-set). Please refer to the vignettes for the steps to acquire the exact data object.

Usage

```
tgfb_gs_dn
```

Format

A GeneSet object

Source

[Foroutan et al,2017](#)

References

Foroutan, Momeneh, Joseph Cursons, Soroor Hadiyah-Zadeh, Erik W Thompson, and Melissa J Davis. 2017. "A Transcriptional Program for Detecting Tgfbeta-Induced Emt in Cancer." Molecular Cancer Research. American Association for Cancer Research. doi:10.1158/1541-7786.MCR-16-0313.

See Also

"GeneSet", [tgfb_gs_up](#)

tgfb_gs_up	<i>Gene set of up-regulated genes for the TGFb-induced EMT gene signature</i>
------------	---

Description

A GeneSet object that contains the up-regulated genes of the TGFb-induced EMT gene signature that was derived by (Foroutan et al.,2017), using two meta-analysis techniques. The gene signature contains an up-regulated gene set (up-set) and a down-regulated gene set (down-set). Please refer to the vignettes for the steps to acquire the exact data object.

Usage

```
tgfb_gs_up
```


Format

A GeneSet object

Source

[Foroutan et al,2017](#)

References

Foroutan, Momeneh, Joseph Cursons, Soroor Hadiyah-Zadeh, Erik W Thompson, and Melissa J Davis. 2017. "A Transcriptional Program for Detecting Tgfbeta-Induced Emt in Cancer." Molecular Cancer Research. American Association for Cancer Research. doi:10.1158/1541-7786.MCR-16-0313.

See Also

["GeneSet",tgfb_gs_dn](#)

toy_expr_se

A toy gene expression dataset of two samples

Description

A toy dataset consisting of 2 samples with the expression values of 20 genes. The data was created by sampling 2 samples and 20 genes from the dataset by Foroutan et al, 2017.

Usage

toy_expr_se

Format

A SummarizedExperiment of 2 samples each with 20 genes

D_Ctrl_R1 a control sample

D_TGFb_R1 a TGFb-treated sample

Source

[Foroutan et al.,2017](#)

References

Foroutan, Momeneh, Joseph Cursons, Soroor Hadiyah-Zadeh, Erik W Thompson, and Melissa J Davis. 2017. "A Transcriptional Program for Detecting Tgfbeta-Induced Emt in Cancer." Molecular Cancer Research. American Association for Cancer Research. doi:10.1158/1541-7786.MCR-16-0313.

toy_gs_dn

A gene set object of down-regulated genes for the toy dataset

Description

A GeneSet object with 5 genes randomly selected from the toy dataset. These genes are independent of those in [toy_gs_up](#)

Usage

```
toy_gs_dn
```

Format

A GSEABase::GeneSet object with 5 genes

See Also

"GeneSet", [toy_expr_se](#), [toy_gs_up](#)

toy_gs_up

A gene set object of up-regulated genes for the toy dataset

Description

A GeneSet object with 5 genes randomly selected from the toy dataset. These genes are independent of those in [toy_gs_dn](#)

Usage

```
toy_gs_up
```

Format

A GeneSet object with 5 genes

See Also

"GeneSet", [toy_expr_se](#), [toy_gs_dn](#)

Index

* datasets

scoredf_ccle_epi, 18
scoredf_ccle_mes, 18
scoredf_tcga_epi, 19
scoredf_tcga_mes, 20
tgfb_expr_10_se, 23
tgfb_gs_dn, 24
tgfb_gs_up, 24
toy_expr_se, 25
toy_gs_dn, 26
toy_gs_up, 26

* internal

generateNull_intl, 5
plotRankDensity_intl, 13

BiocParallel::bplapply(), 2, 5

generateNull, 2
generateNull(), 6, 11
generateNull, GeneSet, ANY-method
(generateNull), 2
generateNull, GeneSet, GeneSet-method
(generateNull), 2
generateNull, vector, ANY-method
(generateNull), 2
generateNull, vector, vector-method
(generateNull), 2
generateNull_intl, 5
GeneSet, 9, 14, 22, 24–26
getPvals, 6
getPvals(), 11
getStableGenes, 7, 17, 22

multiScore, 8
multiScore, matrix, GeneSetCollection, GeneSetCollection-method
(multiScore), 8
multiScore, matrix, GeneSetCollection, missing-method
(multiScore), 8
multiScore, matrix, list, list-method
(multiScore), 8
multiScore, matrix, list, missing-method
(multiScore), 8

plotDispersion, 10

plotNull, 11
plotRankDensity, 12
plotRankDensity, ANY, GeneSet, GeneSet-method
(plotRankDensity), 12
plotRankDensity, ANY, GeneSet, missing-method
(plotRankDensity), 12
plotRankDensity, ANY, vector, missing-method
(plotRankDensity), 12
plotRankDensity, ANY, vector, vector-method
(plotRankDensity), 12
plotRankDensity_intl, 13
plotScoreLandscape, 14
plotScoreLandscape(), 16
projectScoreLandscape, 15

rank, 9, 17, 22
rankGenes, 16, 22
rankGenes(), 4, 5, 8, 9, 12–14, 20, 21
rankGenes, data.frame-method
(rankGenes), 16
rankGenes, DGEList-method (rankGenes), 16
rankGenes, ExpressionSet-method
(rankGenes), 16
rankGenes, matrix-method (rankGenes), 16
rankGenes, SummarizedExperiment-method
(rankGenes), 16

scoredf_ccle_epi, 18, 19
scoredf_ccle_mes, 18, 18
scoredf_tcga_epi, 19, 20
scoredf_tcga_mes, 19, 20
simpleScore, 9, 17, 20
simpleScore(), 6, 8, 10, 11, 18–20
simpleScore, matrix, GeneSet, GeneSet-method
(simpleScore), 20
simpleScore, matrix, GeneSet, missing-method
(simpleScore), 20
simpleScore, matrix, vector, missing-method
(simpleScore), 20
simpleScore, matrix, vector, vector-method
(simpleScore), 20
singscore, 23

tgfb_expr_10_se, 23

tgfb_gs_dn, [24](#), [25](#)
tgfb_gs_up, [24](#), [24](#)
toy_expr_se, [25](#), [26](#)
toy_gs_dn, [26](#), [26](#)
toy_gs_up, [26](#), [26](#)